Cloud Intrusion Detection based on Change Tracking and a New Benchmark Dataset

by

Abdulaziz Aldribi

B.Sc. of Computer Science, King Abdulaziz University, 2004

M.Sc. of Computer Security, University of Birmingham, 2011

A Dissertation Submitted in Partial Fulfillment of the
Requirements for the Degree of

DOCTOR OF PHILOSOPHY

in the Department of Electrical and Computer Engineering

© Abdulaziz Aldribi, 2018

University of Victoria

All rights reserved. This dissertation may not be reproduced in whole or in part, by
photocopying or other means, without the permission of the author.

Cloud Intrusion Detection based on Change Tracking and a New Benchmark Dataset

by

Abdulaziz Aldribi

B.Sc. of Computer Science, King Abdulaziz University, 2004

M.Sc. of Computer Security, University of Birmingham, 2011

Supervisory Committee

Prof. Issa Traore, Supervisor

(Department of Electrical and Computer Engineering, University of Victoria)

Prof. Fayez Gebali, Departmental Member

(Department of Electrical and Computer Engineering, University of Victoria)

Prof. Jianping Pan, Outside Member

(Department of Computer Science)

ABSTRACT

The adoption of cloud computing has increased dramatically in recent years due to attractive features such as flexibility, cost reductions, scalability, and pay per use. Shifting towards cloud computing is attracting not only industry but also government and academia. However, given their stringent privacy and security policies, this shift is still hindered by many security concerns related to the cloud computing features, namely shared resources, virtualization and multi-tenancy. These security concerns vary from privacy threats and lack of transparency to intrusions from within and outside the cloud infrastructure. Therefore, to overcome these concerns and establish a strong trust in cloud computing, there is a need to develop adequate security mechanisms for effectively handling the threats faced in the cloud. Intrusion Detection Systems (IDSs) represent an important part of such mechanisms. Developing cloud based IDS that can capture suspicious activity or threats, and prevent attacks and data leakage from both inside and outside the cloud environment is paramount. However, cloud computing is faced with a multidimensional and rapidly evolving threat landscape, which makes cloud based IDS more challenging. Moreover, one of the most significant hurdles for developing such cloud IDS is the lack of publicly available datasets collected from a real cloud computing environment. In this dissertation, we introduce the first public dataset of its kind, named ISOT Cloud Intrusion Dataset (ISOT-CID), for cloud intrusion detection. The dataset consists of several terabytes of data, involving normal activities and a wide variety of attack vectors, collected over multiple phases and periods of time in a real cloud environment. We also introduce a new hypervisor-based cloud intrusion detection system (HIDS) that uses online multivariate statistical change analysis to detect anomalous network behaviors. As a departure from the conventional monolithic network IDS feature model, we leverage the fact that a hypervisor consists of a collection of instances, to introduce an instance-oriented feature model that exploits individual as well as correlated behaviors of instances to improve the detection capability. The proposed approach is evaluated using ISOT-CID and the experiments along with results are presented.

Contents

Supervisory Committee	ii
Abstract	iii
Table of Contents	iv
List of Tables	ix
List of Figures	xi
List of Abbreviations	xiii
Acknowledgements	xv
Dedication	xvi
1 Introduction	1
1.1 Context	1
1.2 Research Problem	1
1.3 Proposed Approach	4
1.4 Research Contributions	5
1.5 List of Publications from this Dissertation	8
1.6 Dissertation Organization	9
2 State of the Art in Cloud Computing Architectures and Security Issues	11
2.1 Background on Cloud Computing Models and Architectures	11
2.1.1 Cloud Computing Characteristics	11
2.1.2 Cloud Computing Architecture	12
2.1.3 Cloud Computing Service Models	12
2.1.4 Cloud Computing Deployment Models	13

2.2	Cloud Computing Security Challenges	14
2.2.1	Cloud Security Issues Based on Different Layers	15
	Virtualization Level Security Issues	15
	Data Storage Level Security Issues	16
2.3	Background on Cloud Intrusion Detection Systems	18
2.3.1	Overview	18
2.3.2	Detection Approaches	19
2.3.3	Deployment Models	21
2.3.4	Deployment Environments	22
2.4	Summary	23
3	Related Work	24
3.1	On Cloud Intrusion Datasets	25
3.1.1	Cloud Intrusion Detection Dataset (CIDD)- based on (DARPA) dataset 25	
3.1.2	Cloud Storage Datasets	25
3.1.3	Cloud Intrusion Detection Datasets (CIDD)- based on simulation . .	25
3.1.4	Denial of Service Attack Dataset	26
3.1.5	Limitations and Deficiencies of Current Datasets	26
3.2	On Cloud Computing Intrusion Detection Systems	27
3.3	Summary	28
4	ISOT-CID: Collection Environment and Procedure, and Data	31
4.1	Overview	31
4.2	Target Network Architecture	33
4.2.1	OpenStack-based Production Cloud Environment	33
4.2.2	ISOT-CID Collection Environment	34
4.3	Data Collection Procedure	35
4.4	Attack Scenarios	41
4.4.1	Inside Attack Scenarios	42
	Revealing User's Credentials	43
	Extracting User's Confidential Data	43
	Back Door and Trojan Horse	43
	Compromised Instance and Stepping Stone Activities	44
4.4.2	Outside Attack Scenarios	44

	Masquerade Attack	45
	Denial of service (DoS) Attack	46
	Unauthorized Cryptomining	48
4.4.3	Attack Time and Locations	49
4.5	Collected Data	50
4.5.1	System Calls	50
4.5.2	Memory Dump	51
4.5.3	Event Logs	51
	Windows Event Logs	52
	Unix Logs	52
4.5.4	Resource Utilization	52
4.5.5	Network Traffic	53
4.5.6	Excerpt From the Dataset	55
4.6	Summary	55
5	Feature Model	61
5.1	Instance-Oriented Feature Model	62
5.2	Anomalous Behavior Characterizations	64
5.3	Instance-oriented Feature Extraction	65
5.3.1	Frequency Features	66
5.3.2	Entropy Features	68
5.3.3	Load Features	69
5.4	Computing the features	70
5.5	Dimensionality Reduction	71
5.6	Special relational IP feature transformations	71
5.7	Unstructured nature of TCPdumps	73
5.8	Summary	74
6	Cloud Intrusion Detection Algorithms	75
6.1	Change Point Analysis	75
6.2	Change Point-based Intrusion Detection	77
6.3	Intrusion Decision	78
6.4	Summary	82
7	Experiments and Results	83
7.1	Preliminary Experiments	83

7.1.1	Sample Attack Scenario Details	85
7.1.2	Detection Using Chunking Scheme	85
7.1.3	Detection Using Rolling Scheme	86
7.1.4	Comparison and Discussion	88
7.2	Evaluation Metrics	92
7.3	Evaluation Results	92
7.4	Summary	95
8	Conclusion	96
8.1	Contributions Summary	96
8.2	Future Work	98
	Bibliography	99
A	Documentation for the Benchmark Dataset for Cloud Intrusion Detection (ISOT-CID)	114
A.1	Phase One	118
A.1.1	Inside Attack Scenarios	118
	Revealing User's Credentials	121
	Extracting User's Confidential Data	121
	Back Door and Trojan Horse	121
A.1.2	Outside Attack Scenarios	122
	Attack Scenarios for Day 1, 2016-12-09	122
	Network Statistics and Labelling for Day 1, 2016-12-09	126
	Attack Scenarios for Day 2, 2016-12-15	128
	Network Statistics and Labelling for Day 2, 2016-12-15	130
	Attack Scenarios for Day 3, 2016-12-16	134
	Network Statistics and Labelling for Day 3, 2016-12-16	136
	Attack Scenarios for Day 4, 2016-12-19	138
	Network Statistics and Labelling for Day 4, 2016-12-19	140
A.2	Phase Two	143
A.2.1	Day 1, 2018-02-16	144
	Attack Scenarios for Day 1	144
	Network Statistics and Labelling for Day 1	145
A.2.2	Day 2, 2018-02-19	155
	Attack Scenarios for Day 2	155

	Network Statistics and Labelling for Day 2	156
A.2.3	Day 3, 2018-02-20	163
	Attack Scenarios for Day 3	163
	Network Statistics and Labelling for Day 3	165
A.2.4	Day 4, 2018-02-21	172
	Attack Scenarios for Day 4	172
	Network Statistics and Labelling for Day 4	173
A.2.5	Day 5, 2018-02-23	180
	Attack Scenarios for Day 5	180
	Network Statistics and Labelling for Day 5	182

List of Tables

Table 3.1	Summary of related works	30
Table 4.1	Instances specifications.	37
Table 4.2	Hypervisors specifications.	37
Table 4.3	Attack types in the ISOT-CID	57
Table 4.4	Phase 1: Network traffic distribution	58
Table 4.5	Phase 2: Network traffic distribution	58
Table 4.6	Phase 1: Network traffic details	58
Table 4.7	Phase 2: Network traffic details	58
Table 5.1	The raw features extracted from the hypervisor network traffic	64
Table 5.2	Description of <i>in</i> frequency features	67
Table 5.3	Description of <i>out</i> frequency features	68
Table 7.1	Supercomputing machine specifications	84
Table 7.2	Multiple change points detected using E-Div for VM8 with Riemann chunking scheme	86
Table 7.3	Change points detected when using rolling and E-Div with different offsets	87
Table 7.4	Estimated detection times for specific attacks with different offsets when using rolling and E-Div	91
Table 7.5	Phase 1 detection results	93
Table 7.6	Phase 2 detection results Note: The (-) sign represents the effectiveness values that cannot be obtained due to the observations being either all normal or all malicious for corresponding days.	94
Table 7.7	Global detection results for all nodes	95
Table A.1	Attack types in the ISOT-CID	119
Table A.2	Phase 1: Network traffic distribution	120
Table A.3	Phase 2: Network traffic distribution	120

Table A.4 Phase 1: Network traffic details	120
Table A.5 Phase 2: Network traffic details	120
Table A.6 Attack scenario steps for day 1	122
Table A.9 Attack scenario steps for day 2	128
Table A.12 Attack scenario steps for day 3	134
Table A.15 Attack scenario steps for day 4 part 1	138
Table A.16 Attack scenario steps for day 4 part 2	139
Table A.19 Attack scenario steps for day 1	144
Table A.22 Attack scenario steps for day 2	155
Table A.25 1st attack scenario steps for day 3	163
Table A.26 2nd attack scenario steps for day 3	164
Table A.29 Attack scenario steps for day 4	172
Table A.32 1st attack scenario steps for day 5 conducted by attacker A.	181
Table A.33 2nd attack scenario steps for day 5 conducted by attacker B.	181

List of Figures

Figure 2.1	Cloud Computing Service and Deployment models.	13
Figure 4.1	Compute Canada West Cloud OpenStack deployment architecture. . .	35
Figure 4.2	ISOT-CID project environment	36
Figure 4.3	ISOT-CID collection elements.	39
Figure 4.4	1st attack round for inside and outside attacks in Day 1 (Phase 1). . .	47
Figure 4.5	Sample attack scenario in ISOT-CID in Phase 2 (over several days) .	49
Figure 4.6	Summary of the first and second attack scenarios for inside and out- side attacks.	50
Figure 4.7	Traffic flow within one of the hypervisors (Phase 1 - Day 1)	54
Figure 4.8	Sample traffic flow for different VMs (Phase 1 - Day 1)	55
(a)	VM7	55
(b)	VM9	55
(c)	VM8	55
(d)	VM10	55
Figure 4.9	Excerpt from the dataset: sample virtual memory statistics and the CPU and disk utilizations for one of the hypervisors.	59
Figure 4.10	Excerpt from the dataset: sample open files, network connections and TCPdump traces for an hypervisor.	60
Figure 5.1	Riemann approaches	71
(a)	Riemann approach	71
(b)	Riemann chunking scheme	71
(c)	Riemann rolling scheme	71
Figure 5.2	Relational Transformation.	73
Figure 7.1	Sample attack scenario in ISOT-CID in Phase 1 (Day 1)	83
Figure 7.2	First attack round for inside and outside attacks (Phase 1 - Day 1) . .	84
Figure 7.3	Building the baseline for VM8 with 180 normal samples	87

Figure 7.4	Comparison between two offsets for Riemann rolling when the E-Div settings are $m = 500$ and $k = 100$ for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks.	88
(a)	Riemann rolling offset 0.05	88
(b)	Riemann rolling offset 0.1	88
Figure 7.5	Comparison between three E-Div settings for Riemann rolling when the offset is 0.5 for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks. . .	89
(a)	$m=30, k = NULL$	89
(b)	$m=40, k = NULL$	89
(c)	$m=50, k=100$	89
Figure 7.6	Comparison between two E-Div settings for Riemann rolling when the offset is 1.5 for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks. . .	90
(a)	$m=30, k = NULL$	90
(b)	$m=30, k = 100$	90

List of Abbreviations

ARPANET	– Advanced Research Projects Agency Network
C&C	– Command and Control
CAIDA	– Centre for Applied Internet Data Analysis
CID	– Cloud Intrusion Dataset
CIDD	– Cloud Intrusion Detection Dataset
CSA	– Cloud Security Alliance
CSP	– Cloud Service Provider
DARPA	– Defense Advanced Research Project Agency
DDoS	– Distributed Denial of Service
DoS	– Denial of Service
DR	– Detection Rate
FN	– False Negative
FP	– False Positive
FPR	– False Positive Rate
HA	– High-Availability
HIDS	– Hypervisor-based IDS
IaaS	– Infrastructure as a Service
IDS	– Intrusion Detection System
IP	– Internet Protocol
ISOT	– Information security and object technology
KDD	– Knowledge Discovery in Databases
NIDS	– Network-based IDS
OSs	– Operating Systems
PaaS	– Platform as a Service
PCA	– Principal Component Analysis
pcap	– Packet Capture
POP	– Points of Presence
QoS	– Quality of Service
R2L	– Remote-to-Local
SaaS	– Software as a Service
SQL	– Structured Query Language
SSH	– Secure Shell

SVM	– Support Vector Machines
TN	– True Negatives
TP	– True Positive
UDP	– User Datagram Protocol
VIDS	– VM-based IDS
VM	– Virtual Machine
VMM	– Virtual Machine Monitor
VPC	– Virtual Private Cloud
XSS	– Cross-site Scripting

ACKNOWLEDGEMENTS

In the name of **ALLAH**, the Most Gracious, the Most Merciful. All the praise and thanks is due to Allah, the Lord of al-amin.

Above all, I owe it all to Almighty **ALLAH** for giving me the opportunity, granting me the knowledge and patience to undertake this PhD research and enabling me to completed.

I would like to express my sincere gratitude to the people around me that without them it would not have been possible to obtain this doctoral thesis without their help and support.

I would like to acknowledge the most important people in my life like my family. I would like to thank my beloved **Parents**, **Sisters** and **Brothers** whose love, support and prayers are with me in whatever I pursue. Although they are so far away there has never been a time when I have felt alone. A special thanks to my beloved wife, **Afnan** for her encouragement, support, sacrifices and great patience at all times during my PhD. Thank you so much to my son, **Saleh**, daughters; **Atheb** and **Wid**, for they have inspired me in their own ways to finish my dissertation. I could not imagine doing my PhD without them; you really gave me the reason to continue.

Special mention goes to my supervisor **Prof. Issa Traore** for his valuable guidance, scholarly inputs and consistent encouragement I received throughout my PhD study. I would also like to thank my **Supervisory committee members**, Prof. Fayez Gebali, Prof. Jianping Pan and Dr. Natalia Stakhanova for serving as my supervisory committee. I also want to thank you for your helpful comments, suggestions and guidance. My sincere gratitude and appreciation are for **Compute Canada** for given me the opportunity to collect the new cloud intrusion dataset. I would especially like to thank Belaid Moa, Kim Lewall, Ryan Enge and Eric Kolb, for their help in preparing the experimental set-up utilized in this study. I gratefully acknowledge my past and present colleagues and friends in the ISOT lab and my **Officemates** of many years: Sherif Saad, Marcelo Brocardo, Faisal Alshinqity and Paulo Quinan.

Last but not least, special thanks to the **Qassim University** for giving me the opportunity to carry out my doctoral research and for their financial support.

For all of you, without your support it would have been a dream which became a reality today and I finished my Ph.D. Thank you ALL!

“My Lord, keep me thankful for the blessing You have bestowed on me and on my parents, and keep me acting rightly, pleasing You, and admit me, by Your mercy, among Your servants who are righteous.”(Surah an-Naml, 27: 19)

Abdulaziz Aldribi

DEDICATION

I dedicate this work to my entire Family.

Chapter 1

Introduction

1.1 Context

Since the 1990s to recent days the Internet has changed the computing world in a dramatic way. It has evolved from the concept of parallel computing to distributed computing, to grid computing and recently to cloud computing. Although the idea of cloud computing has been around for quite some time, it is an emerging field of computer science. Cloud computing has become one of the popular terms in academia and IT industry. The two main characteristics of cloud computing are: on demand service, and flexible cost model that allows users to pay according to their needs. Cloud is just like water, electric, and gas utilities that can be charged according to the amount used. It integrates and offers several shared computational resources to users as a service on demand. Furthermore, the cloud model offers enticing features such as greater scalability, cost reduction, and flexibility. It can provide various levels of services and enable the completion of different tasks over the Internet. These features and services enabled the cloud to gain tremendous popularity in IT. Moreover, in recent years, cloud computing has started becoming a rich data environment and a very important resource; however, it is also attracting sensitive data hunters, that is, “attackers”.

1.2 Research Problem

The growing popularity for cloud computing comes with an increasing level of concern over the security of the cloud computing infrastructure. Shared resources, virtualization and multi-tenancy, which are the essential components of cloud computing, provide a number

of advantages for increasing resource utilization, and on demand elasticity and scalability. However, they raise many security and privacy concerns that affect and delay the wide adoption of the cloud.

Cloud computing is susceptible to traditional IT attacks because it leverages the existing IT infrastructure, operating systems (OSs), and applications. In addition to the conventional threats, cloud computing environments face new security issues as these involve many new technologies that could lead to new forms of exploitation. For instance, virtualization is a core technology used in cloud computing and an essential element for a cloud to achieve its characteristics. In a virtual environment, multiple OSs run at the same time on a single host computer using a hypervisor [123]. The hypervisor, or virtual machine monitor (VMM), is viewed as any other code embedded on the host OS. This code is available at the boot time of the host OS to control multiple guests' OSs. As with any other code, attackers attempt to exploit its vulnerabilities to gain access and control of the legitimate user's virtual machine (VM). Furthermore, a shared resource environment introduces unexpected new types of threats, such as side channel and covert channel attacks. Moreover, if a malicious user installs a hacking tool on a VM, the other VMs and hypervisors can also be attacked and become victims [97]. In addition to introducing threats, a malicious user can leverage the significant amounts of computational resources offered by the cloud to perform attacks, such as scanning the network, botnet, and denial of service (DoS) against the cloud or outside world, causing severe damage. Furthermore, since cloud computing relies on the Internet to operate, the security problems that exist in the Internet are not only found but are also amplified in the cloud.

In a conventional network, an organization has full access to all types of data available within its own security perimeter. In contrast, in the cloud, some of the assets and communications over virtual resources may be encrypted with encryption keys that are fully controlled by the customers. Furthermore, in cloud networks, protected resources and devices are highly dynamic and regularly changing, whereas in conventional networks, the assets under protection are fairly stable. Constant and dynamic reconfiguration and migration of cloud assets pose new challenges that cloud intrusion detection must contend with. In this context, many cloud hosting sites enable their customers to deploy traditional IDSs on Virtual Private Cloud (VPC) gateways and virtual instances. However, those IDSs are limited in focus and cannot detect specific changes in the cloud hosting environment. For example, the IDS that is deployed at the edge of the cloud will fail to detect the attacks that occur between virtual models (i.e., VM-VM) or between hypervisor and VM because the communications between them never go outside the physical network.

To address the aforementioned challenges, in addition to common host-based and network-based IDSs found in conventional networks, the cloud introduces two more IDS models, namely, hypervisor-based and VM-based. A hypervisor-based IDS (HIDS) is deployed at the hypervisor level and relies on hypervisor-level data and communications. A HIDS has a wide visibility of the cloud environment and is capable of collecting information from both VMs and the host at the same time. The data can be collected via both OSs and network traffic. HIDS is privileged due to hypervisor characteristics, which gives it leverage to monitor and analyze information such as system calls, system events, and running processes from the OSs of the VMs and the host machine within the hypervisor (host-based). Furthermore, it can monitor and analyze network communications between VMs (i.e., VM-VM), between VM and hypervisor, and between the cloud environment and the outside (network-based).

While traditional IDS can address some of the cloud security threats, they are severely limited not only by the specificity of some of the threats involved but also by the regulatory, legal, and architectural considerations unique to cloud computing [116, 22]. Therefore, several research proposals have been recently published on developing cloud-specific intrusion detection systems, also referred to as *cloud IDS*. However, important gaps still remain in the research literature. Compared to conventional computing, the cloud computing threat landscape is more complex due to the huge volume of data and highly heterogeneous technological fabric of cloud environments. Furthermore, the cloud threat landscape is inherently multidimensional. Cloud environments not only face multistage attacks (as in conventional networks), but they also involve a greater likelihood for simultaneous attacks targeting different segments of the cloud, whether these are related or not. In addition, because cloud computing is a fairly recent paradigm, the state of knowledge about cloud vulnerabilities and attack methods is limited and still evolving.

Under this premise, while misuse detection approaches that rely on signatures of known intrusion patterns are useful, anomaly detection is paramount in dealing with the evolving cloud threat landscape. However, although a few cloud anomaly detectors have been proposed, most of the existing cloud IDSs rely predominantly on signature-based detection.

Developing such systems, however, is very challenging as cloud IDS researchers are faced with one of the greatest hurdles: the lack of publicly available datasets collected from a real cloud computing environment, which is a big hindrance for developing and testing realistic detection models. Most existing projects and works on cloud IDS use proprietary

datasets, which they do not share with others. Sometimes the closeness of such datasets is justified by privacy concerns. However, this makes it difficult for other researchers to leverage or replicate the published results, hindering advances in cloud IDS development. Furthermore, some of the datasets used in cloud IDS development are synthetic datasets from simulated clouds or conventional intrusion detection datasets, which obviously miss important characteristics of real-world cloud environments.

The goal of the thesis is to tackle and address effectively some of the aforementioned issues.

1.3 Proposed Approach

Our approach relies on the premise that any intrusion attempt, successful or not, creates a footprint on the targeted environment. Such a footprint creates some change in the environment, which, depending on its intensity, can be measured using statistical models. This requires capturing the system attributes (characteristics or features) that may convey the aforementioned change. Several common idiosyncrasies of intrusive events can help uncover those attributes.

Contrary to popular belief, most hackers are not professionals, and there is a wide spectrum of skill levels among the hacker population. Consequently, the hacking process is often messy and therefore creates a rich data trail. In addition because hacking is more art than science and is strongly opportunistic, the sessions typically involve a significant number of trial and error attempts.

Furthermore, automation plays a significant role in the conduct of the attack, especially as the goal of typical hackers is to maximize gains by increasing scalability and speeding the attack process. The mechanical nature of attack automation creates some patterns in the generated data that potentially could be captured through statistical analysis.

The aforementioned idiosyncrasies are amplified in cloud computing due to the larger and more attractive attack surface that it represents. Our proposed detection model uses multivariate sequential change-point detection to identify malicious anomalous behaviors. Baselineing based on gradient descent is used to tune the change detection parameters and rely only on normal samples. Hence, with no prior knowledge of previous attack patterns, our proposed detection approach is able to detect malicious anomalous behaviors, which is a good indicator of its potential to detect novel cloud-based network attacks not seen before.

1.4 Research Contributions

Contribution 1 A New Benchmark Dataset for Cloud Intrusion Detection

Developing cloud based IDS that can capture suspicious activity or threats, and prevent attacks and data leakage from both inside and outside the cloud environment is paramount. One of the most significant hurdles for developing such cloud IDS, to this date, is the lack of publicly available datasets collected from a real cloud computing environment. By reviewing cloud intrusion datasets in the literature, we noticed that most of the datasets are not suitable and do not reflect the real cloud environment. For example, they are limited to one data source type that is only collected from the host side, and do not include any data collected at the hypervisor level, instances OS level, or internal network traffic. Furthermore, they do not include some attack types that are new and specific to the cloud computing environment. But most importantly, these datasets are not publicly available for researchers to access and use to build, evaluate and compare cloud IDSs. This calls for new datasets that would adequately capture the characteristics of the threat landscape faced by cloud computing. One of the major contributions of this dissertation is introducing a novel labelled real dataset collected from a production cloud environment as an initial response toward addressing such need and paving the way for cloud security communities for more research and finding. It involves multiple attack scenarios, such as masquerade attacks, denial of service, stealth attacks and anomalous user behaviour covering both remote and inside attacks, and attacks originating from within the cloud. It has a mixture of both normal and intrusive activities, and it is labeled. It contains diverse logs and data sources that will enable the development of various intrusion data models, feature sets and analysis models. The dataset was collected over two phases and several days, and involves several hours of attack data, culminating into more than 8 terabytes. The ISOT-CID is an aggregation of different data gathered from a variety of cloud layers, including guest hosts, hypervisors and networks, and it comprises data with different formats and from multiple data sources, including memory dumps, resource (e.g., CPU) utilizations, system call traces, system logs, and network traffic. It is large and diverse enough to accommodate various effectiveness and scalability studies. The purpose of ISOT-CID is the embodiment of a real cloud dataset, it is essentially raw and has not been transformed, manipulated or altered. This is important for the industry and academia towards developing and evaluating realistic intrusion models for cloud computing. Furthermore, it is structured and prepared for the cloud security community, and is available for downloading through ISOT website along with the documentation and metadata files, which explain its production and use in

order to ensure an unambiguous meaning of the data. The ISOT-CID collection environment, procedure and detailed attacks scenarios and data types are presented in Chapter 4. This contribution has been published as a chapter in a book titled as “Cloud Computing for Optimization: Foundations, Applications, and Challenges” by Springer [9].

Contribution 2: A New Feature Extraction Model for Cloud IDS

As a departure from the conventional monolithic network IDS feature model, we leverage the fact that a hypervisor consists of a collection of instances, to introduce our feature model which is the second major contribution of this dissertation. The feature model consists of, a new multidimensional feature space and a new feature extraction model for hypervisor-based cloud intrusion detection called *instance-oriented feature extraction*. The new model leverages the correlated behavior of instances running on a hypervisor to improve cloud feature extraction and anomaly detection capability. Our model involves two stages of feature extraction. An initial feature vector is computed for each individual packet based on the cloud network packet header. Next, we extract a separate feature vector for each packet flow based on the initial feature vectors associated with the packets involved in the flow. Given a set of features, we need a way to compute them based on the observations. Given that each observation is a single packet, computing the flow is statistically meaningless without looking at many observations. Moreover, since a single observation belongs to a correlated stream of packets, it might be useful to group, chunk and compact these observations to produce a summarized data frame with less dependent observations. This compaction of data frames can be done in different ways. By choosing t and δt , we can collect a set of packet flows to study. Depending on the way t and δt are specified, we can gather different packet flows and use various approaches to analyze them. One approach to compute the features is to group them based on one of the fields, for example time. In this dissertation we introduce two approaches, namely *Riemann chunking scheme* and *Riemann rolling scheme*. In the Riemann chunking scheme the time is partitioned into disjoint δt windows and the observations within each window are used to compute the features. The Riemann rolling scheme, instead of taking the window intervals to be disjoint, uses a rolling window with a fixed offset from the start to the end of the data. The Riemann rolling is of course much more general and if the offset is set of the window size δt , we obtain Riemann Chunking. Although the previously defined features could be meaningful, some features may contribute little to the detection process, we use principal component analysis (PCA) to eliminate these features and therefore reduce the dimensions of the defined feature space before further processing. PCA is a nonparametric method that allows

the automatic identification of significant input features that are computationally efficient and effective for real-world cloud IDSs. Therefore, for each flow, only a subset of the components of the feature vector defined previously will be used as input to the detection algorithm. The details of the feature model are provided in Chapter 5. This contribution has been submitted to the IEEE Transactions on Information Forensics & Security and it is currently under review.

Contribution 3: A New Special Relational IP Feature Transformations

The data source of cloud intrusion detection system can be of any kind and can emanate from any element of the cloud, such as audit logs, system calls and network traffic, at any level, including instances, hypervisors and controller nodes. Depending on the data format, we need a way to structure it, especially for unstructured data, and without it we will not be able to proceed further.

The third major contribution of this dissertation is introducing a new special relational feature technique. Looking at the many existing extracted features in the literature, and at the complexity and the ad-hoc nature of implementing them, we introduce relational transformations as an easy declarative paradigm for feature extraction. A *relational transformation* is a relational algebra operator that takes tables (relations) as its input and yields tables (relations) as its output. If the tables are represented as DB tables, then each relational transformation can be expressed as an SQL statement that we run against the tables. This novel framework allows us to combine the realm of feature engineering and the realm of relational algebra/databases to produce extracted features. By doing so, we can even automate the process of generating features instead of relying on the human-fashioned ones. This has the power of being easy to use (as it is declarative) and can implement complex operations in a single statement. To be able to generate meaningful features using relational transformations, we can augment our framework with models that represent the type of data source under consideration. The unreasonable effectiveness of using this paradigm can be seen from a practical example dealing with network traffic as discussed in Chapter 7.

The new special relational feature transformations is described in Chapter 5. This contribution is to be submitted to the International Conference on Intelligent, Secure and Dependable Systems in Distributed and Cloud Environments (ISDDC 2018).

Contribution 4: A New Hypervisor-based Cloud Intrusion Detection Model based on Sequential Change Detection

Detecting changes on the behaviour of cloud computing network traffic presents a few challenges. Firstly, the network traffic for cloud computing is huge by nature, therefore the amount of observations will be very large, that makes storing the data for offline analysis impractical. Secondly, the traffic data consists of a potentially unending sequence of data tuples that stream passing through the hypervisor at a very high rate, and has the potential to behave unexpectedly. Thirdly, detecting the change point on time is crucial for any anomalous network behaviour. Lastly, there may be multiple change points in the data stream, requiring the detector to be continuously running after each change point detection.

The forth major contribution of this dissertation, attempt to overcome these challenges through a new hypervisor-based cloud anomaly detection model that uses multivariate sequential change detection combined with an initial baselining model based on the gradient descent algorithm. Our general approach for hypervisor-based cloud intrusion detection consists of extracting a set of features from the network packet according to the model presented above, and then tracking changes in network behavior through statistical analysis of unlabeled data, upon receiving it, to detect any intrusion buried within the data. We seek a robust change-point detection algorithm that performs sequential change detection and can detect multiple change points in stream data. We derive the baseline model using the gradient descent approach to tune the parameters of the detection algorithm. The anomaly detection model is presented in Chapter 6, this contribution is also presented in the previously mentioned submitted journal paper.

In addition to the above contributions, our preliminary work in the area of cloud computing security yielded two conference papers one published in 2015 IEEE Pacific Rim Conference on Communications, Computers and Signal Processing (PACRIM) [8] and the other in 2015 International Conference on Network and System Security [7], and one chapter in a book titled as “Network and System Security” published by Springer [109].

1.5 List of Publications from this Dissertation

Book Chapters:

- Aldribi A., Traore I., Moa B. (2018) Data Sources and Datasets for Cloud Intrusion Detection Modeling and Evaluation. In: Mishra B., Das H., Dehuri S., Jagadev A. (eds) Cloud Computing for Optimization: Foundations, Applications, and Challenges. Studies in Big Data, vol 39. Springer, Cham.
- Aldribi A., Traore I. (2015) A Game Theoretic Framework for Cloud Security Trans-

parency. In: Qiu M., Xu S., Yung M., Zhang H. (eds) Network and System Security. NSS 2015. Lecture Notes in Computer Science, vol 9408. Springer, Cham.

Journals:

- Aldribi A., Traore I., Moa B. (2018) Hypervisor-Based Cloud Intrusion Detection through Online Multivariate Statistical Change Tracking. In: IEEE Transactions on Information Forensics and Security, May 2018 (under revision).

Conferences:

- Aldribi A., Traore I. "A game theoretic framework for cloud security transparency." International Conference on Network and System Security. Springer, Cham, 2015.
- A. Aldribi, I. Traore and G. Letourneau, "Cloud Slicing a new architecture for cloud security monitoring," 2015 IEEE Pacific Rim Conference on Communications, Computers and Signal Processing (PACRIM), Victoria, BC, 2015.

1.6 Dissertation Organization

The remainder of this dissertation is organized as follows.

Chapter 2 provides a brief background and state of the art in cloud computing architectures and security Issues. We present the cloud characteristics which attract cloud stakeholders. Moreover, we describe the cloud architecture, service, and deployments models. Cloud security issues based on different layers are also discussed in this chapter. Furthermore, overview and background on cloud intrusion detection systems are presented.

Chapter 3 summarizes and discusses related work on cloud computing dataset and on cloud computing intrusion detection systems. A review of the literature on the state of the art on cloud IDS is presented, and the strengths, and limitations and deficiencies of the current works are highlighted.

Chapter 4 presents our new cloud intrusion detection dataset. We describe our data collection approach by presenting the collection environment and procedures. We provide details for both the production cloud environment and the ISOT-CID collection environment. Moreover, this chapter presents the conducted attack scenarios from both

the inside and outside cloud with attack times and locations. Then, description of collected heterogeneous data is given.

Chapter 5 introduces our instance-oriented feature model. We discuss the anomalous behavior characterizations. Then we present our extracted instance-oriented features. Riemann scheme to computing features along with features dimensionality reduction are described. Moreover, we illustrate the new special relational feature transformations.

Chapter 6 introduces our cloud intrusion detection algorithms. It starts with a brief introduction on change point analysis. After that, the change point-based intrusion detection with intrusion decision are presented.

Chapter 7 presents a series of experiments to evaluate our proposed cloud intrusion detection model. We discuss the preliminary experiments and then compare between results obtained from chunking and rolling schemes. Moreover, we analyze and discuss the overall results obtained for our cloud intrusion detection model.

Chapter 8 concludes the dissertation by highlighting the overall contributions of the research. Moreover, it provides a direction for future works.

Chapter 2

State of the Art in Cloud Computing Architectures and Security Issues

This chapter presents an overview of the state of the art in cloud computing architectures and underlying security issues. We provide background information on cloud computing, various types of cloud environments, cloud service models and cloud computing deployment models. Furthermore, we discuss the challenges that cloud computing faces and link them to different cloud layers. Also, this chapter provides background on cloud intrusion detection systems. The detection approaches and the deployment models are discussed, and the distinction between cloud computing environment and conventional network environment is clarified.

2.1 Background on Cloud Computing Models and Architectures

2.1.1 Cloud Computing Characteristics

The idea of cloud computing can be traced back to 1969. In fact, Leonard Kleinrock [25], one of the chief scientists of the original Advanced Research Projects Agency Network (ARPANET) project that seeded the Internet, envisioned the spread of ‘computer utilities’, similar to that of the electric and telephone utilities. Nowadays, cloud computing has become a trend in IT, and is able to move computing and data away from desktop, portable PCs and dedicated remote servers into a large number of distributed and shared computers. By doing so, the customers do not need to own the hardware or the infrastructure required

to offer their services. They free themselves from dealing with the infrastructure, its installation and maintenance, and focus on developing their services on a shared infrastructure offered by another party in a pay-as-you-use manner. This paradigm also solves the limitations in storage, memory, computing power and software on desktops and portable PCs.

In cloud computing, data, applications or any other services are accessed by users through a browser or a terminal regardless of the device used and its location. A key characteristic of the cloud is its large scale. From the customer perspective, the cloud is of unlimited resources and should be ready to satisfy their computational needs no matter how big they are. Therefore, cloud providers have a very large number of servers to accommodate user requests. The other key characteristic of cloud computing is virtualization, which allows the cloud to achieve its agility and flexibility by “segmenting” the shared resources and running any operating system on them. This makes it easy for the cloud customers to offer their heterogeneous services on the virtualized infrastructure without worrying about the specificity of the underlying hardware.

2.1.2 Cloud Computing Architecture

Looking at the literature, there is no standardized or universal cloud architecture reference model available. The cloud computing industry and academia are working in parallel to define and standardize reference models, frameworks and architectures for cloud computing [48]. Therefore, cloud reference models are in the development stage, and are expected to stay that way as long as the cloud computing models are evolving. According to [26], Forrester Research was able to count more than 75 different parties working on cloud standards in 2010. Today, the number of industry and academia involved has clearly increased significantly. From the literature, however, cloud computing architectures are better classified by service and deployment models. In the next sections most common cloud computing service and deployment models are discussed.

2.1.3 Cloud Computing Service Models

Cloud service models try to classify “anything” providers offer as a service (XaaS), where X means any service (e.g., infrastructure, software, storage). Cloud service models are typically classified as: *Infrastructure as a Service* (IaaS), *Platform as a Service* (PaaS) and *Software as a Service* (SaaS). These three models (depicted in Fig. 2.1) are the basis of all services provided by cloud computing. In IaaS, the customers get access to the infrastructure to run and manage their own operating systems and applications. However,

Figure 2.1: Cloud Computing Service and Deployment models.

they do not control the underlying infrastructure, and can typically only launch virtual machines with pre-specified flavors and operating systems. PaaS provides a computing environment on the cloud infrastructure to the customers to create and control their own applications by using programming languages and runtime tools offered and supported by the PaaS provider. The customers do not, however, manage or control the operating systems or the underlying cloud infrastructure. In SaaS, a vendor offers an instance of a software application as a service accessible via an Internet browser. The service provider hosts the software on the SaaS environment so that the customers do not have to install, maintain and run the software on their own resources. By doing so, the customers are only concerned with using it and, therefore, benefit from reduced software purchases by on demand pricing.

It is worth emphasizing that there are other proposed cloud service models including Storage as a Service, Hardware as a Service, Data as a Service, and Security as a Service.

2.1.4 Cloud Computing Deployment Models

Based on the NIST definition framework [92], there are four main cloud computing deployment models. These models are classified as public, private, community, and hybrid deployments as shown in Fig. 2.1.

In a *public cloud*, the pool of resources owned by the cloud provider are available to and shared among all the customers. They can rent parts of the resources and can typically scale their resource consumption according to their demands [111, 127]. Since multiple customers are sharing the resources, the major challenges facing the public cloud are security, regulatory compliance and Quality of Service (QoS) [21]. A *private cloud*, also known as *internal cloud*, is a dedicated cloud serving only the users within a single organization. It relies on internal data centers of an organization not made available to the general public, whereby all resources are reserved to the organization's private use. Although the private clouds are more expensive, they are more secure than the public clouds [16, 141, 146]. Moreover, the compliance and QoS are under the control of the organization [62, 148]. A *hybrid cloud* is a combination of public and private clouds, and tries to address their limitations while maintaining their features [119, 136]. The main purpose of a hybrid cloud is usually to provide extra resources in cases of high demands, for instance, to enable migrating some computation tasks from a private to a public cloud [147, 148]. A *community cloud* is similar to a private cloud with the particular characteristic of being shared by multiple organizations, usually belonging to a specific community [111, 15, 136].

2.2 Cloud Computing Security Challenges

Security concerns are inherent in cloud computing and are delaying its adoption. In fact, when customers move their information to a cloud infrastructure owned by another party, there is a high risk of losing full control over their data as well as a potential leakage of their private information as the resources are not only owned by someone else but also shared with many unknown users. Moreover, when running a data processing service on the cloud (via IaaS or PaaS), the provider can obtain full control on the processes belonging to the service and, therefore, compromise its integrity [59].

Since the cloud computing system relies on the Internet to operate, the security problems that affect the Internet can not only be found but are also amplified in the cloud computing environments. Moreover, given that the cloud computing leverages the existing IT infrastructure, operating systems and applications, it is susceptible to the traditional IT attacks as well. In fact, almost all existing attacks could target cloud-based infrastructure. Moreover, cloud computing systems may face new security issues as they combine many new technologies that lead to new exploits such as, cross-virtual machines exploits, and inter-processes and cross-application vulnerability attacks [49].

There are many academic institutions, research organizations, cloud vendors and prod-

uct development enterprises working on different cloud computing security issues and their solutions. From the literature, these issues are classified into various categories based on different perspectives. For example, D. Högberg [53] pointed out that the cloud computing security issues can be divided into two broad categories: security issues faced by cloud providers including SaaS, PaaS and IaaS providers, and security issues faced by their customers. The European Network and Information Security Institute (ENISA), which developed a detailed review of cloud computing security, classified these issues into three categories: Organizational, Technical and Legal. The Cloud Security Alliance (CSA) identified 15 areas of concerns and grouped them into three general areas: Compliance, Legal, Security and Privacy Issues [11]. Amandeep and Sakshi [130] classified the cloud computing security issues based on the delivery and deployment model of the cloud. Other researchers categorized security issues based on the different layers involved in a cloud infrastructure, which are application level, network level, virtualization level, data storage level, authentication and access control level, trust level, compliance level, and audit and regulations level [97]. Some of the security issues from the above classification will be highlighted next.

2.2.1 Cloud Security Issues Based on Different Layers

Virtualization Level Security Issues

Virtualization is a core technology in cloud computing and an essential element for a cloud to achieve its characteristics, especially scalability, location independence, and resource pooling. In a virtual environment, multiple Operating Systems (OSs) run at the same time on a single host computer using a hypervisor (also called Virtual Machine Monitor (VMM)) [123], and physical servers contain multiple virtualized servers on which several virtual machine instances may be running [97, 77].

A major function of the virtualization layer is to ensure that different Virtual Machine (VM) instances running on a same physical machine are logically but fully isolated from each other. However, the isolation technologies that the current VMMs offer are not perfect, especially with the full access and control the administrators have on host and guest operating systems. This leads to many security issues related to virtualization [143].

In cloud computing, there are mainly three types of virtualization: OS level virtualization, application-based virtualization, and hypervisor-based virtualization. In the OS level virtualization, a hosting OS can run multiple guest OSs and has visibility of and control over each guest OS. In such a configuration, if an attacker compromises the host OS, the

entire set of guest OSs could be controlled by that attacker. Bluepill, SubVirt, and DKSM are some well-known attacks for such a configuration and it is still an open problem to prevent such threats [97]. In the application based virtualization, virtualization is only enabled at the top layer of the host OS, and each VM has its specific guest OS and related applications. This kind of virtualization also suffers from the same vulnerabilities as in the traditional OS case.

Hypervisor or virtual machine monitor (VMM) is viewed as any other code embedded on the host OS. Furthermore, this code is available at boot time of the host OS to control multiple guest OSs. As with any other code, it can harbour vulnerabilities that attackers can exploit. For instance, cross VM side-channel and denial of service (DoS) attacks can take advantage of the hypervisor to compromise the guest OSs.

However, as mentioned earlier, vulnerabilities in a hypervisor allow a malicious user to gain access and control of the legitimate user's virtual machine. Furthermore, a shared resource environment introduces unexpected side channel and covert channel attacks. An attacker if successful in neighboring a target can then use various methods for intercepting data being sent and received from the other resources [97].

The cloud can also be overloaded when trying to serve a huge number of requests, which can ultimately lead to DoS or distributed denial of service (DDoS). This type of attacks usually floods the cloud with many large number of requests via zombies. The DoS attack against BitBucket.org is an excellent example. This attack suspended this web site over 19 hours during a DoS attack on the Amazon Cloud infrastructure [94].

According to [75], if a hacking tool is installed on a virtual machine, the other virtual machines and hypervisors can also be attacked. Hsin-Yi et al. [129] infer that VM hopping is a reasonable threat in cloud computing since it has been shown that an attacker can obtain or determine the IP address using standard customer capabilities. Moreover, because several VMs can run at the same time on the same host, all of them could become victim VMs. VM hopping is thus a crucial vulnerability for PaaS and IaaS infrastructures.

Data Storage Level Security Issues

The security of data on the cloud computing is another important research topic [134, 146]. One of the cloud computing principles is to move and store data in the cloud. Once the data is stored in the cloud, the full control of the data is transferred from the data owner to the hands of cloud computing providers. In addition, the data is moving from a single, private and dedicated tenant to a shared multi-tenant environment where untrusted users

can harbor their VMs. Gaining access to private data in such a shared environment can be very catastrophic if the data storage is not done securely and properly. Therefore, according to [111], data stored in the cloud needs policies for physical, logical and personnel access control.

When the data resides on the cloud and is served from there only, there is a potential security risk that it might not be available, especially when needed the most.

The data security risks on the cloud are rising as the number of parties, devices and applications involved in the cloud infrastructure increases. In the literature, data stored in cloud, data leaks, data remanence, data availability, data location, data privacy and data breaches are examples for data security risks that are still open challenges.

For instance, confidentiality is one of the most difficult aspect of data to guarantee in cloud computing. Compared to the traditional computing, an enterprise has no control over storage and transmission of data once it is in cloud. Therefore, to ensure that the data will not be accessed by unauthorized party, proper encryption techniques should be applied [62]. However, increased number of encryption and decryption operations reduces the application performance and increases the consumption of cloud computing resources [28].

In IaaS, variety of users can access computing resources from a single physical infrastructure. To achieve a proper confidentiality level, it is required to isolate resources among the multiple users and ensure that no user can view the state of the other users' resources [129]. Moreover, since PaaS relies on IaaS virtualization, protecting the state of the resources used by a user from the rest of users is also a security challenge in PaaS.

There are a lot of challenges in a public cloud computing environment to ensure data confidentiality. There are several reasons for that, for example, the needs for elasticity, performance, and fault tolerance lead to massive data duplication and require aggressive data caching, which in turn increase the number of targets that could be attacked by data theft [130].

Given all of the security issues and risks we outlined above, it is clear that cloud security monitoring is of paramount importance to both cloud service provider and cloud service customer. The next section is dedicated to this topic.

2.3 Background on Cloud Intrusion Detection Systems

2.3.1 Overview

The malicious activity “intrusion” is defined as any action that differs from the normal activity of a system and attempts to violate that system security. To distinguish normal activity from malicious activity, it is necessary to detect the intrusion. Intrusion detection can be defined as processes that are developed to identify instances that happen to a system that are noticeably different in their characteristics from the majority of similar normal instances, and rarely appear in total data. The instance could be from sources such as network packets, system calls or system events. Violating any system security can occur using one or all of these instance sources. The instance anomalies can be classified into three different categories [27] as follows:

- **Point Anomalies:** Any single data instance that can be excluded from the entire data with respect to dissimilarity is called a point anomaly. This type of anomaly is considered by the majority of anomaly detection research.
- **Contextual/Conditional Anomalies:** A single data instance is considered a contextual/conditional anomalous data instance if it is determined as an anomaly in some contexts and as normal in others. This characteristic can be used to identify two sets of attributes: contextual attributes and behavioural attributes. The contextual attributes are used to specify the instances context. As an example, in time-series data, time is a contextual attribute that specifies the location of an instance on the entire data sequence. On the other hand, the behavioural attributes are used to specify the instances non-contextual characteristics. For the previous example, the amount of incidents at any time is a behavioural attribute. Therefore, by using the values of the behavioural attributes within a specific context, anomalous behaviour can be determined.
- **Collective Anomalies:** A collective anomaly is defined as when a group of related data instances is anomalous with regard to the complete data set. The single data instances in a collective anomaly may not be considered anomalies by themselves, but since their appearances occur together as a group, it is anomalous.

The occurrence of each of these anomalous instances is different. For example, the occurrence of the point anomalies can be in any data set; on other hand, collective anomalies need a related instance in a data set to occur. In contrast, contextual anomalies rely on

the appearance of context attributes in the data occurring. Therefore, a point anomaly or a collective anomaly can also be a contextual anomaly if the context is considered during analysis.

To protect any system from malicious activity, there is a need to deploy an intrusion detection system. The first attempts in the literature to introduce an IDS go back to Anderson 1980 [13] and Denning's 1987 [39] research papers, and since then the developments in IDS have expanded. IDS was introduced as software or/and hardware, and combined with other protection techniques such as authentication and access control, with the ability to detect actions that bypass these protection techniques. It gathers data from system sources and processes and analyzes them; if an intrusion is present, an IDS will respond by taking action and informing the system administrator. Nowadays, with the increase and advancement in attacks, this has become very challenging. Therefore, the development of an efficient intrusion detection system that can monitor and aid in system protection is of paramount importance.

There are different factors involved in intrusion detection systems that can be used to categorise them. They are: detection approaches (misuse, anomaly and hybrid); where it is deployed (host, network), and the deployment environment (conventional or cloud computing).

2.3.2 Detection Approaches

In general, there are three main approaches used in any intrusion detection system, namely: misuse, anomaly and hybrid (misuse and anomaly) detection approaches.

- **Misuse Detection:** The misuse detection approach matches data from sources such as network traffic or audit trails with the maintained rules of known attack signatures. These rules could be constructed either by using knowledge based approaches (e.g., state transition, signature-based, etc), which contain a database of known attack signatures, or by using machine learning algorithm approaches (e.g., decision tree, multi class support vector machine), which are used to determine user behaviour based on learned normal and suspicious activities [20]. In the literature, there are several works on misuse detection, and the most referenced one is the open source tool Snort [110]. Although misuse detection based approaches are effective for detecting known attacks, they fail to detect attacks whose signatures or patterns are not present in the database (zero day attacks). Moreover, maintaining a regular update for the signatures is not an easy task, especially with a growing number of attacks

being detected. To overcome the misuse detection limitations, anomaly detection approaches are considered.

- **Anomaly Detection:** The anomaly detection approach is based on building models or profiles from the normal behaviour of a user or system learned from the training data. The detector monitors current behaviour, and if it does not fall within expected system behaviours, the activities are flagged up as anomalous behaviour. The assumption behind this approach is that an intrusion will show some deviations from normal behaviour [29]. Therefore, a normal behaviour profile of the system being monitored should be updated regularly, and the system should be trained in it. There are three approaches to generating a behaviour profile for a monitored system for anomaly detection, namely: *statistical-based*, *knowledge-based*, and *machine learning-based* approaches. With respect to the training data, anomaly detection can be characterised into three techniques, namely: *supervised*, *semi-supervised* and *unsupervised anomaly detection*. In supervised anomaly detection, the techniques rely on a labelled training data and test set. The detection algorithm should be trained first with normal and anomaly data, and then tested. In semi-supervised anomaly detection, the algorithm is trained using only normal data and then tested. Unlike supervised anomaly detection, in unsupervised anomaly detection, the techniques do not rely on labelled training data, and the detection algorithm should be able to detect suspicious behaviour without any prior knowledge of normal behaviour. Another classification used for anomaly detection is based on how the anomaly detection technique outputs its result. There are two types of detection result representation, namely: *scores* and *label* [27]. Scoring-based anomaly detection approaches use score ranking to assign a score to each data instance. Then anomalies are chosen by the administrator based on this score. Instead of that, a score threshold could be defined and used to determine the anomalies. On the other hand, label-based anomaly detection approaches present the output as either anomalous or normal. Because of the labelling of data in supervised anomaly detection, label-based techniques are often used. In contrast, score-based techniques are commonly used in semi-supervised and unsupervised anomaly detection approaches.

The main advantage of an anomaly detection approach over misuse detection is the ability to detect new types of malicious activity. However, there is a limitation to anomaly detection in a supervised setting, as if the normal behaviours change slightly, that can be detected as malicious activity and cause a significant number of

false alarms. Therefore, a supervised anomaly detection approach should be regularly retrained and normal behaviour updated, because obtaining a complete scope of normal behaviour during the learning phase is often not an easy task, especially in a dynamic environment (such as cloud computing). Another drawback is that the attacker can evade anomaly detection if they are able to train the detection slowly over time and let the detection system learn about malicious behaviour as normal.

- **Hybrid Detection :** A hybrid detection approach is a combination of two or more of the above intrusion detection approaches (usually misuse and anomaly). The main reason for introducing this detection approach is to try to come up with a robust detection approach that can combine the advantages of each detection approach and eliminate their limitations. As an example, new or unknown malicious behaviours could be detected through anomaly detection approaches, while the misuse detection approaches detect known malicious behaviours. Despite hybrid detection being a good approach to producing a robust detection system, it could diminish the system's performance. Therefore, combining more than one intrusion detection approach to collaborate effectively and efficiently is challenging [106].

2.3.3 Deployment Models

Considering both conventional networking and the cloud computing environment, the deployment of an IDS can be categorised according to the target environment for detection in host-based, network-based and hybrid IDS, which is a combination of host-based and network-based environments. In a cloud computing environment, there are two categories added to the previous one related to virtualisation technology, which are hypervisor-based and virtual machine VM-based.

- **Host-based IDS:** Host-based IDS relies on its monitoring of specific data that is collected from the operating system of the host machine. This collected data contains information such as system calls, system events and CPU utilisation. The host IDS analyses the collected data and alerts the administrator if it detects any suspicious activity. The focus of the host IDS is on events occurring within the host machine.
- **Network-based IDS:** Network-based IDS (NIDS) relies on the network traffic to detect any anomalous activity in the network. It analyses the data collected from the network layer and transport layer of the network in order to detect any attacks, such as unauthorised access, denial of service (DoS) attacks, or port scans.

- **Hypervisor-based IDS:** The two previous deployments are shared between conventional networking and a cloud computing environment. In contrast, the Hypervisor and VM based IDS deployments are specific to and found exclusively in the cloud environment. Hypervisor-based IDS (HIDS) is an intrusion detection system that is specifically proposed for cloud hypervisor IDS and deployed at the hypervisor level. HIDS has a wide vision of the cloud environment. It is capable of collecting information from both VMs and the host at the same time. Moreover, the data collected could be from both operating systems and the network traffic of the host or VMs running on top of the hypervisor. HIDS are privileged by and have leverage due to the hypervisor characteristics, and have greater detection ability than VM-based IDS. It can monitor and analyse network communications between VM-VMs, the VM-hypervisor and between the cloud environment and the outside. Furthermore, HIDS can monitor and analyse information such as system calls, system events and running processes from the operating systems of the VMs and the host machine within the hypervisor. Therefore, HIDS could be network-based, host-based or both of them (hybrid). For HIDS, the configuration and control are restricted to the cloud provider.
- **VM-based IDS:** VM-based IDS (VIDS) is an intrusion detection system that is deployed on the virtual machine. VIDS focuses on protecting a VM instance by monitoring and analyzing the data collected from VM's network traffic and/or operating system. Therefore, it could be based on NIDS, Host-based or hybrid. VIDS is under cloud user control; they can deploy any intrusion detection system they prefer. Moreover, VIDS can be applied by third-party or by cloud provider through add-ons or subscription.

2.3.4 Deployment Environments

One of the most important factors that intrusion detection systems can be categorised according to it, is the detection deployment environment. The networking environment has changed over the years, and it has advanced from local/wide area networks (conventional network environment) to the more recent cloud computing environment. Each of these environments has its own characteristics and speciality. The cloud computing environment is distinct from the conventional network environment as it involves different technologies. Therefore, each environment has its own specification for IDS deployment. Most of the existing IDS approaches have been proposed for conventional network environments. Mixing existing IDS approaches with the cloud environment without considering its characteristics

will not provide protection for cloud computing. Therefore, it must be emphasised that any developmental approach for cloud IDS needs to take its characteristics into consideration.

2.4 Summary

In this chapter, we provided an overview of cloud computing architectures and security issues. We discussed various types of cloud environments, cloud service models and cloud computing deployment models. The challenges that cloud computing faces are also discussed in this chapter. Moreover, we provided some background on cloud intrusion detection systems and discussed the corresponding detection approaches and deployment models.

In the next chapter we will present the related work on cloud intrusion dataset and cloud intrusion detection systems. Moreover, we will discuss the limitations and deficiencies on both of them. Furthermore, the main reasons for why there is no effective real cloud intrusion detection datasets and systems yet will be discussed.

Chapter 3

Related Work

Cloud computing introduces a new era of integration of heterogeneous data in varying formats and from diverse sources and operating systems. This requires an improved understanding of the concept of a cloud dataset and its related concepts, such as the formats and the sources of data. By reviewing cloud intrusion datasets in the literature, there is a floating confusion about what can really be counted as a cloud dataset. This raises the need to define what a real cloud dataset is, since, not only there is no or limited publicly available cloud dataset available for researchers, but most of the datasets that are mentioned in the literature for cloud computing are not suitable and do not reflect the real cloud environment. These deficiencies are the main reasons for why there is no effective real cloud intrusion detection datasets yet.

We define the cloud intrusion detection datasets as *data collected from real cloud computing environments and gathered from either one or different data sources. The dataset may comprise one or more data formats, and can contain strings of characters, numbers, binary or any combination of them.*

This chapter will present the available works on cloud intrusion dataset along with cloud computing intrusion detection systems. Moreover, we will discuss the insufficiency and limitation arising when adopting them to develop, deploy or evaluate cloud IDS.

3.1 On Cloud Intrusion Datasets

3.1.1 Cloud Intrusion Detection Dataset (CIDD)- based on (DARPA) dataset

Kholidy and Baiardi [63] introduced a Cloud Intrusion Detection Dataset (CIDD), which is based on the Defense Advanced Research Project Agency (DARPA) dataset. DARPA dataset was collected from a simulated network for an air force base connected to the Internet. This dataset contains simulated user activities and injects attacks at well defined points, and then gathers tcpdumps, process and filesystem information. CIDD was built by assigning users to different VMs according to their login session times and the applications that they ran. Using this method, CIDD was created by extracting and correlating user audits from DARPA dataset, and was presented to be a dataset for cloud computing.

3.1.2 Cloud Storage Datasets

Drago et al. [40] collected network traffic related to personal cloud storage service, namely, Dropbox. They gathered TCP flows with the commands executed by the Dropbox clients from two university campuses and two Points of Presence (POP) in two different European countries during 42 successive days. The analyzed dataset provides a better understanding for the use of cloud storage in different environments, which have different user habits and access to technology.

3.1.3 Cloud Intrusion Detection Datasets (CIDD)- based on simulation

Moorthy and Rajeswari [100] used the same name CIDD for their datasets as [63] but the datasets are different in content. They simulated the cloud environment by setting up a cloudstack environment using two machines: one running the management services and the other running a kernel-based virtual machine KVM hypervisor. The CIDD was collected based on the traffic, which flow to/from specific ports that were opened for communications in the simulated cloud. The malicious traffic was generated based on attack signatures that are prepared manually and scored using a common vulnerability scoring system. A systematic approach was used to generate CIDD based on profiling intrusions, protocols, or lower level network entities.

3.1.4 Denial of Service Attack Dataset

Another work on the generation of cloud intrusion dataset is the work done by Kumar et al. [70] as a part of developing their DoS attack detector. They stimulated IaaS cloud environment using the open source cloud platform Eucalyptus. They launched 15 normal VMs, 1 target VM and 3 malicious VMs. The normal VMs are used to generate normal traffic while the malicious VMs are used to perform 7 different DoS attacks on the target VM. The attacks were run using 4 different scenarios, including 1 scenario depicting normal activities, and 3 different attack scenarios. The traffic between each VM was captured but was limited to 4 IP-header fields (i.e. source, destination, transferred bytes and protocol type) without any information about the payload. Although this work collected different internal traffics between VMs, the published data does not contain the raw data but, instead, it contains the data obtained after transformation and feature extraction [69] .

3.1.5 Limitations and Deficiencies of Current Datasets

The cloud intrusion datasets described above have limitations and deficiencies that hinder their adoption for a broad range of cloud intrusion detection investigations. The most significant limitation is that they were not collected from a real cloud environment, which is heterogeneous in nature. Therefore, there is a lack of certain data types that need to be collected from specific sources in the cloud environment. For example, some datasets are limited to network traffic traces that are only collected from the host side, and do not include any data collected at the hypervisor level, instance's OS level or internal network traffic. This affects the richness of the datasets and their size, hindering their use in training and testing a wide range of cloud IDS models. Moreover, current datasets do not reflect cloud IDS characteristics because they were either collected organically to evaluate the performance of a cloud service or were transformed and adjusted to be suitable for cloud IDSs. Furthermore, they do not include some attack types that are new and specific to the cloud computing environment. But most importantly, these datasets are not publicly available for researchers to access and use to build, evaluate and compare cloud IDSs.

To overcome these limitations and deficiencies, and help the cloud security community in its effort to build practical IDSs, we opted to collect and share a real cloud dataset called *ISOT-CID*. This dataset, which was collected from an OpenStack cloud production environment, is publicly accessible and available for cloud security researchers.

3.2 On Cloud Computing Intrusion Detection Systems

Reviewing the literature on the existing intrusion detection approaches related to cloud computing shows that there have been many attempts to introduce IDSs for cloud computing environments.

However, several proposals convey just conceptual ideas without further proof of concept implementation or evaluation based on real data, including the following: [108, 31, 6, 87, 101, 4, 67, 142, 2, 122, 84].

Other proposals simply focus on adapting off-the-shelf IDSs for cloud environments or improving existing approaches mainly designed to work on conventional network or grid computing. Neither of these methods take into account the special architectural features and dynamically changing characteristics of cloud computing environments. Examples of such work include [149, 14, 135, 137, 131, 37, 101, 4, 105, 103, 68, 83, 99, 61, 18, 55, 82, 78, 142, 30, 10, 87, 12, 67, 95, 150, 6, 138, 74, 44, 84, 122, 2, 98, 71, 1, 121]. Some of the proposals were developed using a simulation environment or conventional virtualization environment, which obviously miss crucial constraints underlying a real cloud environment [96, 76, 145, 118, 135, 104, 121, 64, 66, 85].

Many proposals focused on detecting only one or two types of attacks (predominantly DoS) [84, 104, 12, 90, 64].

In addition, most importantly, to our knowledge, the overwhelming majority of the datasets used in the published works do not reflect real cloud behavior as discussed in the previous section. Most of the datasets consisted of either conventional intrusion datasets (e.g., DARPA, KDD), or they were collected from virtualization or simulation environments, which in most cases are not available publicly [138, 105, 1, 14, 135, 121, 149, 95, 65, 63].

However, with all the above-mentioned shortcomings in mind, in the following, we discuss existing works that share some similarity with our presented work.

To detect DoS attacks from within the cloud, Kumar et al. [70] proposed a model to detect any attack in VM-to-VM communication. Experiments were conducted by simulating cloud computing environments using Eucalyptus to create an Infrastructure-as-a-Service (IaaS) platform. The traffic between VMs was collected, specifically the Internet Protocol (IP) header fields (source IP address, destination IP address, number of bytes of data transferred, and protocol types). For each protocol, six distinct features were extracted. The extracted features were classified using a one-class support vector machines (SVM) algorithm to detect the attack. The IDS was deployed at the hypervisor level and used to

monitor all incoming and outgoing traffic to and from each VM. The major drawback with this work is not considering DoS attacks originating from external machines.

Liang et al. [79] proposed a collaborative intrusion detection service framework for cloud computing based on a decentralized architecture and using misuse detection. While online detection relies on signature-based rules, a machine learning model is used to help the online-offline analysis system learn the signatures and update the database. The proposed model was implemented in a cluster environment with a simulated cloud. The limitation of this work is not considering the role of the hypervisor in intrusion detection.

Santoso et al. [118] proposed a signature-based intrusion detection model to monitor the network traffic between VMs and simulated a private cloud using the OpenStack cloud platform. The proposed approach was evaluated for attacks using only one attack method, namely, User Datagram Protocol (UDP) flooding.

Lu et al. [85] proposed a VM-based intrusion detection model to detect botnets residing in a cloud environment. They used entropy as a network feature to determine randomness of communications between the command and control (C&C) server and the bots. The entropy was calculated based on the frequency of each character in the payload when the bot checks the C&C channel for a new command every five minutes. The limitation in this work is that the detection is based on the unencrypted payload, which could be evaded easily by encrypting the payload.

Table 3.1 summarizes relevant work from the literature and underscores gaps related to the datasets and attack coverage involved in their evaluations. We take some steps toward bridging these gaps, by introducing in subsequent chapters, our proposed feature model and detection algorithms, and a realistic cloud intrusion dataset that provides a wide range of attacks.

3.3 Summary

We started this chapter by introducing our definition for the cloud intrusion detection datasets. Then we presented available works on cloud intrusion dataset along with cloud computing intrusion detection systems. Next, we discussed the existing works that share some similarity with the work presented in this dissertation. The limitations and deficiencies on both of them were discussed. Moreover, Table 3.1 summarizes relevant work from the literature and underscores gaps related to the datasets and attack coverage involved in their evaluations.

To overcome aforementioned limitations, deficiencies and gaps, we take a couple of

steps toward bridging these gaps, by introducing in subsequent chapters, our proposed feature model and detection algorithms, and a dataset. In the next chapter, ISOT-CID, the first real cloud intrusion dataset of its kind will be presented.

Table 3.1: Summary of related works

Detection Approach	References	Dataset	Attack types	Publicly Available
Misuse and Anomaly	[99]	Simulated and KDD		No(simulated)/Yes(KDD)
	[131]	Simulated		No
	[14]	KDD, NSL-KDD, Botnet DoS Attack dataset and Botnet dataset	Not specified	Yes
	[121]	KDD, NSL-KDD and ITOC		
	[98]	KDD		
Anomaly	[85]		HTTP based botnets	
	[30]		Port scan and stepping stone	
	[70]	Simulated	DoS	No
	[56]		Port scan	
	[103]		Buffer overflow, signed interpretation of unsigned value, and URL decoding error	
	[10]	ISOT-Botnet	Botnet	
	[135]	KDD CUP		
	[3]	DARPA		
	[32]	DARPA and KDD Cup		
	[138]	DARPA	Not specified	Yes
Misuse	[78]	KDD		
	[96]	UNSW-NB, BareCloud and Simulated	Fuzzers, Backdoors, Dos, Exploits, Generic, Reconnaissance, Shellcode and Worms	Yes(UNSW-NB), Yes(BareCloud) and No(simulated)
	[150]	ADFA-LD	Password brute force, add new superuser, Java based meterpreter, Linux meterpreter payload and C100 Web shell	
	[95], [105], [61]	KDD, DARPA, KDD cup	DoS, Probe, U2R and R2L	Yes
	[149]	KDD Cup	DoS, R2L, U2R, and scanning and probing	
	[76], [82] And [47]		Not specified	
	[118], [79], [79], [104], [44], [19] and [89]		DoS	
	[80]		DoS, a worm, two botnets, and two exploits	No
	[90]	Simulated	Evasion techniques, clientSideAttacks, ip Reputation, shell codes DoS, brute force, fragmented Packets, and test rules	
	[12] and [64]		DDoS	
	[89]		SIP flooding attack	
	[137]	KDD and CAIDA UCSD anonymized 2014 Internet Traces	DoS, Probe, Worm, U2R and R2L	Yes
	[11]	DARPA		
	[93]	Honeypot project dataset (http://www.honeybird.hk/)	Not specified	

Chapter 4

ISOT-CID: Collection Environment and Procedure, and Data

4.1 Overview

The analysis and assessment of cloud system based on data collected during production provide valuable information on actual cloud behaviour, and can be used to identify normal behaviours from intrusions, quantify security measures, and perform quantitative evaluations and verifications for the IDS analytical models. Therefore, it is not surprising that the availability of cloud dataset has gained increasing momentum within cloud IDS community, and can help in providing the empirical basis for researching and developing effective models for cloud IDS.

To this date, there is a lack of a cloud IDS dataset that is collected from a real production cloud environment, publicly available and rich enough to satisfy the needs of the cloud security community. The reason for this lack is that collecting a real cloud intrusion dataset is a burdensome task and there are many challenges and barriers associated with it. Privacy is one of the foremost of these challenges as cloud environments are built upon sharing resources among many users and any attempt to collect data on the cloud could reveal private information about the users, their instances and their data. For a cloud provider, protecting the users's privacy is important and revealing some of the data collected on the cloud to researchers is not negotiable. Moreover, most of the cloud systems are commercial by nature, and opening their closed infrastructures for external parties could sabotage their business by breaching privacy agreements they have with their customers. The damage can even be worse if the data collected revealed a silent breach in the provider's cloud

environment.

In addition to privacy, the cloud has many different layers such as hypervisors, networks and guest hosts with different OS environments as well as many components, and collecting real data from these heterogeneous sources is difficult and can increase the complexity of the data correlation for the cloud IDS. The final challenge worth emphasizing is the data size. When collecting data on the cloud one has to be ready for enormous amount of data that will be gathered from different computing resources (more than 8TB for ISOT-CID dataset).

We were able to tackle these challenges and difficulties, and collect a real cloud computing dataset to be the first of its kind and paving the way for cloud security communities for more research and finding.

The ISOT cloud intrusion detection dataset is an aggregation of different data collected in two phases, both against the same production cloud computing environment. The cloud service provider (CSP) is Compute Canada, a nonprofit organization that serves the computational needs of Canadian researchers (see <https://www.compute canada.ca> for more details). The dataset was gathered from a variety of cloud layers, including guest hosts, hypervisors and networks, and comprising data with different data formats and from multiple data sources, including memory dumps, resource (e.g., CPU) utilizations, system call traces, system logs, and network traffic. It contains different attack traces like masquerade attacks, denial of service, stealth attacks, anomalous user behaviour and data attacks from outside and inside the cloud.

The purpose of ISOT-CID is the embodiment of a real cloud dataset for researchers so that they can build, evaluate and compare their works. It is designed to serve different and broad IDS models developments and evaluations. Moreover, ISOT-CID is essentially “raw” and has not been transformed, manipulated or altered. It is structured and prepared for the cloud security community, and is available for downloading through ISOT website along with the documentation and metadata files, which explain its production and use in order to ensure an unambiguous meaning of the data.

In this chapter, we start by describing the ISOT-CID and corresponding data collection process, and then summarize the characteristics of the collected dataset.

4.2 Target Network Architecture

4.2.1 OpenStack-based Production Cloud Environment

The dataset was collected through Compute Canada, which provides computational services for Canadian researchers hosted on the cloud. To address the needs of the non High-Performance Computing researchers, Compute Canada recently launched two new cloud data centers: one in the east (east cloud) located at the University of Sherbrooke, and the other in the west (west cloud) hosted at the University of Victoria. With more than 16000 virtual cores and 1.5 PB of storage, the west cloud is the largest academic cloud in Canada dedicated to all Canadian researchers and their collaborators.

The dataset was collected on the west cloud, which is based on OpenStack. With more than 600 supporting companies, OpenStack is becoming the de facto platform for public and private cloud deployments. It allows the cloud providers to control large pools of resources, including compute, storage and network. OpenStack has a modular architecture composed of many components, each one is usually a full project on its own with a large development team behind it. Currently, OpenStack has the following main components:

- Nova: It is a service that runs on the compute nodes (i.e. hypervisors also called Nova-compute) and manages the instances on them, and on the controller nodes to provide the scheduling and the API functionalities (Nova-api, Nova-scheduler and Nova-conductor).
- Keystone: This is the identity management service for OpenStack, which controls the authentication and authorization of the OpenStack users.
- Neutron: This service manages the network services in Openstack. It allows the providers to virtualize all the network elements, including routers, subnets, ports, etc.
- Glance: A dedicated service for storing and managing images and snapshots.
- Horizon: This is the dashboard of OpenStack. It provides a web-based interface to OpenStack.
- Ceilometer: This service is the main monitoring service for OpenStack. It offers many statistics that allow both users and administrators to monitor their resources.

- Heat: This service allows the user to write recipes for deploying and orchestrating their virtual environments.
- Cinder: The service that manages the block storage on OpenStack. Cinder is designed to support different kinds of backend storage including Ceph. Using it, users can create and attach storage volumes to their instances.
- Swift: The cloud object service that allows users to store and retrieve their objects similar to Dropbox.

In addition to the dashboard web interface, OpenStack offers two other interfaces to manage the resources: a command line interface and a programming API. The communication between different OpenStack services is asynchronously orchestrated using RabbitMq.

The western cloud architecture is shown in Fig. 4.1. The services Horizon, Keystone, Glance and RabbitMq are running on 3 controller nodes (Nefos1, Nefos2, and Nefos3) designed in a high-availability (HA) configuration. Two high-bandwidth nodes (Neut1 and Neut2) are dedicated to the Neutron service. All the rest of compute nodes are hypervisors that are running Nova Compute service. The back end storage used by Cinder is Ceph.

4.2.2 ISOT-CID Collection Environment

The ISOT-CID project aims at setting up a real production cloud environment to collect the necessary data from all three cloud layers (i.e., VMs, Hypervisors and Network traffic). Our lab environment for performing this collection processes consists of two separate environments, namely ISOT-lab environment and ISOT-cloud environment.

The ISOT-lab environment (depicted in Fig. 4.2) contains the server that receives the forwarded dataset from different sources and stores it in a secure way. The ISOT-cloud environment runs on the west cloud. The ISOT-cloud environment has all the three sources involved in the dataset generation (i.e., VMs, Hypervisors and Network traffic), and is composed of two hypervisor nodes and 10 instances launched in three different cloud zones named as A, B and C.

The instances located in these zones are organized as follows: 5 instances launched in zone A, 4 instances launched in zone B, and 1 instance launched in zone C (instances and hypervisors specifications are shown in Table 4.1 and Table 4.2).

All these instances are accessible from outside world through one public VLAN (namely VLAN3337), except one instance, *isotvm.in*, that is hidden under a private internal network and only accessible from specific instances via the internal router. We designed the cloud

Figure 4.1: Compute Canada West Cloud OpenStack deployment architecture.

environment that way on the belief that generating a real cloud computing dataset needs to consist of heterogeneous data sources (i.e. VMs, Hypervisors and Network traffic) to represent the real cloud environment. The ISOT-cloud network topology is depicted in Fig. 4.2.

4.3 Data Collection Procedure

The ISOT-CID project started as a response to our need to build and develop practical cloud IDSs. This need was then amplified by not finding any source for real cloud datasets, and ignited a formal data collection procedure structured as follows:

Figure 4.2: ISOT-CID project environment

1. Elicitation of the requirements related to the data collection targeted to cloud IDSs.
2. Official agreement between ISOT lab and Compute Canada to approve the ISOT-cloud environment on the Compute Canada West Cloud and obtain the real datasets thereafter. The agreement took few months to be finalized and approved.
3. Designing and setting up the appropriate ISOT-cloud environment for the data collection.
4. Setting up and configuring the ISOT-lab environment.

Table 4.1: Instances specifications.

VM Number	VM's OS	Specification	Zone
VM 1	Centos	RAM: 6 GB Disk: 0 GB VCPUs: 4	C
VM 2	Centos	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	A
VM 3	Debian	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	A
VM 4	Windows Server12	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	A
VM 5	Ubuntu	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	A
VM 6	Centos	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	A
VM 7	Ubuntu	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	B
VM 8	Ubuntu	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	B
VM 9	Windows Server12	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	B
VM 10	Centos	RAM: 7.5 GB Disk: 20 GB VCPUs: 2	B

Table 4.2: Hypervisors specifications.

ID	OS	Specification
A	Centos	RAM: 125GB CPU: 32 cores Clock Speed: 2.00GHZ
B	Centos	RAM: 125GB CPU: 32 cores Clock Speed: 2.00GHZ
C	Centos	RAM: 264GB CPU: 55 cores Clock Speed: 2.40GHZ

5. Designing and implementing the data collection agents.
6. Collecting the data for normal and attack scenarios.
7. Finalizing the data collection.
8. Publishing the data via a secure webserver on the ISOT-lab environment.

In addition to using syslog as our main logging mechanism, we designed and wrote agents for collecting specialized data syslog does or can not include. Since we intended to collect heavy data (e.g., memory and tcp dumps), we deployed three types of agents:

- Light weight agents that run very often (every ~ 5 secs) and use minimal resources on the targeted machines.
- Medium weight agents that run less often (every ~ 60 secs) but collect large amount of data.
- Heavy weight agents that are intensive, run even less often (every 120 secs), and collect an even larger amount of data.

Figure 4.3 shows the general architecture of the logging platform. The specialized collector agents were implemented as shell and powershell scripts, and ran in the background at specific times during normal and attack periods. The time interval for the data collection in different agents can be adjusted to avoid missing the attack period. The data gathered at the agent level is either forwarded to the syslog daemon, or lz4 compressed and transferred directly to the logging server using *scp*. The type of data collected by the agents is described in Sect. 4.5.

After verifying and validating the collector agent scripts, we embedded them into and ran them simultaneously on the ISOT-cloud machines. The body of each script is different according to the targeted source, but in general they are very similar as they collect information from the same data sources except for the hypervisor agents that collect extra data and more detailed traces. The main pseudo code for the collector agents is shown in Algorithm 1.

Algorithm 1 Light weight agents

send anything printed to stdout and stderr to the syslog

while *True* **do**

```

    get information about all the processes
    get the CPU and disk utilization report
    get virtual memory statistics
    get information about network connections
    get the list of open files
    tcpdump the light weight network traffic
    sleep 5 sec
    kill tcpdump

```

Figure 4.3: ISOT-CID collection elements.

When the collector agents are invoked during collection processes, they extract and collect the required data from low level logs in all specified sources. The collected binary logs by the agents are forwarded through a secure channel to a dedicated log repository server in the ISOT-lab for data storage and future processing. Furthermore, the data collected from each source is sorted chronologically on the server. Fig. 4.3 briefly describes the collection processes.

The collector agents can be classified and mapped into the three cloud layers (instances, hypervisors and networks) as follows: Instance-based agents, Hypervisor-based agents and Network-based agents into the three cloud stack layers. The goal of each agent is to collect specific type of real time data that is relevant to the environment in which it resides as described next.

- *Host-based agent:* The host-based agent is installed on each VM in ISOT-cloud environment. The agent's responsibility is to collect runtime information from the VM's data sources such as, operating system and network, and forward them to the log

server in the ISOT-lab.

- *Hypervisor-based agent*: The hypervisor-based agent runs on each hypervisor in ISOT-cloud environment. Its main responsibility is to collect runtime information from the hypervisor data sources and forward them to the log server.
- *Network-based agent*: The network-based agent also runs on each hypervisor and collects runtime data from the hypervisor network traffic and forward them to the log server.

By spreading the agents between all cloud stack layers we were able to build a rich cloud dataset. We collected different data types by targeting a variety of data sources. These data sources are: system calls, cpu utilization, windows events log, memory dumps and tcp dumps.

ISOT-CID was collected in two phases and over several months for the VM instances, and several days and time slots for the Hypervisors and the Network traffics (more details will be provided when describing the attack scenarios).

The dataset is labeled and contains a mixture of both normal and malicious activities. The malicious data consists primarily of attacks executed by a tiger team and unsolicited malicious sessions by external hackers, unknown to the researchers. The unsolicited sessions were identified based on the source IP addresses and attack timing, and they were labeled as unclassified. Because the members of the tiger team worked independently, some of the attacks were launched around the same time against different parts of the cloud platform.

The benign/normal data are from web applications and administrative activities ranging from maintaining the status of VMs, rebooting, updating, creating files, SSHing to the machine, and logging in a remote server. The web traffic was generated by more than 160 legitimate visitors, including more than 60 human users and genuine traffic generated by 100 robots, performing tasks such as account registration, reading/posting and commenting on blogs, browsing various pages, and so on. One of the web applications consists of a password management service for registered users.

4.4 Attack Scenarios

As discussed previously in Sec. 4.2, the aims of our cloud environment setup is to obtain a rich cloud dataset by gathering different data types from variety of sources. Moreover, to amplify its richness and make it comprehensive, we performed a wide range of attacks that are ranked as the top threats in cloud computing. These attacks, originating from both outside and within the cloud, were executed covering both application and network levels, and major categories such as Remote-to-Local (R2L), DOS, probing, information disclosure, input validation, authentication breach, and backdoors. All the traces of these attacks were collected from all the previously specified data sources. This is essential as cloud IDS researchers/developers need a cloud dataset that covers different attack scenarios in advance so that they can effectively and productively go through the development and evaluation cycles.

In addition, there are two major categories of users in cloud computing: the insiders who have some sort of access to the cloud infrastructure, and the outsiders who are not. Both of this kind of users are included in our ISOT-CID attack scenarios. Likewise, the ISOT-CID attacks are divided into inside and outside attacks that are performed by an insider and outsider attackers, respectively. The inside attacks were originated from within the ISOT-cloud environment and targeted either the internal cloud infrastructure or the outside world. In our case, we opted for two scenarios:

1. The attacks are performed by a malicious insider who has high privileges (e.g., root access) on the hypervisor nodes in our ISOT-cloud environment.
2. The attacks are originated from an instance inside the ISOT-cloud environment. This instance could be either compromised or used on purpose as a bot to attack other instances in the ISOT-cloud environment or the outside world.

The outside attacks are defined as the attacks that target the ISOT- cloud environment from the outside world. In the outside attacks, in addition to the daily attacks that were performed by stranger attackers, we carried out different attacks such as Remote-to-Local (R2L), DOS, probing, information disclosure, input validation, authentication breach, and backdoors. Attack types and scenarios are discussed next. For instance, Fig. 7.1 and Fig. 7.2 depict one of the outside attack scenarios carried out on Day 1 (Phase 1). The attacker conducted an attack first against one cloud node by scanning the network and then launched a successful dictionary attack against VM8. After that, the attacker leveraged the cloud environment, used the compromised VM8 as a stepping stone, and started new

attacks from inside the cloud, targeting other VMs in the cloud environment and the outside world. The attack times were recorded with the attack types as well.

The above scenario is consistent with many of the attacks against Microsoft Azure customers as reported by analysts from Azure Security Center [73, 72, 36, 46]. Many of the reported attacks involved an initial RDP brute force attack to gain access.

Some of the attacks in ISOT-CID simply consist of layer 7 and network layer DoS attacks launched remotely against the cloud infrastructure. Further attacks in ISOT-CID consist of exploiting input validation vulnerabilities in web applications, including cross-site scripting (XSS), SQL injection, and path/directory traversal. For instance, Fig. 4.5 depicts an attack scenario that occurred in Phase 2, where through path traversal, the attacker was able to gain access to secure shell (SSH) configuration and certificate files for an unspecified instance in the cloud. Through trial and error, trying the credentials against different machines, the attacker was able to locate the machine with the found credentials. Next, the attacker logged in the compromised machine, and downloaded, installed, and ran a cryptominer, which joined a mining pool hosted remotely. Unauthorized cryptomining is a serious and growing threat for existing cloud platforms as discussed in [43, 72, 42]. All conducted attack types during collecting ISOT-CID are presented in Table A.1.

4.4.1 Inside Attack Scenarios

Most cloud vendors provide little to no information about their policies regarding recruitment procedures, the level of privileges assigned to their employees, and the legal actions that could be taken against the malicious insiders. This lack of transparency can encourage the insiders, especially employees, to carry out their malicious activities, and to even have escalated privileges that they are not supposed to have. With these privileges and the knowledge about the resources to attack, an employee can easily gain access to confidential data [97]. In most cases, this can even go undetected as the insider activities often bypass the provider firewall or IDS. Moreover, current data protection mechanisms, such as encryption, have failed to prevent the inside data theft attacks [125]. Therefore, it is not surprising that the number of data breaches by malicious insiders have been increasing [17] and malicious insiders are ranked as the 3rd top threat in cloud computing [57].

In the inside attack scenarios performed, multiple attacks were run by an insider having root access to the ISOT-cloud hypervisors. These attacks violate confidentiality, privacy, integrity of cloud user's data. We discuss below the different categories of inside attacks enacted.

Revealing User's Credentials

Two different techniques were used to attack the ISOT-cloud environment and reveal user's credentials. The summary of the first attack scenario as follows:

Step 1 Scan the running instances and their associated disks.

Step 2 Extract the names of the instances from their *libvirt.xml* specifications.

Step 3 Focus on a single instance, and locate and mount its disk.

Step 4 Copy the password and shadow files, and the *.ssh* folder.

Step 5 Copy the private key to the attacker workstation.

Step 6 Finally, compromise the ISOT instance using the copied private key.

The second inside attack was performed by a root privileged user to get memory and strace dumps. These dumps were obtained using *gcore* and *strace*, respectively. As shown in [38], once the memory dumps are available, the inside attacker can extract user credential and private information, including passwords in clear text.

Extracting User's Confidential Data

Following the same steps as above, once the inside attacker has mounted the instance's disk he can search, copy, delete and change any user's data, similar to copying the *.ssh* folder above.

Back Door and Trojan Horse

In this scenario, the inside attacker shut down the instance using *virsh* tools [33], mounted its disk using *guestfish* tools [60], and created Trojan horse for *ls* and *ps*. He also added an attractive script called *psb* that runs a malicious code when executed (this is a kind of back door to access the machine later on).

The other inside attack scenarios that we performed were carried out from compromised ISOT-cloud instances. After two instances were compromised, the inside attacker configured one of them to be a stepping stone, which potentially could be part of a botnet. Although this stepping stone was setup by an insider attacker, it could have been launched by the owner of the instance himself.

Compromised Instance and Stepping Stone Activities

These attacks are carried out from an inside attacker who is either aiming at compromising an instance and using it for his malicious activities, or owning an instance that behaved as a normal instance for a while but it then turns out to be part of a botnet¹. Once the attackers compromise an instance, they start attacking the neighboring instances. The summary of the attack scenario for this step is as follows:

- Step 1** After a successful access to an instance VM8 from a previous outside attack (see 4.4.2), the attacker started to discover the internal network by searching local IP information and scanning the subnet. A few VMs with open ports were then discovered.
- Step 2** A file was transferred via *scp* from the attacker machine to the compromised instance VM8. The file was used as a password dictionary.
- Step 3** The attacker installed *hydra* on VM8 and launched internal network scans using *nmap*. The machines discovered were then subjected to brute-force attacks using the password dictionary file. One of these attacks was successful against the instance VM5.
- Step 4** A quick ssh login into the internal host VM5 from VM8 was logged.
- Step 5** Finally, the attacker installed *hping3* on VM8 and ran several failed DoS attempts against VM4.

4.4.2 Outside Attack Scenarios

As we previously emphasized, the cloud is becoming an attractive target to outside data hunters. Having a centralized environment for virtual machines and data is a hacker's dream that is becoming true with the widespread adoption of cloud computing. Many attack attempts are made every single second to access instances and exploit any vulnerabilities within cloud. We can easily see that in our ISOT-CID; outside attackers are performing many different masquerade and DoS attacks attempts. Just within few months of operations, the Compute Canada's West cloud detected 5 compromised instances, most of which had weak passwords that the outsider attackers cracked using brute-force attacks. Moreover, at least one of these instances was compromised within one hour of its deployment.

¹In our particular scenario, the botnet command and control (C&C) server is hosted remotely, outside the cloud and only one bot is in the cloud.

In the outside attack scenarios, we performed multiple attacks against ISOT-cloud environment to breach the confidentiality, privacy, integrity, protection and availability of cloud user's data by performing masquerade, DoS attacks and exploiting input validation vulnerabilities in web applications, including cross-site scripting (XSS), SQL injection, and path/directory traversal. Moreover, once the instance is compromised, it is leveraged to attack other instances from within the cloud environment, executing the inside attack scenarios that were outlined above. In addition, it is leveraged to join a mining pool hosted remotely. Three selected outside attack scenarios from aforementioned are discussed next.

Masquerade Attack

Masquerade attacks are very challenging in cloud computing as they can escape detection because any related trace can be buried in the massive amounts of data generated from user audits and activities across cloud environments. A masquerader is an insider or outsider attacker who steals the legitimate user credentials and uses them to authenticate as a legal user. This allows the attacker to fool the system and get access to its abundant resources illegally. In ISOT-CID attack scenarios, we performed different masquerade attacks launched from the outside. As an illustration, we outline the steps of one of these masquerade attacks below:

Step 1 Scanning subnet of the VMs using *nmap* scanner.

Step 2 Password dictionary attack against VM8 using *Ncrack* scan leading to credential discovery.

Step 3 SSH login to VM8 using the cracked credentials.

Step 4 Running *ifconfig* to display network IP address info/range, local IP address determined.

Step 5 *Nmap* scan (against internal network) from VM8 to uncover a few hosts with open ports.

Step 6 Transferring a file using *scp* from the attack host to VM8 (to be used as password dictionary).

Step 7 Installing *hydra* on VM8.

Step 8 Internal network scanning using *nmap* to discover 10 IP addresses (4 hosts up).

Step 9 Cracking the password using *hydra* against one of the internal machines VM5.

Step 10 SSH login to VM5 using the cracked password to check the ssh connection.

Step 11 Setting up *hping3* on VM8 after checking that it was not previously installed.

Step 12 Launching *nmap* scan against VM4 to discover a host with 2 open ports.

Denial of service (DoS) Attack

The second attack scenario performed from the outside against ISOT-cloud environment is Denial of service (DoS) attack. In a DoS attack, the attacker overloads the targeted victim's system or service with huge number of requests consuming large amounts of system resources and leaving the system or the service unavailable. Not only that, in a cloud environment DoS attacks can render the whole cloud infrastructure unusable. In fact, two instances running on the same hypervisor are usually sharing the physical resources of the node. If one of them is subject to a DoS attack, the effect of this attack leaks into the second instance. In addition, consuming huge resources leads to an expensive bill that the victim will need to pay. As opposed to the cloud being a target for DoS attacks, many malicious users are leveraging the "unlimited" amount of resources in the cloud to launch massive outside DoS attacks. It is worth mentioning that, in cloud computing paradigm, DoS attacks were marked by the Cloud Security Alliance as the first of seven top threats [23]. The reader should also keep in mind that DoS attacks are the most common attacks on the Internet, and are hard to detect as distinguishing between DoS attack traffic and legitimate system unavailability is an open problem. In ISOT-CID, we designed and launched three types of DoS attacks. We performed the most common DoS attack, which targets the transport layer, and exploits the flaws in TCP three-way handshake procedures, called the TCP SYN attack. We used the open source *hping3* tool [117] to create a SYN flood attack. The first TCP SYN attack was performed on a compromised instance inside ISOT-cloud environment against another virtual machine in another ISOT-cloud zone. The attack flooded the instance with TCP SYN packets consuming its resources, hindering its use, and causing it to crash.

The second attack was performed from an outside machine against an instance inside the ISOT-cloud environment. The last attack was performed from a compromised instance inside ISOT-cloud environment against the logging server in the ISOT-lab. The 1st and 2nd DoS attack scenarios were the last attack steps from the 1st attack scenario, which we explained before. (The full and detailed attack scenarios for both phases are available

Figure 4.4: 1st attack round for inside and outside attacks in Day 1 (Phase 1).

for interested readers along with ISOT-CID documentations). To complete the 1st attack round, we added the following DoS attacks:

Step 1 From VM8, an unsuccessful *syn* flood DoS attack was launched against VM4.

Step 2 Another *syn* flood DoS attack against VM4 from the attacker machine caused VM4 to crash and we had to reboot it.

The 1st attack round for inside and outside attacks are depicted in Fig. 4.4.

Unauthorized Cryptomining

The third attack scenario performed from the outside against ISOT-cloud environment is unauthorized cryptomining also called cryptojacking. Unauthorized cryptomining is a serious and growing threat for existing cloud platforms. It leverages the “unlimited” amount of resources in the cloud to join a mining pool hosted remotely and then consumes the cloud resources. In cryptojacking attack, the attacker installs and runs a cryptominer on compromised instances leaving the victim with an expensive electricity bill.

As mentioned before, in ISOT-CID attack scenarios, some of the attacks consist of exploiting input validation vulnerabilities in web applications, including cross-site scripting (XSS), SQL injection, and path/directory traversal. For instance, Fig. 4.5 depicts an attack scenario that occurred in Phase 2, where through path traversal, the attacker was able to gain access to secure shell (SSH) configuration and certificate files for an unspecified instance in the cloud. Through trial and error, trying the credentials against different machines, the attacker successfully located the machine with the found credentials. After that, the attacker logged in the compromised machine, and downloaded, installed, and ran a cryptominer. We outline the steps of this attack below:

First Round:

Step 1 Scan VM 10 using ZAP (XSS, SQL Injection, Path traversal etc.)

Step 2 Manual path traversal to download and upload files (was able to download shadow file and ssh keys)

Step 3 Manual XSS on blog posts and comments pages

Step 4 More manual path traversal to download and upload files (was able to download some system files like logs and configs and also the application config file containing the DB password)

Step 5 Manual scan of the network trying to login to the database using the password acquired in the step above

Second Round:

Step 1 SSH into VM 7 using key acquired beforehand

Step 2 Download and install the cryptominer

Step 3 Run the cryptominer

Figure 4.5: Sample attack scenario in ISOT-CID in Phase 2 (over several days)

4.4.3 Attack Time and Locations

In designing our ISOT-CID attack scenarios, we chose different attack times and distinct attacker's geographical locations. The attacks were divided into 4 rounds in phase one, averaging for 1 hour for each round, and spread over 4 different days. Moreover, the attackers performed and completed the attack scenarios from two different continents, precisely Europe and North America. And in phase 2 the attacks were divided into 5 rounds, averaging for 2 hours for each round, and spread over 5 different days. The dataset is labeled and contains a mixture of both normal and malicious activities. The malicious data consists primarily of planned attacks and unsolicited malicious sessions by external hackers, unknown to the researcher. The unsolicited sessions were identified based on the source IP addresses and attack timing, and they were labeled as unclassified. Fig. 4.6 summarizes the first and second attack scenarios for inside and outside attacks for day 1 in phase 1. Furthermore, Fig. 4.5 depicts an attack scenarios that occurred in Phase 2.

Figure 4.6: Summary of the first and second attack scenarios for inside and outside attacks.

4.5 Collected Data

4.5.1 System Calls

A *system call* is a mechanism by which a user-space application requests a service from the kernel space of the OS [24, 45, 140]. Although every OS (like *nix and Windows) has its own specific system calls that are accessed via dedicated APIs, all of them follow the same bidirectional process in the sense that all requests from a user-level application to the OS are delivered by a system call interface to the kernel before they are executed on hardware. This allows the kernel to run the code on behalf of the user in the privileged space and get the information requested by the user via restricted system calls [24]. Furthermore, each one of these system calls has a unique number that is written in the kernel's system call table to identify them. Examples of system calls for OS (like *nix and WinX) are fork, pipe, read, CreateProcess and ReadFile. In ISOT-CID collection process, we collected

the system calls from both hypervisors and instances. They provide useful information, like opened and accessed files, execution time stamps and the count of each system call number executed by the application. This information reflects every activity occurring inside the instances and hypervisors, and the communication between them. In fact, when a guest OS initiates a system call to access the host resources, the hypervisor intercepts and interprets it into the corresponding system call supported by the host OS. By doing so, the hypervisor has full control over the host OS resources like CPU, memory, persistent storage, I/O devices, and the network, and each VM access to any of these resources is accounted for.

4.5.2 Memory Dump

Memory dump is a procedure by which the contents of a physical memory, representing the internal states of the system, are printed out or written to a storage drive. Memory dumps are usually generated when a crash occurred or during debugging [91]. They are very helpful to pin point the source of a crash, to debug system errors and performance issues, to obtain information about the running programs and the overall state of a system, to detect any intrusion or attack, to locate deleted or temporary information, and to carry out malware and forensic investigation.

Unfortunately memory dumps capture sensitive information, like passwords, encryption keys, and the contents of a private document, which can be very harmful if it ends up in the hands of an attacker [38]. The ISOT-CID contains memory dump files that were collected using *gcore* command on the processes of the instances running on the ISOT-cloud hypervisors. The memory dumps collected resulted in a large amount of data as each instance had around 7.5GB of memory.

4.5.3 Event Logs

On any computer system, there is a specific auditing or event log service used to capture any predefined events, such as error reports, system alerts, and diagnostic messages that happen during the daily operation of the system. This event log service usually runs in background and listens to events sent by processes running on the local or remote system [102].

Windows Event Logs

In WinX OS, an event is defined as a notification posted to the user and raised by a hardware, software, or system component [35]. The event log service is responsible for logging and organizing these events in WinX OS. There are three types of event logs stored on Windows machine: Security, System and Application event logs. In general, security logs record events related to sensitive components of the system, such as the authentication component, as well as events related to resource usage, such as file operations and process invocations. The system log contains events logged by the system components, for example, driver failures and hardware issues. Finally, the application events can be triggered by any application as long as it implements the event API. The developer can generate events by calling the proper Windows event API. Windows event logs are not only useful in diagnosing problems, but also crucial in monitoring activities on a system. ISOT-CID includes all of these event log file types from the two windows instances that run in different zones and have been involved in the attack scenarios.

Unix Logs

Messages, notifications and events generated by *nix subsystems and services are usually logged as text under /var/log in specific files. Each process can virtually log its messages into a dedicated file. For example, sshd logs its authentication events into /var/log/auth.log and kernel messages are sent to /var/log/messages. This of course leads to unmanageable large amounts of log files, especially when dealing with many machines. To avoid that, we installed and configured rsyslog on the *nix machines to collect the logs in a central and secured location on the ISOT log server. Our scripts use the *logger* command to send the collected information to the rsyslog daemons, which in turn forwards them to the ISOT lab logging server.

4.5.4 Resource Utilization

One of the main functions of the operating system is the scheduling of the resources to serve all the running processes [115]. Scheduling CPU is the most important scheduling function of the OS as without it only a single program can use the CPU from start to finish and the rest of processes will starve [139]. When no task is requesting CPU, the processor becomes idle. By summing up the idle times during a given number of CPU ticks, one can deduce the overall CPU utilization. There are two types of CPU utilization,

user CPU utilization and system CPU utilization. Both presenting the percentage of time spent performing user and system tasks, respectively. Analyzing the CPU utilization during different states, especially, over long periods of time, allows for building a profile for the system. This profile can be enhanced by collecting other statistics, such as disk utilization. By monitoring the usage of resources one can build a baseline profile that characterizes the normal behavior of the system. Any deviation from such a baseline profile can be detected and subjected to further investigation. ISOT-CID provides different information about the usage of resources on all instances and hypervisors. This information was collected using commands like *ps* and *iostat*.

ISOT-CID also contains more information about memory and disk IO in its documentations. Figures 7 and 8 illustrate some excerpts from ISOT-CID.

4.5.5 Network Traffic

Because the scope of this dissertation focuses on building cloud network IDSs, the network traffic of ISOT-CID, which has been used in our experiments, will be detailed in this section.

Network traffic is the main mechanism for exchanging information between computers. It is defined as a sequence of packets traveling between two communication endpoints known as source and destination. Each packet consists of a transport layer header, a network layer header, a data-link layer header and a payload representing the actual data exchanged [41]. These network packets can provide rich statistics that is essential for developing network security tools. In a cloud computing infrastructure such as OpenStack, the network traffic travels through different network points. In our case, the outside traffic first arrives via the entry and top-rack switches to dedicated network nodes, called neutron nodes, and then travels to the hypervisor on the compute nodes passing through our internal physical switches. Finally, the hypervisor delivers the traffic to the designated instance. With this OpenStack networking configuration, there are three different network flows: external, internal and local traffic. The external traffic is between the virtual machine and an outside machine (an “instance-outside” traffic). The internal traffic is between the compute node and another compute node (“hypervisor-hypervisor” traffic). The local traffic is between two instances on the same Compute node (“instance-instance” traffic). In ISOT-CID, we were able to collect all of these three different traffics from both hypervisors and instances. By setting the network interface into promiscuous mode, we were able to collect all the network traffic that passes through all the network interfaces on the hyper-

visors and instances (except for the special network interfaces not involved in our network traffic). The utility TCPdump was used to capture the network traffic [81] on *nix OSs and Netsh on winX OS, and stored in packet capture (pcap) format. We performed two kinds of network traffic data collections: the network traffic without payload on both hypervisors and instances, and the full network traffic on the hypervisors only (the interested readers can find more details in ISOT-CID documentations). Figure 4.7 shows the traffic flow to all possible destinations in one of the hypervisors, whereas network traffic flows for selected individual VMs are depicted in Fig. 4.8.

Figure 4.7: Traffic flow within one of the hypervisors (Phase 1 - Day 1)

The network traffic dataset contains a total of 22,372,418 network packets for phase 1, of which 22,356,769 packets are normal, and 15,649 are malicious. Table A.2 summarizes the total network traffic statistics and Table A.4 details the traffic breakdown per day and node for phase 1. For phase 2, the dataset contains a total of 11,509,254 network packets, of which 9,502,872 packets are normal, and 2,006,382 are malicious. Table A.3 summarizes the total network traffic statistics, and Table A.5 details the traffic breakdown per day and node.

Figure 4.8: Sample traffic flow for different VMs (Phase 1 - Day 1)

4.5.6 Excerpt From the Dataset

This section provides snapshots from the dataset that was collected from one hypervisor during one attack scenario. Fig. 4.9 shows collected data about virtual memory statistics, and the CPU and disk utilizations.

Fig. 4.10 provides information about the list of open files, network connections and the collected TCPdump for the lightweight network traffic.

4.6 Summary

To this date, there has been a lack of a cloud IDS dataset that is collected from a real production cloud environment, publicly available and rich enough to satisfy the needs of the cloud security community. In this chapter, we discussed the reasons for this lack and the challenges and barriers associated with it. Then we presented our cloud intrusion dataset ISOT-CID which will pave the way for the cloud security community for more research and findings. We gave details in this chapter about, the collection environment, the data

sources and the attack traces. Finally, this chapter summarized the characteristics of the collected dataset and excerpt from the dataset was given.

In the next chapter we will present our feature model which is a multidimensional feature space that is constructed through multiple stages. Moreover, we will present its components and show how to structure them in a way to optimize the detection of malicious events.

Table 4.3: Attack types in the ISOT-CID

<div>Attack Origin</div> <div>Attack Target</div>	Outside	Inside
Application Layer	<ul style="list-style-type: none"> • Web Vulnerabilities Scanning • Dictionary/Brute Force login attack • Directory/Path Traversal • Cross-site Scripting (XSS) • SQL Injection • Fuzzers • HTTP Flood DOS 	
Network Layer	<ul style="list-style-type: none"> • Dictionary/Brute Force login attack • DNS amplification DOS • Synflood DOS • Ports and Network scanning • Unclassified (unsolicited traffic) 	<ul style="list-style-type: none"> • Unauthorized Cryptomining (download/install/run cryptominer) • Ports and Network scanning • Dictionary/Brute Force login attack • Synflood DOS • UDP Flood DOS • Revealing Users Credentials and Confidential Data by Insider • Trojan Horse • Backdoor (reverse shell) • Stepping Stone Attack

Table 4.4: Phase 1: Network traffic distribution

Total Normal Traffic	Total malicious Traffic	Total Packets
22356769	15649	22372418
99.93%	0.07%	100%

Table 4.5: Phase 2: Network traffic distribution

Total Normal Traffic	Total malicious Traffic	Total Packets
9502872	2006382	11509254
82.57%	17.43%	100%

Table 4.6: Phase 1: Network traffic details

Date	Node A			Node B		
	Total Normal Traffic	Total Malicious Traffic	Total Packets	Total Normal Traffic	Total Malicious Traffic	Total Packets
Day 1 9/12/16	3294811	982	3295793	2975278	243	2975521
Day 2 15/12/16	6704732	6833	6711565	4832628	1174	4833802
Day 3 16/12/16	522590	1470	524060	1549115	618	1549733
Day 4 19/12/16	1419617	3667	1423284	1057998	662	1058660

Table 4.7: Phase 2: Network traffic details

Date	Node A			Node B		
	Total Normal Traffic	Total Malicious Traffic	Total Packets	Total Normal Traffic	Total Malicious Traffic	Total Packets
Day 1 15/02/18	599051	8478	607529	199673	11080	210753
Day 2 16/02/18	1701631	249555	1951186	898076	21917	919993
Day 3 19/02/18	604090	11127	615217	387495	5043	392538
Day 4 20/02/18	956179	40089	996268	715215	47267	762482
Day 5 21/02/18	1075900	32996	1108896	651908	21570	673478
Day 6 23/02/18	952603	1537079	2489682	761051	20181	781232

```

2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: procs r b swpd free inact active si so bi bo in cs us sy id wa st
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: 2 0 0 4750936 394696 2355556 0 0 1 14 29 4 0 1 98 1 0
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: 0 0 0 4750944 394692 2355604 0 0 0 0 0 28 43 0 0 100 0 0
2016-12-15T08:24:28-08:00 hpsot-dj ssnd[1713]: Failed password for root from 122.194.229.39 port 13956 ssh2
2016-12-15T08:24:28-08:00 hpsot-dj ssnd[1713]: DISCONNECTING: Too many authentication failures for root from 122.194.229.39 port 13956 ssh2 [preauth]
2016-12-15T08:24:28-08:00 hpsot-dj ssnd[1713]: PAM 5 more authentication failures; logname= uid=0 euid=0 tty=ssh ruser= rhost=122.194.229.39 user=root
2016-12-15T08:24:28-08:00 hpsot-dj ssnd[1713]: PAM service(sshd) ignoring max retries; 6 > 3
2016-12-15T08:24:29-08:00 hpsot-dj ssnd[1715]: Failed password for root from 59.63.166.83 port 21770 ssh2
2016-12-15T08:24:29-08:00 hpsot-dj logIt.sh: 0 0 0 4752240 394688 2354568 0 0 0 0 0 135 71 0 1 99 0 0

2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: MemTotal: 7679804 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: MemFree: 4750936 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: MemAvailable: 7217908 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Buffers: 87776 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Cached: 2641048 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: SwapCached: 0 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Active: 2355556 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Inactive: 394696 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Active(anon): 74600 kB
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: Inactive(anon): 110920 kB

- Virtual memory statistics

2016-12-15T08:24:25-08:00 hpsot-dj logIt.sh: disk- total merged sectors ms total merged sectors ms cur sec
2016-12-15T08:24:25-08:00 hpsot-dj logIt.sh: vda 20226 0 2900002 411604 1427026 3998 12380304 158566696 0 7265
2016-12-15T08:24:25-08:00 hpsot-dj logIt.sh: vdb 9780 0 78234 289032 1970862 2622 19754664 116462564 0 2428
2016-12-15T08:24:25-08:00 hpsot-dj ssnd[1713]: Failed password for root from 122.194.229.39 port 13956 ssh2
2016-12-15T08:24:26-08:00 hpsot-dj logIt.sh: vda 20226 0 2900002 411604 1427026 3998 12380304 158566696 0 7265
2016-12-15T08:24:26-08:00 hpsot-dj logIt.sh: vdb 9780 0 78234 289032 1970862 2622 19754664 116462564 0 2428
2016-12-15T08:24:26-08:00 hpsot-dj ssnd[1715]: Failed password for root from 59.63.166.83 port 21770 ssh2
2016-12-15T08:24:27-08:00 hpsot-dj logIt.sh: vda 20226 0 2900002 411604 1427026 3998 12380304 158566696 0 7265

2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: Linux 3.16.0-4-amd64 (hpsot-dj) #01112/15/2016 #011_x86_64_#011(2 CPU)
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh:
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: avg-cpu: %user %nice %system %iowait %steal %idle
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: 0.12 0.00 1.34 0.69 0.06 97.79
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: Device: tps kB_read/s kB_wrtn/s kB_read kB_wrtn
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: vda 2.47 2.48 10.57 1450001 6189980
2016-12-15T08:24:23-08:00 hpsot-dj logIt.sh: vdb 3.38 0.07 16.86 39117 9877332

- The CPU and disk utilization report

```

Figure 4.9: Excerpt from the dataset: sample virtual memory statistics and the CPU and disk utilizations for one of the hypervisors.

2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: COMMAND	PID	TID	USER	FD	TYPE	DEVICE	SIZE/OFF	NODE	NAME
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	cwd	DIR	254,1	4096	2	/
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	rtld	DIR	254,1	4096	2	/
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	txt	REG	254,1	1309072	107008	/lib/systemd/systemd
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	18640	107161	/lib/x86_64-linux-gnu/libattr.so.1.1.0
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	14664	109709	/lib/x86_64-linux-gnu/libc.so.2.19.0
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	448440	106511	/lib/x86_64-linux-gnu/libc.so.3.13.1
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	31784	109721	/lib/x86_64-linux-gnu/libc.so.2.19.0
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	92888	106513	/lib/x86_64-linux-gnu/libmod.so.2.2.8
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: systemd	1		root	mem	REG	254,1	19016	106545	/lib/x86_64-linux-gnu/libcap.so.2.24

- The list of open files											
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: Active UNIX domain sockets (servers and established)									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: Proto RefCnt Flags									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 6									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 2									
2016-12-15T08:24:29-08:00	hpsiot-dj	logIt.sh: unix 4									

- Information about network connections											
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: tcpdump: listening on any, link-type LINUX_SLL (Linux cooked), capture size 262144 bytes									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: tcpdump: verbose output suppressed, use -v or -vv for full protocol decode									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: Listening on any, link-type LINUX_SLL (Linux cooked)									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.345112 In fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 68: 142.104.64.106.514 > 172.16.1.23.42332: Flags [P], seq 14178\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.347131 In fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 68: 142.104.64.106.514 > 172.16.1.23.42332: Flags [P], seq 141\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.347352 Out fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 224: 172.16.1.23.42332 > 142.104.64.106.514: Flags [P], seq 160\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.348828 In fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 68: 142.104.64.106.514 > 172.16.1.23.42332: Flags [P], seq 316\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.349260 Out fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 227: 172.16.1.23.42332 > 142.104.64.106.514: Flags [P], seq 316\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.350689 In fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 68: 142.104.64.106.514 > 172.16.1.23.42332: Flags [P], seq 475\$									
2016-12-15T08:24:31-08:00	hpsiot-dj	logIt.sh: 08:24:30.351129 Out fa:16:3e:3e:7c:39 etherType IPv4 (0x8000), length 228: 172.16.1.23.42332 > 142.104.64.106.514: Flags [P], seq 475\$									

- Tcpdump the light weight network traffic											
--	--	--	--	--	--	--	--	--	--	--	--

Figure 4.10: Excerpt from the dataset: sample open files, network connections and TCP-dump traces for an hypervisor.

Chapter 5

Feature Model

As mentioned earlier, a network-based HIDS can monitor the network traffic at the hypervisor level since it is a tunnel for all network traffic. The network traffic in the cloud environment is huge and includes volumes of high-dimensional data (high number of features or independent variables) that is transferred at high speed rates. With this type of network, deep inspection of the complete content of a packet is very difficult, and perhaps inapplicable for online detection in such an environment. Moreover, encryption might be used in the communication and the payload cannot be examined in this case. Furthermore, inspecting the payload in an environment like cloud computing may be restricted because of privacy regulations. Therefore, to achieve online detection for the cloud computing environment, analysing the statistical features and aggregating properties of the network traffic should be considered instead. These features and properties are usually computed based on the packet's header, such as IP addresses, ports, and protocol types, at different time windows. This ability to summarize the data and focus on the *flow* of the network rather than individual packets will make such a network-based HIDS attractive for the cloud environments. The challenge with such an approach is having a full framework that works hand-in-hand with the rest of the cloud environment services and is capable of

- reducing the packet's header dimensions by automatically extracting the appropriate attributes and features,
- eliminating the redundancy or irrelevant features by reducing their dimensions,
- having a systematic way to computing new cloud-based features, and
- improving its online detection by choosing the appropriate features for online detection algorithms.

One of the main contributions of this dissertation is a new feature model, which is a multidimensional feature space that is constructed through multiple stages. In this chapter we identify its components and show how to structure them in a way to optimize the detection. More specifically, this chapter introduces a systematic way for extracting features using a model-based approach. Moreover, we introduce our new instance-oriented feature extraction approach with the new set of extracted features based on network flow for cloud computing architecture.

5.1 Instance-Oriented Feature Model

If we treat the instances running on the hypervisor as independent, we can use the traditional network feature extraction methodology to extract the features from each instance and feed them independently to our detection engine. This methodology, however, is not enough because instances share the same hypervisor, and taking their correlated behavior into consideration can improve cloud feature extraction and anomaly detection.

Our detection model takes as input data the network packets captured at the hypervisor level. We denote by $\mathcal{P}_{\mathcal{H}}$ a set of IP packets on a hypervisor $\mathcal{H}$. Because many instances can run on a single hypervisor, the set of packets $\mathcal{P}_{\mathcal{H}}$ can be expressed as the union of all sets of packets targeting an instance i on $\mathcal{H}$,

$$\mathcal{P}_{\mathcal{H}} = \bigcup_{i \in \mathcal{I}} \mathcal{P}_i, \quad (5.1)$$

where $\mathcal{I}$ is the set of instances running on $\mathcal{H}$, and $\mathcal{P}_i$ is the set of IP packets associated with the instance i . To express the features succinctly, we introduce the notion of endpoint. An *endpoint* is defined as a pair (i, ip) , where i is an instance, and ip is a port on it. A packet at time t from a port sp on source s to a port dp on destination d can be regarded as a unit of data traveling from the endpoint (s, sp) to the endpoint (d, dp) . We denote such a packet by $p_t(s, sp, d, dp)$. If we consider the endpoints to be the nodes of a graph and the packets to be its edges, such that a packet at time t from endpoint $e_s = (s, sp)$ to endpoint $e_d = (d, dp)$ is the directed edge $p_t(s, sp, d, dp)$ connecting the nodes e_s to e_d , we then obtain a multigraph that we can use to define features and properties. Under this representation, the set of packets going to the instance i is given by

$$\mathcal{P}_i^{in} = \bigcup_{\forall s, sp, ip, t} \{p_t(s, sp, i, ip)\}, \quad (5.2)$$

and the set of packets going out of the instance i is

$$\mathcal{P}_i^{out} = \bigcup_{\forall ip, d, dp, t} \{p_t(i, ip, d, dp)\}. \quad (5.3)$$

Therefore, we have

$$\mathcal{P}_i = \mathcal{P}_i^{in} \cup \mathcal{P}_i^{out}. \quad (5.4)$$

Moreover, given a hypervisor $\mathcal{H}$ hosting a set of instances $\mathcal{I}$, we define the hypervisor packet flow $\mathcal{F}_{\mathcal{H}}^{t, \delta t}$ as a set of outgoing/incoming packets from/to any instance running on $\mathcal{H}$ during a specified observation interval $[t, t + \delta t]$,

$$\mathcal{F}_{\mathcal{H}}^{t, \delta t} = \bigcup_{i \in \mathcal{I}} \mathcal{F}_i^{t, \delta t}, \quad (5.5)$$

where $\mathcal{I}$ is the set of all possible instances on $\mathcal{H}$, t is the starting time of the observation, δt is the observation time length, and $\mathcal{F}_i^{t, \delta t}$ is the packet flow from/to the instance $i \in \mathcal{I}$ during the time interval $[t, t + \delta t]$. For a given instance i , a packet flow from/to the instance i during $[t, t + \delta t]$ is the set of all packets traveling between any endpoint on i and all other possible endpoints. Under our multigraph representation, the packet flow can be expressed as follows. First, we define the packet flow from an endpoint $e_s = (s, sp)$ to an endpoint $e_i = (i, ip)$:

$$\mathcal{F}^{t, \delta t}(s, sp, i, ip) = \bigcup_{z \in [t, t + \delta t]} \{p_z(s, sp, i, ip)\}. \quad (5.6)$$

The packet flow to i is defined as

$$\mathcal{F}_{in}^{t, \delta t}(i) = \bigcup_{\forall s, sp, ip} \mathcal{F}^{t, \delta t}(s, sp, i, ip). \quad (5.7)$$

The packet flow from i is defined as

$$\mathcal{F}_{out}^{t, \delta t}(i) = \bigcup_{\forall d, dp, ip} \mathcal{F}^{t, \delta t}(i, ip, d, dp). \quad (5.8)$$

The total packet flow associated with i is then

$$\mathcal{F}^{t, \delta t}(i) = \mathcal{F}_{in}^{t, \delta t}(i) \cup \mathcal{F}_{out}^{t, \delta t}(i). \quad (5.9)$$

Table 5.1: The raw features extracted from the hypervisor network traffic

Representation	Description
frame_time	time stamp that represents the appearing of the packet in a specific time window
eth_src	source MAC address
eth_dst	destination MAC address
ip_dst	destination IP address; this is usually linked with the address of a host that need to be protected
tcp_dstport	destination TCP port
udp_dstport	destination UDP port
ip_src	source IP address
tcp_srcport	source TCP port
udp_srcport	source UDP port
ip_len	the length of the IP packet
ip_hdr_len	the IP header length of the IP packet
tcp_hdr_len	the TCP header length
frame_len	the packet length including header and data
ident	identification number for the current data in a packet
ipfrag_offs	the offset of the IP packet
tcp_seq	data location of the TCP segment
tcp_ack	number of data received
traffic_in	a frequency number calculated by counting the appearing of packets incoming to the destination IP address during the observation time window
traffic_out	a frequency number calculated by counting the appearing of packets outgoing from the destination IP address during the observation time window

5.2 Anomalous Behavior Characterizations

Anomaly detection requires characterizing anomalous network behavior and modeling such behavior through a set of representative features. While there are many idiosyncrasies of

network behaviors that are symptoms of attacks, we focus our detection model on three such prominent characteristics, specifically, load dissimilarity or irregularity, high level of randomness, and high frequency for certain traffic characteristics.

For example, during the normal network traffic, traffic flow to/from specific ports could be distinguished from the high level of randomness that occurs during malicious activities such as port scanning or distributed denial of service (DDoS). Applying entropy to measure this randomness could help to detect that change in the network behavior. Furthermore, changes in the normal frequency of packet flow from/to specific IP addresses or ports are strong indicators that corresponding flows stem from malicious activities. This could be embodied by the DoS attack, when the victim's machine receives or produces a network flow that is higher than its baseline frequency. Another consideration that should be made concerning the network flow is the load ratio. Network flow to a specific machine during normal traffic is usually self-similar; that is, the incoming traffic pattern matches the outgoing pattern. Therefore, a dramatic change in traffic load is a sign that malicious activities are being conducted.

To capture these changes in cloud network traffic behavior, our proposed flow features rely mainly on three statistical methods, namely, entropy, frequency, and load, which will be discussed next.

5.3 Instance-oriented Feature Extraction

Our detection model takes as input the captured hypervisor packets and then groups them into a stream of packet flows (each packet flow contains a group of packets based on the time window δt). Our model involves two stages of feature extraction. An initial feature vector is computed for each individual packet based on the packet header. Next, we extract a separate feature vector for each packet flow based on the initial feature vectors associated with the packets involved in the flow.

Given a packet $p \in \mathcal{P}_{\mathcal{H}}$ (set of IP packets on a hypervisor $\mathcal{H}$), we extract from the packet a feature vector consisting of 19 components, as described in Table 5.1.

After grouping the packets into flows, we extract a feature vector for each flow by combining the initial features presented in Table 5.1. Our cloud feature extraction methodology is based on extracting instance-oriented features. We describe in the following the proposed flow features and extraction methodology.

5.3.1 Frequency Features

In [86], frequency features were computed for intrusion detection for conventional networks but only for the incoming traffic to a destination and independently of the source. This method has many limitations, especially in the cloud paradigm, as outgoing traffic can be very important in detecting anomalies. Moreover, abstracting the source in computing the frequency features causes the malicious traffic to be hidden within the legitimate traffic originating from other sources. This can easily lead to undetected attacks, especially if the instance is receiving high-volume traffic from different sources. Furthermore, even when the attack is detected, determining the attacking source is challenging, especially when it is carried out by many agents (or hackers) connecting from different machines and devices. Therefore, we introduce several frequency features defined for each instance $i \in \mathcal{I}$. The *in* frequency features are defined as follows:

$$f_{s,sp,i,ip}^{in}(t) = \frac{|\mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.10)$$

$$f_{s,i,ip}^{in}(t) = \frac{|\bigcup_{sp} \mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.11)$$

$$f_{s,sp,i}^{in}(t) = \frac{|\bigcup_{ip} \mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.12)$$

$$f_{s,i}^{in}(t) = \frac{|\bigcup_{sp,ip} \mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.13)$$

$$f_{sp,i}^{in}(t) = \frac{|\bigcup_{s,ip} \mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.14)$$

$$f_{i,ip}^{in}(t) = \frac{|\bigcup_{s,sp} \mathcal{F}_{in}^{t,\delta t}(s,sp,i,ip)|}{\delta t}, \quad (5.15)$$

$$f_i^{in}(t) = \frac{|\mathcal{F}_{in}^{t,\delta t}(i)|}{\delta t}, \quad (5.16)$$

$$\max_{ip} \{f_{i,ip}^{in}(t)\}. \quad (5.17)$$

Similarly, the *out* frequency features are defined as follows:

$$f_{i,ip,d,dp}^{out}(t) = \frac{|\mathcal{F}_{out}^{t,\delta t}(i,ip,d,dp)|}{\delta t}, \quad (5.18)$$

Table 5.2: Description of *in* frequency features

Feature	Description
$f_{s,sp,i,ip}^{in}(t)$	The number of packets flowing from the endpoint e_s to e_i during $[t, t + \delta t]$ divided by δt .
$f_{s,i,ip}^{in}(t)$	The number of packets flowing from all sp in the endpoint e_s to e_i during $[t, t + \delta t]$ divided by δt .
$f_{s,sp,i}^{in}(t)$	The number of packets flowing from the endpoint e_s to all ip in e_i during $[t, t + \delta t]$ divided by δt .
$f_{s,i}^{in}(t)$	The number of packets flowing from all sp in the endpoint e_s to all ip in e_i during $[t, t + \delta t]$ divided by δt .
$f_{sp,i}^{in}(t)$	The number of packets flowing from specific sp in all endpoints e_s to all ip in e_i during $[t, t + \delta t]$ divided by δt .
$f_{i,ip}^{in}(t)$	The number of packets flowing from all sp in all endpoints e_s to specific ip in e_i during $[t, t + \delta t]$ divided by δt .
$f_i^{in}(t)$	The total number of packets flowing to e_i during $[t, t + \delta t]$ divided by δt .
$\max_{ip}\{f_{i,ip}^{in}(t)\}$	The maximum number of packets over ip flowing to e_i during $[t, t + \delta t]$ divided by δt .

$$f_{i,ip,d}^{out}(t) = \frac{|\bigcup_{\forall dp} \mathcal{F}_{out}^{t,\delta t}(i, ip, d, dp)|}{\delta t}, \quad (5.19)$$

$$f_{i,d,dp}^{out}(t) = \frac{|\bigcup_{\forall ip} \mathcal{F}_{out}^{t,\delta t}(i, ip, d, dp)|}{\delta t}, \quad (5.20)$$

$$f_{i,d}^{out}(t) = \frac{|\bigcup_{\forall ip, dp} \mathcal{F}_{out}^{t,\delta t}(i, ip, d, dp)|}{\delta t}, \quad (5.21)$$

$$f_{i,dp}^{out}(t) = \frac{|\bigcup_{\forall ip, d} \mathcal{F}_{out}^{t,\delta t}(i, ip, d, dp)|}{\delta t}, \quad (5.22)$$

$$f_{i,ip}^{out}(t) = \frac{|\bigcup_{\forall d, dp} \mathcal{F}_{out}^{t,\delta t}(i, ip, d, dp)|}{\delta t}, \quad (5.23)$$

Table 5.3: Description of *out* frequency features

Feature	Description
$f_{i,ip,d,dp}^{out}(t)$	The number of packets flowing from the endpoint e_i to e_d during $[t, t + \delta t]$ divided by δt .
$f_{i,ip,d}^{out}(t)$	The number of packets flowing to all dp from the endpoint e_i to e_d during $[t, t + \delta t]$ divided by δt .
$f_{i,d,dp}^{out}(t)$	The number of packets flowing from all ip in the endpoint e_i to e_d during $[t, t + \delta t]$ divided by δt .
$f_{i,d}^{out}(t)$	The number of packets flowing from all ip in the endpoint e_i to all dp in e_d during $[t, t + \delta t]$ divided by δt .
$f_{i,dp}^{out}(t)$	The number of packets flowing from all ip in e_i to specific dp in all endpoints e_d during $[t, t + \delta t]$ divided by δt .
$f_{i,ip}^{out}(t)$	The number of packets flowing from specific ip in e_i to all dp in all endpoints e_d during $[t, t + \delta t]$ divided by δt .
$f_i^{out}(t)$	The total number of packets flowing from e_i during $[t, t + \delta t]$ divided by δt .
$\max_{ip}\{f_{i,ip}^{out}(t)\}$	The maximum number of packets over ip flowing out of e_i during $[t, t + \delta t]$ divided by δt .

$$f_i^{out}(t) = \frac{|\mathcal{F}_{out}^{t,\delta t}(i)|}{\delta t}, \quad (5.24)$$

$$\max_{ip}\{f_{i,ip}^{out}(t)\}. \quad (5.25)$$

Tables 5.2 and 5.3 explain the meaning of each of these quantities.

5.3.2 Entropy Features

Given a fixed extracted feature f that depends on a parameter j with possible values $j_1, \dots, j_k$, we compute its entropy as follows. Let $F = \{v_{j_i}, i = 1, \dots, k\}$ be the set of possible values of f , v_{j_i} , for each parameter value, j_i , during the observation time interval

$[t, t + \delta t]$. The entropy of f with respect to j is

$$H_f(t) = - \sum_{i=1}^k \left(\frac{v_{ji}}{v} \right) \log_2 \left(\frac{v_{ji}}{v} \right), \quad (5.26)$$

where $v = \sum_{i=1}^k v_{ji}$ is the sum of values in F . The entropy value is between $[0, \log_2 k]$; when the feature exhibits deterministic behavior, the entropy is 0, and when the feature is fully random, the entropy reaches its maximum value $\log_2 k$. In cases where f depends on other parameters, we can fix them and use the same treatment as above to compute the conditional entropy of f given the fixed values of the parameters.

As an example, the entropies $H(sip)$, $H(sp)$, and $H(dp)$ defined in Lu's paper [86] can be computed as particular cases of our model, which is more general.

As an example, the entropies $f_{s,i}^{in}$, $f_{sp,i}^{in}$ and $f_{i,ip}^{in}$, defined in Table 5.2, with respect to s , sp and ip respectively, as follows:

$$\begin{aligned} H_i(f_{s,i}^{in}, t) &= - \sum_s \left(\frac{f_{s,i}^{in}}{\sum_s f_{s,i}^{in}} \right) \log_2 \left(\frac{f_{s,i}^{in}}{\sum_s f_{s,i}^{in}} \right), \\ H_i(f_{sp,i}^{in}, t) &= - \sum_{sp} \left(\frac{f_{sp,i}^{in}}{\sum_{sp} f_{sp,i}^{in}} \right) \log_2 \left(\frac{f_{sp,i}^{in}}{\sum_{sp} f_{sp,i}^{in}} \right), \\ H_i(f_{i,ip}^{in}, t) &= - \sum_{ip} \left(\frac{f_{i,ip}^{in}}{\sum_{ip} f_{i,ip}^{in}} \right) \log_2 \left(\frac{f_{i,ip}^{in}}{\sum_{ip} f_{i,ip}^{in}} \right). \end{aligned}$$

As opposed to Lu and others, our entropy calculations are not limited to those only; they extend to all extracted features discussed above.

5.3.3 Load Features

We define different traffic load features from the matching *in* and *out* frequency features as

$$L_j(t) = \frac{f_j^{in}(t)}{f_{j'}^{out}(t)}, \quad (5.27)$$

where j and j' refer to subscripts of the *in* and *out* matching features presented in Table 5.2 and Table 5.3, respectively. We can generalize this further and allow j and j' to be any

subscripts from the two tables. In that case, the load feature will be:

$$L_{j,j'}(t) = \frac{f_j^{in}(t)}{f_{j'}^{out}(t)}. \quad (5.28)$$

5.4 Computing the features

Grouping packets into flows that yield statistically meaningful observations can be done in different ways. In this work, we use two different approaches that are based on the Riemann scheme to computing features.

The first approach to compute the features is to group them based on one of the fields, for example, time. This approach is reminiscent of the way the integral is defined and computed in the Riemann sense as depicted in Fig. 5.1a. The x axis, which is the time in our case, is partitioned into disjoint δt windows, and the observations within each window are used to compute the features. This approach is called the *Riemann chunking scheme*. Instead of taking the window intervals to be disjoint, another interesting approach is to imagine the window rolling with a fixed offset from the start to the end of the data. This is what we call *Riemann rolling scheme*. The Riemann rolling scheme is of course much more general, and if the offset is set to the window size δt , we obtain Riemann chunking. Although the Riemann chunking scheme is widely used, it is important to emphasize a few of its drawbacks:

- The scheme is not appropriate for the bursty nature of network traffic. Some δt intervals can have few or zero observations, and therefore the computed features are statistically meaningless.
- Machines with heavy loads can be bottlenecks for the Riemann approaches, with a much bigger downside for the chunking approach because this will produce a large number of observations that can cause huge computational latencies for the detection system.
- In a cloud environment, the traffic load spectrum can be so different that some machines have many observations within the time interval while others have none.

The chunking and rolling schemes are illustrated in Fig. 5.1b and Fig. 5.1c, respectively. As shown in Fig. 5.1b, the packet flow is partitioned into equal chunks of size δt in the chunking scheme. In the rolling scheme, depicted in Fig. 5.1c, the chunks are produced by sliding the time windows using a prespecified offset.

Figure 5.1: Riemann approaches

5.5 Dimensionality Reduction

Given that some features may contribute little to the detection process, we use principal component analysis (PCA) [107] [54] to eliminate these features and therefore reduce the dimensions of the previously defined feature space before further processing. PCA is a nonparametric method that allows the automatic identification of significant input features that are computationally efficient and effective for real-world cloud IDSs. Therefore, for each flow, only a subset of the components of the feature vector defined previously will be used as input to the detection algorithm. Based on exploratory experiments on sample data, we have decided to retain (as cutoff) the first four features outputted/obtained by PCA because the remaining PCA features had zero values.

The final representation of the data obtained after the PCA is a sequence of observations consisting of a stream $X_1, X_2, \dots, X_N$, where each observation corresponds to an optimized feature vector X_i associated with and representing a separate packet flow.

5.6 Special relational IP feature transformations

The data source of our cloud intrusion detection system can be of any kind and can emanate from any element of the cloud, such as audit logs, system calls and network traffic,

at any level, including instances, hypervisors and controller nodes. Let us denote by $D(S)$ the data collected from the data source S . Depending on the source type, we filter/match $D(S)$ against a set of fields $f_1, f_2, \dots, f_n$ to obtain raw tables with features $F_1, F_2, \dots, F_n$ corresponding to these fields. These features are qualified as *raw* to distinguish them from the extracted features. This filter/match operation is very essential, especially for unstructured data, and without it we will not be able to proceed further. In the case where $D(S)$ is structured, the filtering/matching can be as simple as taking the fields to be the columns of $D(S)$. Although the raw tables are structured, they will need to be transformed further. In fact, raw tables are usually inconvenient as their raw features are not adequate for further analytics. Moreover, the raw tables can be very wide and reducing their raw features (using a dimension reduction technique) becomes a necessity. They can also be very long (i.e. huge number of observations) and, as such, compacting the number of observations is required. This compactness can be very important to extract meaningful statistical features and reduce the tight dependency between consecutive observations. These extracted features can be further reduced using a dimension reduction transformation. Looking at the many existing extracted features in the literature, and at the complexity and the ad-hoc nature of implementing them, we introduce relational transformations as an easy declarative paradigm for feature extraction.

A *relational transformation* is a relational algebra operator that takes tables (relations) as its input and yields tables (relations) as its output. If the tables are represented as DB tables, then each relational transformation can be expressed as an SQL statement that we run against the tables. This has the power of being easy to use (as it is declarative) and can implement complex operations in a single statement.

To be able to generate meaningful features using relational transformations, we can augment our framework with models that represent the type of data source under consideration. The unreasonable effectiveness of using this paradigm can be seen from a practical example dealing with network traffic as discussed in Chapter 7.

Depending on the number of the extracted features and the detection algorithm used, we might wish to apply a dimension/feature reduction analysis to obtain a limited number of important features - the “optimal” features. In our case this is important as we plan to automate the process of generating and applying relational transformations to produce large number of features.

Starting from the raw tables, we apply selection queries to generate chunks of rows according to one of the chunking schemes described in Section 5.4. Each chunk is then subjected to aggregate transformations that summarize the rows therein. The results are

then reduced using a dimension reduction transformation such as the principle component analysis (Section 5.5). Figure 5.2 illustrates this process. These features are then fed to different detection algorithms, such as E-divisive (see Chapter 6 for more details).

Figure 5.2: Relational Transformation.

5.7 Unstructured nature of TCPdumps

TCPDumps are binary files that store the captured packets and their associated information. To parse these files usually requires a deep knowledge of OSI model, especially TCP, UDP, and IP protocols. Fortunately, tools to read the TCPDump capture files are available and the well-known tool is *Wireshark* [34]. Since we are interesting in running an online detection system and automating the process of generating raw tables from the TCPDumps, we rely on the command line version of *Wireshark*, namely *TShark*. By specifying the fields we are interested in, *TShark* will parse the unstructured TCPDump data and extract the values that corresponds to the fields. Chapter 7 provides a very specific example of using *TShark* to implement our filter/match component. This unstructured nature of TCPDumps is not

restricted to network data but it is relevant to many data sources such as system calls, system logs, and memory dumps.

5.8 Summary

To enable a network-based HIDS to achieve online detection for the cloud computing environment, analysing the statistical features and aggregating properties of the network traffic should be considered. In this chapter, we presented in detail our feature model and extraction approaches which are computed based on the packet's header and network flow at different time windows. We introduced a new instance-oriented feature extraction approach with several new set of extracted features defined for each instance i based on network flow. Our proposed flow features rely mainly on three statistical methods to capture the changes in cloud network traffic behavior, namely, entropy, frequency, and load. We discussed in this chapter, Riemann schemes, namely chunking and rolling, to computing features. Moreover, the new special relational IP feature transformations are discussed.

In the next chapter, we will discuss the change analysis and then present the algorithms used in this dissertation for anomaly detection through change tracking.

Chapter 6

Cloud Intrusion Detection Algorithms

Our general approach for hypervisor-based cloud intrusion detection consists of extracting a set of features from the packet according to the model presented above, and then tracking changes in network behavior through statistical analysis. In this chapter, we discuss change analysis and then present the algorithms used in our work for anomaly detection through change tracking.

6.1 Change Point Analysis

The main objective of change-point analysis is to determine if the monitored time series “data stream” is statistically homogeneous. If the data stream is not homogeneous, a change is detected at the time when the change happens. The change detection problem has been an evolving research area since the 1950s [113]. Although several proposals have been published on using change-point analysis to detect intrusions [88] [128] [5] [120] [133], these proposals have mostly focused on conventional networks. To detect a change point, the data should be received sequentially or in a stream fashion, known as a sequence of observations. The detection occurs when a single change or multiple changes suddenly happen in the distribution at the unknown change points $T_1, T_2, \dots, T_n$. In addition, between every pair of change points, it is usually assumed that the observations are independent and identically distributed. Two statistics are commonly observed to detect change: the mean and variance. The mean was used in the first change-point detection model introduced by [50] for detecting a change in a univariate mean. Then it was extended to detect a change in different settings, for example, in the variance [51], in multivariate change detection [144], and in the nonparametric setting [112] [114], either in a single change point or

multiple change points. The two main types of change-point detection algorithms are batch and sequential, also known as offline and online, respectively. In batch detection, the decision between homogeneity or a change point is made offline only after all observations are received. A fixed length sequence of observations is examined to determine whether any change point occurred at a particular point in the sequence. In contrast, in sequential detection, the decision of homogeneity or a change point is made online while the observations are being received sequentially.

The offline method performs well with a sequence of observations that has only a small number of change points [113] [52] [124].

Detecting changes in the behavior of cloud computing network traffic presents a few challenges:

1. The network traffic for cloud computing is huge by nature; therefore the number of packets will be very large, making storing them for offline analysis difficult.
2. The traffic data consists of a potentially unending stream of data tuples passing through the hypervisor at a very high rate.
3. Detecting the change point on time is crucial for any anomalous network behavior. Hence, the detection in this context needs to be online, in the sense that the detection is carried out on the current data stream to detect the intrusion just when it occurs.
4. Attacks may involve multiple heterogeneous phases (i.e., multistep attacks) that may lead to multiple change points in the data stream, requiring the detector to be continuously tracking and detecting multiple change points.

To overcome these challenges, we seek a robust change-point detection algorithm that performs sequential change detection and can detect multiple change points in stream data. After studying different algorithms, we selected and implemented an R change-point detection package, namely, the ECP package [58]. ECP provides implementation of different methods for nonparametric and sequential multiple change-point analysis of multivariate observations. Moreover, it offers methods to estimate both the number and locations for the multiple change points simultaneously without a priori knowledge of them. Specifically, we use the ECP implementation of the E-divisive algorithm and call it E-Div throughout the thesis [77].

6.2 Change Point-based Intrusion Detection

The E-Divisive method uses both the bisection technique [132] and a multivariate divergence measure [126]. Given two sample sets, $S_n = \{X_1, \dots, X_n\}$ and $R_m = \{Y_1, \dots, Y_m\}$, drawn from two independent and identically distributed random variables, X and Y , respectively, the E-Divisive method calculates the differences in multivariate distributions, which is based on Euclidean distances using a divergence measure defined as

$$\begin{aligned} \hat{\mathcal{E}}(S_n, R_m; \alpha) &= \frac{2}{mn} \sum_{i=1}^n \sum_{j=1}^m |X_i - Y_j|^\alpha - \binom{n}{2}^{-1} \sum_{1 \leq i < k \leq n} |X_i - X_k|^\alpha \\ &\quad - \binom{m}{2}^{-1} \sum_{1 \leq j < k \leq m} |Y_j - Y_k|^\alpha, \end{aligned} \quad (6.1)$$

where α is the moment index: $\alpha \in (0, 2)$. This divergence statistic leads to a consistent approach for estimating change point locations. Let $Z_1, \dots, Z_T \in \mathbb{R}^d$ be an independent sequence of observations, and let $1 \leq \tau < \kappa \leq T$ be constants. Now, define the following sets, $X_\tau = \{Z_1, Z_2, \dots, Z_\tau\}$ and $Y_\tau(\kappa) = \{Z_{\tau+1}, Z_{\tau+2}, \dots, Z_\kappa\}$, and where P_1 and P_2 are corresponding probability distributions, respectively. A change point location $\hat{\tau}$ is then estimated as

$$(\hat{\tau}, \hat{\kappa}) = \underset{(\tau, \kappa)}{\operatorname{argmax}} \hat{\mathcal{Q}}(X_\tau, Y_\tau(\kappa); \alpha), \quad (6.2)$$

where $\hat{\mathcal{Q}}$ is the scaled sample measure of divergence computed from $\hat{\mathcal{E}}$ as follows

$$\hat{\mathcal{Q}}(S_n, R_m; \alpha) = \frac{mn}{n+m} \hat{\mathcal{E}}(S_n, R_m; \alpha).$$

After the first estimation for a change point, a statistical test is performed to confirm its statistical significance. The change detection consists of testing the following statistical hypothesis of homogeneity in distribution ($H_0 : P_1 = P_2$) versus significant distributional change ($H_1 : P_1 \neq P_2$). A change is deemed to have occurred at Z_τ if the null hypothesis H_0 is rejected.

To estimate multiple change points, the above technique is applied repeatedly until all change points in the bisections are found. Assume that $n - 1$ points have been estimated at $0 < \tau_1 < \tau_2 < \dots < \tau_{n-1} < T$; this divides the set of observations into n clusters $\Sigma_j = \Sigma_{\tau_{j-1}+1}, \Sigma_{\tau_{j-1}+2}, \dots, \Sigma_{\tau_j}$, where $1 \leq j \leq n, \tau_0 = 0, \tau_n = T$.

The n^{th} change point is estimated by applying the same procedure for finding a single point to the observations within each of the n clusters, and then taking the point corresponding to the maximum test statistic over all clusters. Because the underlying distribution is unknown, a permutation test is applied to determine the significance of the corresponding test statistic by permuting the observations in each of the n clusters and reapplying the above estimation process to the permuted observations. By performing a number r of permutations, an approximate p-value p is computed. The algorithm uses a fixed p-value $p_0 \in [0, 1]$. The n^{th} change point is considered significant if $p \leq p_0$; otherwise, there is no additional change point.

As mentioned earlier, we use the E-Divisive implementation of the ECP [77]. The E-Divisive algorithm is defined as $E - Div((X_i)_{i=1}^{i=T}, (m, \alpha, s, r))$, a function that returns a set of change points, and takes the following input parameters:

- $(X_i)_{i=1}^{i=T}$: the sequence of observations;
- m : the minimum number of observations required by the E-Div;
- α : the moment index used for determining the distance between segments;
- s : the significance level;
- r : the number of permutations used to compute the p -values.

The online E-Div change detection algorithm is summarized in Algorithm 2.

6.3 Intrusion Decision

Our proposed approach uses change-point techniques to detect any behavior changes. The main assumption is that changes occur due to abnormal activities. An ideal IDS will not raise an alert until a change in behavior occurs as a consequence of malicious activities. However, such an ideal system does not exist because the so-called normal behavior depends on many factors, which usually include the human factors, and this "normal behavior" can change depending on different circumstances. Anomaly detection techniques are more general and can detect changes due not only to malicious activities but also to legitimate ones. As such, using change-point detection requires building a baseline model to tune the parameters of the change detection algorithm so that it is sensitive to the changes caused by malicious activities. Using such an approach, any change detected can be attributed to change in the malicious distributions between two successive segments. It is

Algorithm 2 Summary of online E-Div change detection algorithm

Input: A new observation point X_T , significance level (s),

Number of permutations (r),

Number of change point locations to estimate (k), Minimum number of observations between change points (m), The moment index (α)

Output: Change points $X_{d_1}, \dots, X_{d_h}$

- 1: **Initialization:** Add X_T to the observations seen so far, $X_1, \dots, X_{T-1}$, and initialize the set of clusters $C = \{[1, T]\}$
 - 2: $i \leftarrow 0$
 - 3: **while** $i < k \wedge C \neq \emptyset$ **do**
 - 4: $[a, b] \leftarrow$ remove an interval (cluster) from C
 - 5: $(\hat{\tau}, \hat{\kappa}) \leftarrow \underset{(\tau, \kappa)}{\operatorname{argmax}} \left(\hat{\mathcal{Q}}((X_j)_{j=a}^{j=a+\tau}, (X_n)_{n=a+\tau+1}^{n=a+\kappa}; \alpha) \right),$
 where $\tau \in [m, b - m - a - 1]$ and $\kappa \in [\tau + m + 1, b - a]$
 - 6: $p \leftarrow$ the p-value of the significance testing based on the two intervals $[a, a + \hat{\tau}]$ and $[a + \hat{\tau} + 1, b]$
 - 7: **if** $p \leq s$ **then**
 - 8: $i = i + 1$
 - 9: $X_{d_i} = X_{a+\hat{\tau}}$
 - 10: insert $[a, a + \hat{\tau}]$ and $[a + \hat{\tau} + 1, b]$ into C
 - 11: **end if**
 - 12: **end while**
 - 13: **return** $X_{d_1}, \dots, X_{d_h}$
-

important to detect not only the starting time of the malicious activity but also the changes during this activity and its end.

We derive the baseline model using the gradient descent approach to tune the parameters of E-Div on sample data. The E-Div parameters described earlier are passed to the baseline model, which is described in Algorithm 3. The output is then fed to the E-Div to perform the change-point detection over incoming observation streams.

Algorithm 3 Building the Baseline Model

Input: X : sequence of observations $(X_k)_{k=1}^{k=N}$, N is the number of observations, l_k : is the label for the observation X_k , $l_k \in \{0, 1\}$, $l_k = 1$ for normal and $l_k = 0$ for malicious.

Output: (m, α, s, r)

Initialize (m, α, s, r) **to** $(30, 1, 0.05, 499)$.

- 1: $k \leftarrow 1$
 - 2: **while** $k < N$ **do**
 - 3: $(p_k, d_k) = \text{EDiv}((X_i)_{i=1}^{i=k}, (m, \alpha, s, r))$ (p_k is the p-value, and d_k is true if X_k is a change)
 - 4: $O(k) = \sum_{i=1}^{i=k} (p_k - l_k)^2$ ($O(k)$ is the Euclidean cost function)
 - 5: $(m, \alpha, s, r) = (m, \alpha, s, r) - \epsilon \times \nabla(O(k))$ (ϵ is the learning rate)
 - 6: $k = \min(k + m, N)$
 - 7: **end while**
 - 8: **return** (m, α, s, r)
-

The initialization parameter values in the baseline algorithm, $s = 0.05$ and $r = 499$, are default values used in E-Div implementations, whereas $\alpha = 1$ was chosen to detect any distributional change. The value $m = 30$ was based on an exploratory experiment conducted with a small data sample (outlined in subsection 7.1), although such values can be arbitrary.

After the E-Div parameters are tuned for the intrusion decision based on the baseline model, we can use them in detection mode as shown in Algorithm 4.

It is worth pointing out that Algorithm 3 is used as a hyperparameter tuning algorithm. Once the parameters are tuned, the E-Div anomaly detection algorithm uses them as they are without any further tuning. In this sense, we conform to the definition of anomaly detection. However, Algorithm 3 can be applied for supervised learning as well in the sense that E-Div anomaly detection algorithm can call the baseline model from time to time, depending on the data labelling, to retune the parameters. This can be very effective especially in the case where the E-Div detection starts reporting too many false behavioral changes.

Furthermore, baselining and testing are done per instance. A baseline is built for each instance and is submitted to E-Div for anomaly detection.

Algorithm 4 E-Div Intrusion Decision

Input: X_k
Output: F_k

Initialization: Sequence of previous observations $X_1, X_2, \dots, X_{k-1}$; the baseline model M_l with parameters $(\hat{m}, \hat{\alpha}, \hat{s}, \hat{r}), l < k$

- 1: $C_k \leftarrow EDiv(X_k, (\hat{m}, \hat{\alpha}, \hat{s}, \hat{r}))$;
- 2: **if** ($C_k == true$) **then**
- 3: $F_k \leftarrow$ Intrusion
- 4: **else**
- 5: $F_k \leftarrow$ Normal
- 6: **end if**
- 7: **return** F_k

6.4 Summary

The discussion in this chapter focused on the algorithms used in our work for anomaly detection through change tracking. Our proposed approach uses change-point techniques to detect any behavior changes. Using a change-point detection requires building a baseline model to tune the parameters of the change detection algorithm so that it is sensitive to the changes caused by malicious activities. Using such an approach, any change detected can be attributed to change in the malicious distributions between two successive segments. It is important to detect not only the starting time of the malicious activity but also the changes during this activity and its end. In this chapter, we presented in detail and discussed the change-point detection algorithm that performs sequential change detection and can detect multiple change points in stream data, namely E-divisive algorithm. Moreover, we introduced our derived baseline model using the gradient descent approach to tune the parameters of E-divisive algorithm on sample data.

The comprehensive experiments and results of our new proposed hypervisor-based cloud intrusion detection system will be presented and discussed in the next chapter.

Chapter 7

Experiments and Results

In this section, we present some preliminary results based on sample data, then introduce the evaluation metrics, and finally conduct a large-scale evaluation of our proposed detection model based on the entire dataset.

7.1 Preliminary Experiments

As outlined earlier, we considered two different approaches for computing features: Riemann rolling and Riemann chunking. In this section, we study and compare the performance of E-Div when used in combination with each of the aforementioned schemes. We ran a series of experiments using one supercomputing machine (see Table 7.1) and one day of hypervisor network traffic from ISOT-CID for one attack scenario (see Fig. 7.1), focusing on VMs that launched in one cloud node. Further investigations were carried out with one VM (VM8).

Figure 7.1: Sample attack scenario in ISOT-CID in Phase 1 (Day 1)

Figure 7.2: First attack round for inside and outside attacks (Phase 1 - Day 1)

Table 7.1: Supercomputing machine specifications

OS	Specification
Centos	RAM: 236GB CPU: 28 cores Clock Speed: 2.40GHZ

The goal was to detect the change points in the network traffic behavior and recognize an attack after it had happened without any long delays. A variety of parameter settings were used to compare between different E-Div's effectiveness when detecting similar types of changes and deduce the accurate setting.

7.1.1 Sample Attack Scenario Details

In the attack scenario outlined in Fig. 7.1 and Fig. 7.2, which was carried out in Day 1 (Phase 1), four different types of attacks were performed by the attacker. The first two were scanning the cloud network and launching a dictionary attack against VM8. These attacks were performed as outsider attacks. The time of the scanning attack was around 09:37, and the dictionary attack was around 09:41. After the attacker obtained valid credentials and logged on, the attack changed to an insider perspective, and a scanning attack was launched to discover the internal cloud network at 9:45. From around 10:07 to 10:31, the attacker performed different malicious activities such as repeated arbitrary logins and logouts, files transfers, and downloads. At 10:30, the attacker ran a ports scan against VM5 located in the other cloud node. After that, at around 10:36, a dictionary attack was launched against the VM5. Multiple logins and logouts occurred from around 10:38 to 10:45. The third type of attack was the attacker pinging the same machine at around 10:46, followed by downloading a file at around 10:47. The last type of attack, launched at around 11:01 by the attacker, was a failed DoS attack against VM4 located in the other cloud node. Finally, the recorded attacks ended by pinging VM4 at around 11:04 from VM8 (see Sec. 4.4.2 for more details).

7.1.2 Detection Using Chunking Scheme

In this approach, the offset 2.0 was chosen, and different values were studied for m , α , s , r , and k during the experiments to reach the optimum setting. Other values of the offset (e.g., 4.0) failed to yield any meaningful results.

The experiments started by varying m , α , s , and r to reach the optimum settings, which were found to be $\alpha = 1$ (because we are looking for any distributional change), $s = 0.05$, $r = 199$, and $m = 30$, and these were used along with $k = 100$ and $k = NULL$. Table 7.2 summarizes the detection of multiple change points for VM8. From the table, it can be seen that the change points caused by scanning attacks were only detected for the first one at 09:38:27.491, which indicates that E-Div with this setting does not perform well in detecting scanning attacks. Moreover, the second attack that changed the network behavior was the dictionary attack, which happened around 9:41 and 10:36. Note that the dictionary attacks were also missed (i.e., not detected) when chunking was used with that setting.

Table 7.2: Multiple change points detected using E-Div for VM8 with Riemann chunking scheme

Attack periods	09:37 - 9:41	09:42 - 9:45	10:06 - 10:37	10:43 - 10:48	10:48 - 11:07
E-Div Parameters	Scanning, Dictionary attack	Scanning	Transfer a file, Download a Program, Scanning, Dictionary attack	Ping the same machine, Download a Program	Failed DoS attack, Ping VM4
$(m, k, \alpha = 1, s = 0.05, r = 199)$					
offset=2.0 $m=30$ $k = NULL$	Yes	No	No	No	Yes
$m=30$ $k=100$	Yes	No	Yes	No	Yes

7.1.3 Detection Using Rolling Scheme

In this approach, to study the benefits of keeping some previous network traffic with the new one for detection, different offsets for window size were used. The offset ranges of 0.05, 0.1, 0.5, and 1.5 were used. Similarly to the chunking scheme, different values were used for m , α , s , r , and k . For α , s , and r , similar values that were used before for chunking were used; for k , 100, and NULL were used, whereas for m , 30, 40, 50, and 100 were used. The change-point detections for the different offset, k , and m values are presented in Fig. 7.4, Fig. 7.5, and Fig. 7.6 and summarized in Table 7.3. Table 7.4 shows the corresponding estimated detection times. In the figures, a change is detected using all four features at a time, and is shown as a red line, and the estimation of the change point is shown as a blue dashed line.

From the results, note that the rolling scheme contributed to the detection of a scanning attack with different offsets. For example, when the offset was 0.05, the change points were detected at the estimated times of 09:32:22.787 and 09:46:53.57, whereas the last change point, which was at 10:34, was missed. However, when the offset was chosen to be 0.5, the E-Div was able to detect all the change points of the scanning attack at 09:38:28.491, 09:49:53.637, and 10:34:15.847.

The second attack that changed the network behavior was the dictionary attack, which happened around 9:41 and 10:36. The dictionary attacks were missed when chunking was used with that setting. However, with rolling, the algorithm was able to detect both attack times with all settings in most cases.

The third attack type is ping. The attacker pinged VM8 at around 10:46 and VM4 at around 11:05. Generally, the algorithm performed well at detecting this attack when using the rolling scheme, except when the offset was 0.1, where only one attack was detected.

Figure 7.3: Building the baseline for VM8 with 180 normal samples

Table 7.3: Change points detected when using rolling and E-Div with different offsets

Attack periods		09:37 - 9:41	09:42 - 9:45	10:06 - 10:37	10:43 - 10:48	10:48 - 11:07
E-Div Parameters ($m, k, \alpha = 1, s = 0.05, r = 199$)		Scanning, Dictionary attack	Scanning	Transfer a file, Download a Program, Scanning, Dictionary attack	Ping the same machine, Download a Program	Failed DoS attack, Ping VM4
offset=0.05	$m=50$ $k=100$	No	Yes	Yes	Yes	Yes
offset=0.1	$m=50$ $k=100$	No	No	Yes	Yes	No
offset=0.5	$m=30$ $k = NULL$	Yes	No	Yes	Yes	Yes
	$m=40$ $k = NULL$	Yes	No	Yes	Yes	Yes
	$m=100$ $k=100$	Yes	No	Yes	Yes	Yes
offset=1.5	$m=40$ $k = NULL$	No	Yes	Yes	Yes	Yes
	$m=30$ $k=100$	Yes	No	Yes	Yes	Yes

The last attack is the DoS attack launched at around 11:00. Even though this attack failed, this attempt was detected on time, when using rolling, for all settings except the offset 0.1, which missed it.

(a) Riemann rolling offset 0.05

(b) Riemann rolling offset 0.1

Figure 7.4: Comparison between two offsets for Riemann rolling when the E-Div settings are $m = 500$ and $k = 100$ for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks.

7.1.4 Comparison and Discussion

Looking at the change points detected during the full attack periods reveals that E-Div performed well when rolling was used compared with chunking. For example, the dictionary attacks were missed when Riemann chunking was used. However, with rolling, the algo-

(a) $m=30, k = NULL$ (b) $m=40, k = NULL$ (c) $m=50, k=100$

Figure 7.5: Comparison between three E-Div settings for Riemann rolling when the offset is 0.5 for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks.

(a) $m=30, k = NULL$ (b) $m=30, k = 100$

Figure 7.6: Comparison between two E-Div settings for Riemann rolling when the offset is 1.5 for the four different PCA features. The dashed vertical lines correspond to the detected change points or attacks.

rithm was able to detect both attack times almost with all settings. Moreover, with rolling, the algorithm performed well with three selected offsets and only missed one attack period. In contrast, the offset 0.1 was able to detect only two attack periods. The scanning attack is the noticeable attack missed by most of the settings, and it was only detected by

Table 7.4: Estimated detection times for specific attacks with different offsets when using rolling and E-Div

E-Div Parameters ($m, k, \alpha = 1, s = 0.05, r = 199$)		Attack Type & Time	Scanning			Dictionary		DoS	Malicious Activities
			9:37	9:45	10:34	9:41	10:36	11:00	Different times
offset=0.05	$m=50$	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
	$k=100$	estimated time at 9:32:22.787	estimated time at 9:46:53.572		estimated time at 9:46:53.572	estimated time at 10:36:49.112	estimated time at 11:00:02.204		especially transfer/download files and multiple logins within short time
offset=0.1	$m=50$	Yes	Yes	No	Yes	No	No		Yes
	$k=100$	estimated time at 9:33:35.884	estimated time at 9:51:43.877		estimated time at 9:51:43.877				especially transfer/download files and multiple logins within short time
offset=0.5	$m=30$	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes
	$k = NULL$	estimated time at 9:38:28.491	estimated time at 9:49:53.637	estimated time at 10:34:15.847	estimated time at 9:49:53.637		estimated time at 11:00:03.204		especially transfer/download files and multiple logins within short time
	$m=40$	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	$k = NULL$	estimated time at 9:38:28.491	estimated time at 9:49:53.637	estimated time at 9:49:53.637	estimated time at 10:36:49.212	estimated time at 10:36:49.212	estimated time at 11:00:02.704		especially transfer/download files and multiple logins within short time
offset=1.5	$m=100$	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
	$k=100$	estimated time at 9:38:28.491	estimated time at 9:51:43.777		estimated time at 9:51:43.777	estimated time at 9:36:49.212	estimated time at 11:00:02.204		especially transfer/download files and multiple logins within short time
	$m=40$	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	$k = NULL$	estimated time at 9:32:22.787	estimated time at 9:46:53.572	estimated time at 10:32:59.957	estimated time at 9:46:53.572	estimated time at 10:36:59.212	estimated time at 11:00:03.204		especially transfer/download files and multiple logins within short time
offset=1.5	$m=30$	No	No	No	Yes	Yes	No		Yes
	$k=100$				estimated time at 9:51:44.277	estimated time at 10:36:44.212			especially transfer/download files and multiple logins within short time

rolling with offset 0.05 and offset 1.5 when $k = NULL$ and $m = 40$. One of the important findings from these experiments is the choice of $k = NULL$. Although it provides a good detection result, it is not applicable to use in cloud intrusion detection because of its long running time. Another point that should be mentioned is the choice of the offset and E-Div parameters. These should be selected carefully because there is a trade-off between the detection of small changes in the statistics, which may cause false change-point detection, with detection of only large changes, which will cause important change points to be missed.

In conclusion, the results and analyses of the preliminary experiments conducted above show that our proposed features, along with the two Riemann approaches, contributed to the detection of change points. As mentioned previously, each VM has different network behavior, and one setting for all VMs will not work, as expected. Therefore, we recommend using the Riemann rolling scheme with the extracted features, and adjusting the parameters according to the VM's needs, which can be done automatically using our baselining approach based on Algorithm 3.

7.2 Evaluation Metrics

In the proposed approach, after a change is detected, an estimate for its location is returned. If the observation at that location is malicious, then we assume the change is caused by a malicious activity, and the change is qualified as a **True Positive (TP)**. If the observation at the estimated location is normal, then it could be that the malicious behavior falls in an observation window denoted by δO that surrounds it. If that is the case, the change is still qualified as TP. Otherwise, it is qualified as a **False Positive (FP)**. If the detection algorithm failed to detect a malicious observation that might cause a change, we refer to the location of such an observation as a **False Negative (FN)**. The remaining normal observations that do not cause any change are referred to as **True Negatives (TN)**. We calculate the False Positive Rate (FPR) and the Detection Rate (DR) as follows:

$$FPR \% = 100 \times \frac{\sum FP}{\sum (FP + TN)} \quad (7.1)$$

$$DR \% = 100 \times \frac{\sum TP}{\sum (TP + FN)} \quad (7.2)$$

7.3 Evaluation Results

To evaluate our proposed detection scheme, we used Algorithm 3 to build a separate baseline for each instance using sample traffic from Day 1 of Phase 1, by setting the learning rate $\varepsilon = 0.001$. For instance, Fig. 7.3 shows sample traffic from Day 1 (Phase 1) for VM8, and normal samples (in the amount of 180) used for the initial value of m in baselining at the beginning of the stream. After building the baselines, we used all the remaining traffic (i.e., unused Day 1 [Phase 1] traffic, and all the traffic from remaining days of Phase 1 and Phase 2).

Tables 7.5 and 7.6 show the detection accuracy obtained for different VM instances with corresponding baseline parameter values over different days and the overall results for each VM obtained by aggregating the misclassification counts for all days. For instance, the overall FPR for a given VM is obtained as the ratio of the sums of all FPs over all days by the total count of normal samples for all days for the given VM.

From the above tables, some obtained results show that if the VM receives only a small amount of traffic, either normal or malicious, that will not help the algorithm build enough statistics for detection. Moreover, the change on the VM's operation mode, for example,

Table 7.5: Phase 1 detection results

		Days	Day 1		Day 2		Day 3		Day 4		Overall	
Nodes	M_l Parameters ($r = 499, s = 0.05,$ $k = 100, \alpha = 1$)	VMs	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %
A	$m = 140$	VM 2	5.19	93	14.65	36.40	0	100	7.44	0	9.78	75
	$m = 150$	VM 3	17.50	100	17.92	100	0	100	0	100	12.47	100
	$m = 12$	VM 4	10.86	100	23.07	95.45	21.59	100	21.59	100	18.85	98.76
	$m = 60$	VM 5	6.60	100	6.23	100	5.48	0	6.23	0	6.16	98.50
	$m = 100$	VM 6	8.43	100	10.45	86.81	10.86	48.27	8.73	0	9.83	73.68
B	$m = 130$	VM 7	0.64	100	9.71	22.22	9.98	0	13.08	100	8.52	58.08
	$m = 180$	VM 8	0	100	1.99	100	0	100	0	100	0.88	100
	$m = 81$	VM 9	0	100	21.56	100	0	0	0	100	17.73	87.74
	$m = 180$	VM 10	1.59	72.50	5.27	97.74	3.70	0	0	100	3.71	96.04

from being a multiple high-volume traffic environment to a low-volume closed environment will affect the accuracy result, and the initial learned baseline should be adjusted (or adapted) based on that change. For example, the operation of VM7 has been changed during some days in both phases without considering rebuilding the baseline. This caused the traffic to change from multiple high-volume traffic into a small amount of normal or malicious traffic, which impacted the effectiveness, diminished the DR, and increased the FPR. On the other hand, the VMs that remain on the same learned operational environment such as VM4 and VM8 give a good indicator of the detection accuracy.

The obtained global results are shown in Table 7.7 for all nodes. For node A, the obtained global results consist of $DR = 94.77\%$ and $FPR = 10.42\%$ for phase 1 and $DR = 96.70\%$ and $FPR = 13.23\%$ for phase 2. Moreover, the obtained global results for node B consist of $DR = 96.11\%$ and $FPR = 7.34\%$ for phase 1 and $DR = 95.94\%$ and $FPR = 5.66\%$ for phase 2. The overall effectiveness for all nodes during both phases consist of $DR = 96.23\%$ and $FPR = 7.56\%$

The obtained results are very encouraging and provide indication of the strong potential of the approach to detect novel attack patterns, which is crucial in the fast evolving cloud threat landscape that is characterized by an increasing number of unknown threat vectors.

Table 7.6: Phase 2 detection results

Note: The (-) sign represents the effectiveness values that cannot be obtained due to the observations being either all normal or all malicious for corresponding days.

Nodes	M_I Parameters ($r = 499, s = .05,$ $k = 100, \alpha = 1$)	Days			Day 1		Day 2		Day 3		Day 4		Day 5		Day 6		Overall	
		VMs	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %	FPR %	DR %
A	$m = 150$	VM 3	-	94.19	0	98.05	0	0	0	0	-	98.83	-	97.62	-	96.13	0	97.31
	$m = 100$	VM 6	12.74	98.85	6.77	85.35	18.73	90.33	12.38	98.29	17.59	79.96	14.13	92.88	13.24	91.01		
B	$m = 130$	VM 7	100	-	-	68.89	-	100	-	43.46	-	0	95.20	62.33	86.02			
	$m = 180$	VM 8	1.18	97.39	0	98.60	2.55	91.50	0.91	94.10	1.10	98.35	0.68	99.20	1.07	97.62		
	$m = 180$	VM 10	20.05	71.03	1.84	90.65	13.80	79.57	4.46	94.22	13.11	97.10	7.43	95.93	8.81	97		

Table 7.7: Global detection results for all nodes

Phases	Nodes		Node A		Node B	
			FPR %	DR %	FPR %	DR %
Phase 1			10.42	94.77	7.34	96.11
Phase 2			13.23	96.70	5.66	95.94
Aggregate Per Node			12.69	96.70	5.77	95.95
Overall Effectiveness			FPR %		DR %	
			7.56		96.23	

7.4 Summary

This chapter presented the experimental results obtained in evaluating our proposed approach for cloud intrusion detection. We performed some preliminary experiments using our proposed approaches for computing features, precisely Riemann rolling and Riemann chunking. Moreover, we studied and compared the effectiveness of E-Div when used in combination with each of the aforementioned schemes. We varied the chosen values for both the Riemann offset and E-Div parameters to obtain the optimum setting. We observed that, each VM has different network behavior, and one setting for all VMs will not work, as expected. Therefore, we recommended using the Riemann rolling scheme with the extracted features, and adjusting the parameters according to the VMs needs. This can be done automatically using proposed baselining approach. After varying E-Div parameters m , α , s , and r to reach the optimum settings, we evaluated our framework by performing our change points detection to the entire dataset, during the full attack periods and for all VMs.

The obtained results from the comprehensive experiments are very encouraging. It provides indication of the strong potential of the approach to detect novel attack patterns, which is crucial in the fast evolving cloud threat landscape that is characterized by an increasing number of unknown threat vectors. To that end, the final chapter of the dissertation will conclude this research work by summarizing the contributions and outlining some possible directions for future work.

Chapter 8

Conclusion

The adoption of cloud computing has increased dramatically in recent years due to its attractive features. Shifting towards cloud computing is attracting not only industry but also government and academia. However, given their stringent privacy and security policies, this shift is still hindered by many security concerns related to the cloud computing features. Therefore, there is a dire need for systems that can detect and protect the cloud from malicious activities and that could be achieved by a proper cloud intrusion detection system.

Building a robust cloud intrusion detection system is a challenging task. This not only requires datasets that represent the real cloud environment, but also extracting useful features from the data is a very important aspect to achieve effective detection capability.

In this dissertation, we step forward and take action and provide to the research communities a full approach by creating and connecting all angles to enhance the cloud computing security. In this dissertation a new cloud intrusion dataset has been collected and a new feature model for cloud network has been presented. Moreover, a new intrusion detection framework based on change point detection algorithm has been implemented and empirically tested.

8.1 Contributions Summary

To overcome the aforementioned challenges and plugging the gaps in the research literature for establishing a strong trust in cloud computing, this dissertation contributes in several ways to provide an effective security monitoring and defense system adequate for the cloud. The main contributions of the dissertation are summarized in the following.

In this dissertation we introduced a new cloud intrusion detection dataset (ISOT-CID). ISOT-CID is addressing the lack of a publicly available dataset, it is to our knowledge the first publicly available dataset of its kind. The dataset was collected in a production environment in partnership with a cloud service provider (CSP). It covers a variety of logs and data sources that will enable the development of diverse intrusion data models, feature sets and analysis models. Moreover, it involves multiple attack scenarios, covering both remote and inside attacks, and attacks originating from within the cloud. It has a mixture of both normal and intrusive activities, and it is labeled. The dataset was collected over two phases and over several days, and it involves several hours of attack data, culminating into a few terabytes. It is large and diverse enough to accommodate various effectiveness and scalability studies.

A new multidimensional feature space and a new feature extraction model for hypervisor-based cloud intrusion detection called *instance-oriented feature extraction* were introduced. The new model leverages the correlated behavior of instances running on a hypervisor to improve cloud feature extraction and anomaly detection. Moreover, we introduced two different approaches that were based on the Riemann scheme to computing features.

The contribution of the feature model has been extended further to another contribution called *special relational IP feature transformations*. As we proposed above, most of the extracted features rely on counting, selecting some columns and grouping the data. As such we proposed using relational database operators to express and implement our extracted features. Each extracted feature is therefore viewed as a relational transformation of the raw data, more precisely the raw tables. This novel framework allows us to combine the realm of feature engineering and the realm of relational algebra/databases to produce extracted features. By doing so, we can even automate the process of generating features instead of relying on the human-fashioned ones. Starting from the raw tables, we applied selection queries to generate chunks of rows according to one of the Riemann schemes. Each chunk was then subjected to aggregate transformations that summarize the rows therein. The results were then reduced using a dimension reduction transformation such as the principle component analysis.

A new hypervisor-based cloud anomaly detection model that uses multivariate sequential change detection combined with an initial baselining model based on the gradient descent algorithm is proposed. Our general approach for hypervisor-based cloud intrusion detection consists of extracting a set of features from the network packet according to the model presented above, and then tracking changes in network behavior through statistical analysis. We sought a robust change-point detection algorithm that performs sequential

change detection and can detect multiple change points in stream data. We derived the baseline model using the gradient descent approach to tune the parameters of the detection algorithm.

Finally, the framework was evaluated on the entire dataset. The overall effectiveness for all nodes during both phases consisted of $DR = 96.23\%$ and $FPR = 7.56\%$. The results shows that the framework is promising in terms of detection effectiveness. It provides indication of the strong potential of the approach to detect novel attack patterns, which is crucial in evolving cloud threat environment characterized by an increasing number of novel attack patterns.

8.2 Future Work

While the work in this dissertation has already led to new contributions, there are couple of directions in which our work can be improved. One future avenue of research is to extend the ISOT-CID by adding different application types and emerging attack vectors. Although exploitations of novel vulnerabilities, such as, *Meltdown* and *Spectre* and other forms of cross-VM attacks (e.g., VM escape) may not have much impact on the type of data used in evaluating our current detection model, they are relevant to some of the other data sources collected in ISOT-CID.

Another potentially fruitful direction worth exploration is to apply our proposed approach to the additional data sources, such as system calls, system logs, and resource usages. The aggregation of such diversified data sources will strengthen the effectiveness of the proposed hypervisor-based cloud IDS and improve its detection accuracy.

Another direction for the future work is to extend the proposed feature extraction model by introducing *a hypervisor-oriented feature extraction*. In a production cloud, the nodes are usually segregated into partitions each handling a specific workload. If the correlation between the network flows of the hypervisors exist, this could be leveraged to improve cloud feature extraction and anomaly detection. In addition, our characterization of anomalous network behavior focuses on three major aspects: frequency, load, and randomness. We will investigate and integrate in our model more anomalous network behavioral characteristics beyond the aforementioned.

A final suggestion for future work is to develop a service-oriented architecture and a dataflow framework for cloud intrusion detection which can be deployed and integrated with the existing services of the *cloud operating systems*.

Bibliography

- [1] Mohamed Abdlhamed, Kashif Kifayat, Qi Shi, and William Hurst. A system for intrusion prediction in cloud computing. In *Proceedings of the International Conference on Internet of things and Cloud Computing*, page 35. ACM, 2016.
- [2] Omar Achbarou, My Ahmed El Kiram, and Salim Elbouanani. Cloud security: A multi agent approach based intrusion detection system. *Indian Journal of Science and Technology*, 10(18), 2017.
- [3] Azuan Ahmad, Norbik Bashah Idris, and Mohd Nazri Kama. Cloudids: Cloud intrusion detection model inspired by dendritic cell mechanism. *International Journal of Communication Networks and Information Security (IJCNIS)*, 9(1), 2017.
- [4] Azuan Ahmad, Bharanidharan Shanmugam, Norbik Bashah Idris, Ganthan Nayarana Samy, and Sameer Hasan AlBakri. Danger theory based hybrid intrusion detection systems for cloud computing. *International Journal of Computer and Communication Engineering*, pages 650–654, 2013.
- [5] Leman Akoglu and Christos Faloutsos. Event detection in time series of mobile communication graphs. In *Army science conference*, pages 77–79, 2010.
- [6] Zayed Al Haddad, Mostafa Hanoune, and Abdelaziz Mamouni. A collaborative framework for intrusion detection (c-nids) in cloud computing. In *Cloud Computing Technologies and Applications (CloudTech), 2016 2nd International Conference on*, pages 261–265. IEEE, 2016.
- [7] Abdulaziz Aldribi and Issa Traore. A game theoretic framework for cloud security transparency. In *International Conference on Network and System Security*, pages 488–500. Springer, 2015.

- [8] Abdulaziz Aldribi, Issa Traore, and Gabriel Letourneau. Cloud slicing a new architecture for cloud security monitoring. In *Communications, Computers and Signal Processing (PACRIM), 2015 IEEE Pacific Rim Conference on*, pages 18–22. IEEE, 2015.
- [9] Abdulaziz Aldribi, Issa Traore, and Belaid Moa. *Data Sources and Datasets for Cloud Intrusion Detection Modeling and Evaluation*, pages 333–366. Springer International Publishing, Cham, 2018.
- [10] Nouf Saleh Aljurayban and Ahmed Emam. Framework for cloud intrusion detection system service. In *Web Applications and Networking (WSWAN), 2015 2nd World Symposium on*, pages 1–5. IEEE, 2015.
- [11] Cloud Security Alliance. *Sampling of issues we are addressing*, 2009.
- [12] Saeed M. Alqahtani, Maqbool Al Balushi, and Robert John. An intelligent intrusion detection system for cloud computing (SIDSCC). In *2014 International Conference on Computational Science and Computational Intelligence*. IEEE, mar 2014.
- [13] James P Anderson et al. Computer security threat monitoring and surveillance. Technical report, Technical report, James P. Anderson Company, Fort Washington, Pennsylvania, 1980.
- [14] Kamatchi Arjunan and Chirag N Modi. An enhanced intrusion detection framework for securing network layer of cloud computing. In *Asia Security and Privacy (ISEASP), 2017 ISEA*, pages 1–10. IEEE, 2017.
- [15] Francesco Maria Aymerich, Gianni Fenu, and Simone Surcis. An approach to a cloud computing network. In *Applications of Digital Information and Web Technologies, 2008. ICADIWT 2008. First International Conference on the*, pages 113–118. IEEE, 2008.
- [16] LD Dhinesh Babu, P Venkata Krishna, A Mohammed Zayan, and Vijayant Panda. An analysis of security related issues in cloud computing. In *International Conference on Contemporary Computing*, pages 180–190. Springer, 2011.
- [17] W Baker, M Goudie, A Hutton, C Hylender, J Niemantsverdriet, C Novak, D Osertag, C Porter, M Rosen, B Sartin, et al. Verizon 2010 data breach investigations report. *Verizon Business*, 2010.

- [18] Aman Bakshi and Yogesh B. Dujodwala. Securing cloud from DDOS attacks using intrusion detection system in virtual machine. In *2010 Second International Conference on Communication Software and Networks*. IEEE, 2010.
- [19] Aman Bakshi and Yogesh B Dujodwala. Securing cloud from ddos attacks using intrusion detection system in virtual machine. In *Communication Software and Networks, 2010. ICCSN'10. Second International Conference on*, pages 260–264. IEEE, 2010.
- [20] Daniel Barbará and Sushil Jajodia. *Applications of data mining in computer security*, volume 6. Springer Science & Business Media, 2002.
- [21] T Berners-Lee, R Fielding, and L Masinter. Std66 rfc3986: Uniform resource identifier (uri) generic syntax. ietf full standard rfc, 2005.
- [22] Jon Brodtkin. Gartner: Seven cloud-computing security risks. *Infoworld*, 2008:1–3, 2008.
- [23] Glenn Brunette, Rich Mogull, et al. Security guidance for critical areas of focus in cloud computing v2. 1. *Cloud Security Alliance*, pages 1–76, 2009.
- [24] Iker Burguera, Urko Zurutuza, and Simin Nadjm-Tehrani. Crowdroid: behavior-based malware detection system for android. In *Proceedings of the 1st ACM workshop on Security and privacy in smartphones and mobile devices*, pages 15–26. ACM, 2011.
- [25] Rajkumar Buyya, Chee Shin Yeo, and Srikumar Venugopal. Market-oriented cloud computing: Vision, hype, and reality for delivering it services as computing utilities. In *High Performance Computing and Communications, 2008. HPCC'08. 10th IEEE International Conference on*, pages 5–13. Ieee, 2008.
- [26] L. Coit C. Wang, S. Balaouras. Q&a: Demystifying cloud security. an empowered report: getting past cloud security fear mongering. Technical report, Forrester Research, Inc., 2010.
- [27] Varun Chandola, Arindam Banerjee, and Vipin Kumar. Anomaly detection: A survey. *ACM computing surveys (CSUR)*, 41(3):15, 2009.

- [28] Nitin Singh Chauhan and Ashutosh Saxena. Energy analysis of security for cloud application. In *India Conference (INDICON), 2011 Annual IEEE*, pages 1–6. IEEE, 2011.
- [29] Srilatha Chebrolu, Ajith Abraham, and Johnson P Thomas. Feature deduction and ensemble design of intrusion detection systems. *Computers & security*, 24(4):295–307, 2005.
- [30] Chia-Mei Chen, D.J. Guan, Yu-Zhi Huang, and Ya-Hui Ou. Attack sequence detection in cloud using hidden markov model. In *2012 Seventh Asia Joint Conference on Information Security*. IEEE, aug 2012.
- [31] Z Chiba, N Abghour, K Moussaid, M Rida, et al. A cooperative and hybrid network intrusion detection framework in cloud computing based on snort and optimized back propagation neural network. *Procedia Computer Science*, 83:1200–1206, 2016.
- [32] Hui-Hao Chou and Sheng-De Wang. An adaptive network intrusion detection approach for the cloud environment. In *Security Technology (ICCST), 2015 International Carnahan Conference on*, pages 1–6. IEEE, 2015.
- [33] Justin Clift, Justin Clift, Eric Blake, Nikunj A. Dadhania, and Zdenek Styblik. libvirt 0.8.7 virsh command reference edition 1.
- [34] Gerald Combs et al. Wireshark. *Web page: <http://www.wireshark.org/last modified>*, pages 12–02, 2007.
- [35] Microsoft Corporation. *Windows Event Log Service*, 2011.
- [36] Greg Cottingham. How azure security center helps reveal a cyberattack, March 2017.
- [37] Amir Vahid Dastjerdi, Kamalrulnizam Abu Bakar, and Sayed Gholam Hassan Tabatabaei. Distributed intrusion detection in clouds using mobile agents. In *2009 Third International Conference on Advanced Engineering Computing and Applications in Sciences*. IEEE, oct 2009.
- [38] Sherri Davidoff. Cleartext passwords in linux memory. *Massachusetts institute of technology*, pages 1–13, 2008.
- [39] Dorothy E Denning. An intrusion-detection model. *IEEE Transactions on software engineering*, (2):222–232, 1987.

- [40] Idilio Drago, Marco Mellia, Maurizio M Munafo, Anna Sperotto, Ramin Sadre, and Aiko Pras. Inside dropbox: understanding personal cloud storage services. In *Proceedings of the 2012 ACM conference on Internet measurement conference*, pages 481–494. ACM, 2012.
- [41] Felix Fuentes and Dulal C Kar. Ethereal vs. tcpdump: a comparative study on packet sniffing tools for educational purpose. *Journal of Computing Sciences in Colleges*, 20(4):169–176, 2005.
- [42] Dan Goodin. Tesla cloud resources are hacked to run cryptocurrency-mining malware, February 2018.
- [43] Andy Greenberg. How hackers hid a money-mining botnet in the clouds of amazon and others, July 2014.
- [44] Irfan Gul and M Hussain. Distributed cloud intrusion detection model. *International Journal of Advanced Science and Technology*, 34(38):135, 2011.
- [45] Jinhong Guo and Stephen L Johnson. Intrusion detection using system call monitors on a bayesian network, February 21 2007. US Patent App. 11/677,059.
- [46] Sajva Halverson. How azure security center aids in detecting good applications being used maliciously, August 2017.
- [47] Hatem Hamad and Mahmoud Al-Hoby. Managing intrusion detection as a service in cloud networks. *International Journal of Computer Applications*, 41(1), 2012.
- [48] Mohammad Hamdaqa and Ladan Tahvildari. Cloud computing uncovered: a research landscape. *Advances in Computers*, 86:41–85, 2012.
- [49] Steve Hanna. A security analysis of cloud computing. *Cloud Computing Journal*, 2009.
- [50] Douglas M Hawkins, Peihua Qiu, and Chang Wook Kang. The changepoint model for statistical process control. *Journal of quality technology*, 35(4):355, 2003.
- [51] Douglas M Hawkins and KD Zamba. A change-point model for a shift in variance. *Journal of Quality Technology*, 37(1):21, 2005.
- [52] David V Hinkley and Elizabeth A Hinkley. Inference about the change-point in a sequence of binomial variables. *Biometrika*, 57(3):477–488, 1970.

- [53] Daniel Högberg. An applied evaluation and assessment of cloud computing platforms, 2012.
- [54] Harold Hotelling. Analysis of a complex of statistical variables into principal components. *Journal of educational psychology*, 24(6):417, 1933.
- [55] Tian Huang, Yan Zhu, Qiannan Zhang, Yongxin Zhu, Dongyang Wang, Meikang Qiu, and Lei Liu. An LOF-based adaptive anomaly detection scheme for cloud computing. In *2013 IEEE 37th Annual Computer Software and Applications Conference Workshops*. IEEE, jul 2013.
- [56] Tian Huang, Yan Zhu, Qiannan Zhang, Yongxin Zhu, Dongyang Wang, Meikang Qiu, and Lei Liu. An lof-based adaptive anomaly detection scheme for cloud computing. In *Computer Software and Applications Conference Workshops (COMP-SACW), 2013 IEEE 37th Annual*, pages 206–211. IEEE, 2013.
- [57] Dan Hubbard, Michael Sutton, et al. Top threats to cloud computing v1. 0. *Cloud Security Alliance*, 2010.
- [58] Nicholas A James and David S Matteson. ecp: An r package for nonparametric multiple change point analysis of multivariate data. *arXiv preprint arXiv:1309.3295*, 2013.
- [59] Meiko Jensen, Jorg Schwenk, Jens-Matthias Bohli, Nils Gruschka, and Luigi Lo Iacono. Security prospects through cloud computing by adopting multiple clouds. In *Cloud Computing (CLOUD), 2011 IEEE International Conference on*, pages 565–572. IEEE, 2011.
- [60] Richard Jones. guestfish - the guest filesystem shell.
- [61] Anand Kannan, Gerald Q. Maguire Jr., Ayush Sharma, and Peter Schoo. Genetic algorithm based feature selection algorithm for effective intrusion detection in cloud networks. In *2012 IEEE 12th International Conference on Data Mining Workshops*. IEEE, dec 2012.
- [62] Puneet Jai Kaur and Sakshi Kaushal. Security concerns in cloud computing. In *High Performance Architecture and Grid Computing*, pages 103–112. Springer, 2011.

- [63] Hisham A Kholidy and Fabrizio Baiardi. Cidd: A cloud intrusion detection dataset for cloud computing and masquerade attacks. In *Information Technology: New Generations (ITNG), 2012 Ninth International Conference on*, pages 397–402. IEEE, 2012.
- [64] Hisham A Kholidy, Fabrizio Baiardi, Salim Hariri, Esraa M Elhariri, Ahmed M Yousof, and Sahar A Shehata. A hierarchical intrusion detection system for clouds: Design and evaluation. *International Journal on Cloud Computing: Services and Architecture (IJCCSA)*, 2(6), 2012.
- [65] Hisham A Kholidy, Abdelkarim Erradi, and Sherif Abdelwahed. Attack prediction models for cloud intrusion detection systems. In *Artificial Intelligence, Modelling and Simulation (AIMS), 2014 2nd International Conference on*, pages 270–275. IEEE, 2014.
- [66] Hisham A Kholidy, Abdelkarim Erradi, Sherif Abdelwahed, and Fabrizio Baiardi. Ha-cids: A hierarchical and autonomous ids for cloud systems. In *Computational Intelligence, Communication Systems and Networks (CICSyN), 2013 Fifth International Conference on*, pages 179–184. IEEE, 2013.
- [67] Manoj Kumar and Robin Mathur. Unsupervised outlier detection technique for intrusion detection in cloud computing. In *Convergence of Technology (I2CT), 2014 International Conference for*, pages 1–4. IEEE, 2014.
- [68] Pardeep Kumar, Vivek Sehgal, Kinjal Shah, Shiv Shankar Prasad Shukla, Durg Singh Chauhan, et al. A novel approach for security in cloud computing using hidden markov model and clustering. In *Information and Communication Technologies (WICT), 2011 World Congress on*, pages 810–815. IEEE, 2011.
- [69] Raneel Kumar, Sunil Pranit Lal, and Alok Sharma, 2016.
- [70] Raneel Kumar, Sunil Pranit Lal, and Alok Sharma. Detecting denial of service attacks in the cloud. In *Dependable, Autonomic and Secure Computing, 14th Intl Conf on Pervasive Intelligence and Computing, 2nd Intl Conf on Big Data Intelligence and Computing and Cyber Science and Technology Congress (DASC/PiCom/DataCom/CyberSciTech), 2016 IEEE 14th Intl C*, pages 309–316. IEEE, 2016.

- [71] Sunita Kumawat, Anil Kumar Sharma, and Anjali Kumawat. Intrusion detection and prevention system using k-learning classification in cloud. In *Computing for Sustainable Global Development (INDIACom), 2016 3rd International Conference on*, pages 815–820. IEEE, 2016.
- [72] Jessen Kurien. How azure security center detects a bitcoin mining attack, April 2017.
- [73] Jessen Kurien. How azure security center detects ddos attack using cyber threat intelligence, July 2017.
- [74] Hyukmin Kwon, Taesu Kim, Song Jin Yu, and Huy Kang Kim. Self-similarity based lightweight intrusion detection method for cloud computing. In *Asian Conference on Intelligent Information and Database Systems*, pages 353–362. Springer, 2011.
- [75] Hyangjin Lee, Jeeyeon Kim, Youngsook Lee, and Dongho Won. Security issues and threats according to the attribute of cloud computing. In *Computer Applications for Security, Control and System Engineering*, pages 101–108. Springer, 2012.
- [76] Bo Li, Peng Liu, and Li Lin. A cluster-based intrusion detection framework for monitoring the traffic of cloud environments. In *Cyber Security and Cloud Computing (CSCloud), 2016 IEEE 3rd International Conference on*, pages 42–45. IEEE, 2016.
- [77] Hongjiao Li, Xiuxia Tian, Weimin Wei, and ChaoChao Sun. A deep understanding of cloud computing security. In *Network Computing and Information Security*, pages 98–105. Springer, 2012.
- [78] Zhe Li, Weiqing Sun, and Lingfeng Wang. A neural network based distributed intrusion detection system on cloud platform. In *Cloud Computing and Intelligent Systems (CCIS), 2012 IEEE 2nd International Conference on*, volume 1, pages 75–79. IEEE, 2012.
- [79] Hong Liang, Yufei Ge, Wenjiao Wang, and Lin Chen. Collaborative intrusion detection as a service in cloud computing environment. In *Progress in Informatics and Computing (PIC), 2015 IEEE International Conference on*, pages 476–480. IEEE, 2015.
- [80] Ming-Yi Liao, Zhi-Kai Mo, Mon-Yen Luo, Chu-Sing Yang, and Jiann-Liang Chen. Novel intrusion detection system for cloud computing: A case study. In *Inter-*

national Conference on Cloud Computing and Big Data in Asia, pages 386–398. Springer, 2015.

- [81] Jorg Liebeherr and Magda El Zarki. *Mastering Networks: An Internet Lab Manual*. Addison-Wesley Longman Publishing Co., Inc., 2003.
- [82] Chih-Hung Lin, Chin-Wei Tien, and Hsing-Kuo Pao. Efficient and effective nids for cloud virtualization environment. In *2012 IEEE 4th International Conference on Cloud Computing Technology and Science*. IEEE, 2012.
- [83] Chi-Chun Lo, Chun-Chieh Huang, and Joy Ku. A cooperative intrusion detection system framework for cloud computing networks. In *2010 39th International Conference on Parallel Processing Workshops*. IEEE, sep 2010.
- [84] Alina Madalina Lonea, Daniela Elena Popescu, and Huanglory Tianfield. Detecting ddos attacks in cloud computing environment. *International Journal of Computers Communications & Control*, 8(1):70–78, 2013.
- [85] Wei Lu, Mark Miller, and Ling Xue. Detecting command and control channel of botnets in cloud. In *International Conference on Intelligent, Secure, and Dependable Systems in Distributed and Cloud Environments*, pages 55–62. Springer, 2017.
- [86] Wei Lu and Issa Traore. A new unsupervised anomaly detection framework for detecting network attacks in real-time. In *International Conference on Cryptology and Network Security*, pages 96–109. Springer, 2005.
- [87] Aine MacDermott, Qi Shi, and Kashif Kifayat. Detecting intrusions in federated cloud environments using security as a service. In *2015 International Conference on Developments of E-Systems Engineering (DeSE)*. IEEE, dec 2015.
- [88] Ratul Mahajan, Steven M Bellovin, Sally Floyd, John Ioannidis, Vern Paxson, and Scott Shenker. Controlling high bandwidth aggregates in the network. *ACM SIGCOMM Computer Communication Review*, 32(3):62–73, 2002.
- [89] Claudio Mazzariello, Roberto Bifulco, and Roberto Canonico. Integrating a network ids into an open source cloud computing environment. In *Information Assurance and Security (IAS), 2010 Sixth International Conference on*, pages 265–270. IEEE, 2010.

- [90] Yasir Mehmood, Muhammad Awais Shibli, Ayesha Kanwal, and Rahat Masood. Distributed intrusion detection system using mobile agents in cloud computing environment. In *Information Assurance and Cyber Security (CIACS), 2015 Conference on*, pages 1–8. IEEE, 2015.
- [91] Abhay Mehta. Process and apparatus for collecting a data structure of a memory dump into a logical table, December 7 1999. US Patent 5,999,933.
- [92] Peter Mell and Tim Grance. Effectively and securely using the cloud computing paradigm. *NIST, Information Technology Laboratory*, pages 304–311, 2009.
- [93] Yuxin Meng, Wenjuan Li, and Lam-For Kwok. Design of cloud-based parallel exclusive signature matching model in intrusion detection. In *High Performance Computing and Communications & 2013 IEEE International Conference on Embedded and Ubiquitous Computing (HPCC_EUC), 2013 IEEE 10th International Conference on*, pages 175–182. IEEE, 2013.
- [94] Cade Metz. Ddos attack rains down on amazon cloud. *The Register*, 2009.
- [95] Preeti Mishra, Emmanuel S Pilli, Vijay Varadharajan, and Udaya Tupakula. Efficient approaches for intrusion detection in cloud environment. In *Computing, Communication and Automation (ICCCA), 2016 International Conference on*, pages 1211–1216. IEEE, 2016.
- [96] Preeti Mishra, Emmanuel S Pilli, Vijay Varadharajant, and Udaya Tupakula. Nvcloudids: A security architecture to detect intrusions at network and virtualization layer in cloud environment. In *Advances in Computing, Communications and Informatics (ICACCI), 2016 International Conference on*, pages 56–62. IEEE, 2016.
- [97] Chirag Modi, Dhiren Patel, Bhavesh Borisaniya, Avi Patel, and Muttukrishnan Rajarajan. A survey on security issues and solutions at different layers of cloud computing. *The Journal of Supercomputing*, 63(2):561–592, 2013.
- [98] Chirag N Modi and Dhiren Patel. A novel hybrid-network intrusion detection system (h-nids) in cloud computing. In *Computational Intelligence in Cyber Security (CICS), 2013 IEEE Symposium on*, pages 23–30. IEEE, 2013.
- [99] Chirag N Modi, Dhiren R Patel, Avi Patel, and Rajarajan Muttukrishnan. Bayesian classifier and snort based network intrusion detection system in cloud computing.

- In *Computing Communication & Networking Technologies (ICCCNT), 2012 Third International Conference on*, pages 1–7. IEEE, 2012.
- [100] Manthira Moorthy and M Rajeswari. Virtual host based intrusion detection system for cloud. *International Journal of Engineering & Technology*, pages 0975–4024, 2013.
 - [101] S Manthira Moorthy and M Roberts Masillamani. Intrusion detection in cloud computing implementation of (saas & iaas) using grid environment. In *Proceedings of International Conference on Internet Computing and Information Communications*, pages 53–64. Springer, 2014.
 - [102] James D Murray. *Windows NT Event Logging*. O'Reilly & Associates, Inc., 1998.
 - [103] Gustavo Nascimento and Miguel Correia. Anomaly-based intrusion detection in software as a service. In *Dependable Systems and Networks Workshops (DSN-W), 2011 IEEE/IFIP 41st International Conference on*, pages 19–24. IEEE, 2011.
 - [104] Jason Nikolai and Yong Wang. Hypervisor-based cloud intrusion detection system. In *Computing, Networking and Communications (ICNC), 2014 International Conference on*, pages 989–993. IEEE, 2014.
 - [105] N. Pandeewari and Ganesh Kumar. Anomaly detection system in cloud environment using fuzzy clustering based ANN. *Mobile Networks and Applications*, 21(3):494–505, aug 2015.
 - [106] Animesh Patcha and Jung-Min Park. An overview of anomaly detection techniques: Existing solutions and latest technological trends. *Computer networks*, 51(12):3448–3470, 2007.
 - [107] Karl Pearson. Liii. on lines and planes of closest fit to systems of points in space. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 2(11):559–572, 1901.
 - [108] Md Tarique Prwez and Kakali Chatterjee. A framework for network intrusion detection in cloud. In *2016 IEEE 6th International Conference on Advanced Computing (IACC)*. IEEE, feb 2016.
 - [109] Meikang Qiu, Shouhuai Xu, Moti Yung, and Haibo Zhang. *Network and System Security*. Springer, 2015.

- [110] Martin Roesch et al. Snort: Lightweight intrusion detection for networks. In *Lisa*, volume 99, pages 229–238, 1999.
- [111] Chunming Rong, Son T Nguyen, and Martin Gilje Jaatun. Beyond lightning: A survey on security challenges in cloud computing. *Computers & Electrical Engineering*, 39(1):47–54, 2013.
- [112] Gordon J Ross and Niall M Adams. Two nonparametric control charts for detecting arbitrary distribution changes. *Journal of Quality Technology*, 44(2):102, 2012.
- [113] Gordon J Ross et al. Parametric and nonparametric sequential change detection in r: The cpm package. *Journal of Statistical Software*, 78, 2013.
- [114] Gordon J Ross, Dimitris K Tasoulis, and Niall M Adams. Nonparametric monitoring of data streams for changes in location and scale. *Technometrics*, 53(4):379–389, 2011.
- [115] Fariza Sabrina, Cong Duc Nguyen, Sanjay Jha, Don Platt, and Farzad Safaei. Processing resource scheduling in programmable networks. *Computer communications*, 28(6):676–687, 2005.
- [116] Reza Sahandi, Adel Alkhalil, and Justice Opara-Martins. Smes? perception of cloud computing: Potential and security. In *Working Conference on Virtual Enterprises*, pages 186–195. Springer, 2012.
- [117] Salvatore Sanfilippo. Hping3 (8)-linux man page, 2005.
- [118] Berkah I Santoso, M Rien Suryatama Idrus, and Irwan Prasetya Gunawan. Designing network intrusion and detection system using signature-based method for protecting openstack private cloud. In *Engineering Seminar (InAES), International Annual*, pages 61–66. IEEE, 2016.
- [119] Nuno Sénica, Cláudio Teixeira, and Joaquim Sousa Pinto. Cloud computing: A platform of services for services. In *International Conference on ENTERprise Information Systems*, pages 91–100. Springer, 2011.
- [120] Karlton Sequeira and Mohammed Zaki. Admit: anomaly-based data mining for intrusions. In *Proceedings of the eighth ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 386–395. ACM, 2002.

- [121] Dinesh Singh, Dhiren Patel, Bhavesh Borisaniya, and Chirag Modi. Collaborative ids framework for cloud. *International Journal of Network Security*, 18(4):699–709, 2016.
- [122] Madhan Kumar Srinivasan, K Sarukesi, Ashima Keshava, and P Revathy. eclouids—design roadmap for the architecture of next-generation hybrid two-tier expert engine-based ids for cloud computing environment. *Recent Trends in Computer Networks and Distributed Systems Security*, pages 358–371, 2012.
- [123] Madhan Kumar Srinivasan, K Sarukesi, Paul Rodrigues, M Sai Manoj, and P Revathy. State-of-the-art cloud computing security taxonomies: a classification of security challenges in the present cloud computing environment. In *Proceedings of the international conference on advances in computing, communications and informatics*, pages 470–476. ACM, 2012.
- [124] DA Stephens. Bayesian retrospective multiple-changepoint identification. *Applied Statistics*, pages 159–178, 1994.
- [125] Salvatore J Stolfo, Malek Ben Salem, and Angelos D Keromytis. Fog computing: Mitigating insider data theft attacks in the cloud. In *Security and Privacy Workshops (SPW), 2012 IEEE Symposium on*, pages 125–128. IEEE, 2012.
- [126] Gabor J. Szekely and Maria L. Rizzo. Disco analysis: A nonparametric extension of analysis of variance. *The Annals of Applied Statistics*, 4(2):1034–1055, 2010.
- [127] Hassan Takabi, James BD Joshi, and Gail-Joon Ahn. Security and privacy challenges in cloud computing environments. *IEEE Security & Privacy*, 8(6):24–31, 2010.
- [128] Alexander G Tartakovsky, Boris L Rozovskii, Rudolf B Blazek, and Hongjoong Kim. A novel approach to detection of intrusions in computer networks via adaptive sequential and batch-sequential change-point detection methods. *IEEE Transactions on Signal Processing*, 54(9):3372–3382, 2006.
- [129] Hsin-Yi Tsai, Melanie Siebenhaar, Andre Miede, Yulun Huang, and Ralf Steinmetz. Threat as a service?: Virtualization’s impact on cloud security. *IT professional*, 14(1):32–37, 2012.
- [130] Amandeep Verma and Sakshi Kaushal. Cloud computing security issues and challenges: a survey. In *International Conference on Advances in Computing and Communications*, pages 445–454. Springer, 2011.

- [131] Kleber Vieira, Alexandre Schulter, Carlos Westphall, and Carla Westphall. Intrusion detection for grid and cloud computing. *It Professional*, 12(4):38–43, 2010.
- [132] LI Vostrikova. Detection of the disorder in multidimensional random-processes. *Doklady Akademii Nauk SSSR*, 259(2):270–274, 1981.
- [133] Haining Wang, Danlu Zhang, and Kang G Shin. Change-point monitoring for the detection of dos attacks. *IEEE Transactions on dependable and secure computing*, 1(4):193–208, 2004.
- [134] Laifu Wang, Jun Shen, and Huamin Jin. Research on cloud computing security. *Telecommunications Science*, 26(6):67–70, 2010.
- [135] Zhijian Wang and Yanqin Zhu. A centralized hids framework for private cloud. In *Software Engineering, Artificial Intelligence, Networking and Parallel/Distributed Computing (SNPD), 2017 18th IEEE/ACIS International Conference on*, pages 115–120. IEEE, 2017.
- [136] Marvin Waschke. *Cloud standards: Agreements that hold together clouds*. Apress, 2012.
- [137] Qingtang Xia, Tianjia Chen, and Wei Xu. CIDS: Adapting legacy intrusion detection systems to the cloud with hybrid sampling. In *2016 IEEE International Conference on Computer and Information Technology (CIT)*. IEEE, dec 2016.
- [138] Wei Xiong, Hanping Hu, Naixue Xiong, Laurence T. Yang, Wen-Chih Peng, Xiaofei Wang, and Yanzhen Qu. Anomaly secure detection methods by analyzing dynamic characteristics of the network traffic in cloud communications. *Information Sciences*, 258:403–415, feb 2014.
- [139] Rakesh Kumar Yadav, Abhishek K Mishra, Navin Prakash, and Himanshu Sharma. An improved round robin scheduling algorithm for cpu scheduling. *International Journal on Computer Science and Engineering*, 2(04):1064–1066, 2010.
- [140] Roman V Yampolskiy and Venu Govindaraju. Behavioural biometrics: a survey and classification. *International Journal of Biometrics*, 1(1):81–113, 2008.
- [141] Zhang Yandong and Zhang Yongsheng. Cloud computing and cloud security challenges. In *Information Technology in Medicine and Education (ITME), 2012 International Symposium on*, volume 2, pages 1084–1088. IEEE, 2012.

- [142] Warusia Yassin, Nur Izura Udzir, Zaiton Muda, Azizol Abdullah, and Mohd Taufik Abdullah. A cloud-based intrusion detection service framework. In *Cyber Security, Cyber Warfare and Digital Forensic (CyberSec), 2012 International Conference on*, pages 213–218. IEEE, 2012.
- [143] Pengfei You, Yuxing Peng, Weidong Liu, and Shoufu Xue. Security issues and solutions in cloud computing. In *Distributed Computing Systems Workshops (ICDCSW), 2012 32nd International Conference on*, pages 573–577. IEEE, 2012.
- [144] KD Zamba and Douglas M Hawkins. A multivariate change-point model for statistical process control. *Technometrics*, 48(4):539–549, 2006.
- [145] Amirreza Zarrabi and Alireza Zarrabi. Internet intrusion detection system service in a cloud. *International Journal of Computer Science Issues (IJCSI)*, 9(5):308, 2012.
- [146] Qi Zhang, Lu Cheng, and Raouf Boutaba. Cloud computing: state-of-the-art and research challenges. *Journal of internet services and applications*, 1(1):7–18, 2010.
- [147] Shuai Zhang, Shufen Zhang, Xuebin Chen, and Xiuzhen Huo. Cloud computing research and development trend. In *Future Networks, 2010. ICFN'10. Second International Conference on*, pages 93–97. Ieee, 2010.
- [148] Wei Zhao. An initial review of cloud computing services research development. In *Multimedia information networking and security (MINES), 2010 international conference on*, pages 324–328. IEEE, 2010.
- [149] Xinlong Zhao and Weishi Zhang. An anomaly intrusion detection method based on improved k-means of cloud computing. In *2016 Sixth International Conference on Instrumentation & Measurement, Computer, Communication and Control (IMCCC)*. IEEE, jul 2016.
- [150] Xinlong Zhao and Weishi Zhang. Hybrid intrusion detection method based on improved bisecting k-means in cloud computing. In *Web Information Systems and Applications Conference, 2016 13th*, pages 225–230. IEEE, 2016.

Appendix A

Documentation for the Benchmark Dataset for Cloud Intrusion Detection (ISOT-CID)

Cloud computing is susceptible to traditional IT attacks because it leverages the existing IT infrastructure, operating systems (OSs), and applications. In addition to the conventional threats, cloud computing environments face new security issues as these involve many new technologies that could lead to new forms of exploitation.

Developing cloud based IDS that can capture suspicious activity or threats, and prevent attacks and data leakage from both inside and outside the cloud environment is paramount. Developing such systems, however, is very challenging as cloud IDS researchers are faced with one of the greatest hurdles: the lack of publicly available datasets collected from a real cloud computing environment, which is a big hindrance for developing and testing realistic detection models.

We introduce the first public dataset of its kind collected from a production cloud environment, named ISOT Cloud Intrusion Dataset (ISOT-CID), as an initial response toward addressing such need and paving the way for cloud security communities for more research and finding. The dataset consists of several terabytes of data, involving normal activities and a wide variety of attack vectors, collected in two phases and over several months for the VM instances, and several days and time slots for the Hypervisors and the Network traffics. The benign/normal data are from web applications and administrative activities ranging from maintaining the status of VMs, rebooting, updating, creating files, SSHing to the machine, and logging in a remote server. The web traffic was generated by more than

160 legitimate visitors, including more than 60 human users and genuine traffic generated by 100 robots, performing tasks such as account registration, reading/posting and commenting on blogs, browsing various pages, and so on. One of the web applications consists of a password management service for registered users. The ISOT-CID is an aggregation of different data gathered from a variety of cloud layers, including guest hosts, hypervisors and networks, and it comprises data with different formats and from multiple data sources, including memory dumps, resource (e.g., CPU) utilizations, system call traces, system logs, and network traffic. It is large and diverse enough to accommodate various intrusion data models, feature sets and analysis models. The purpose of ISOT-CID is the embodiment of a real cloud dataset, it is essentially raw and has not been transformed, manipulated or altered. This is important for the industry and academia towards developing and evaluating realistic intrusion models for cloud computing.

The ISOT-CID collection environment, procedure and detailed data types are published as a chapter in a book titled as “Cloud Computing for Optimization: Foundations, Applications, and Challenges” by Springer [9].

The current documentation describes and explains the dataset metadata files and how they are structured and stored into ISOT-lab servers in order to ensure an unambiguous meaning of the data. Moreover, it provides details on the attack scenarios and the network statistics. In particular, the network traffic of ISOT-CID, is described in much more details.

ISOT-CID Structure

ISOT-CID is organized on the ISOT-lab servers under two main directories *Logs* and *Additional Materials*.

```
[..@.... ISOT-CID]$ ls
Logs      Additional_Materials
```

The *Additional Materials* directory contains directories and files describing the cloud environment such as hypervisors and instances mapping information and performed attack commands.

```
[..@.... Additional_Materials]$ ls
attacks      instance-mapping.txt      hyper_cpuintfo
poseidon0049_ifconfig     ....etc.
```

The *Logs* directory contains two main directories, named based on the two collection phases, *Phase_1* and *Phase_2*. Under each directory, there are 3-5 levels of subdirectories and files.

```
[..@... Logs]$ ls
Phase_1  Phase_2
```

```
[..@... Phase_1]$ ls
byday
```

```
[..@... byday]$ ls
2016-12-09    2016-12-15    2016-12-16    2016-12-19
```

The fourth level of directories is contain the dataset collected from both hypervisors and VMs stored under each attack day separately.

```
[..@... 2016-12-15]$ ls
Hyps_logs    VMs_logs
```

The fifth level of directories contains different directories for data types and sources and named accordingly.

```
[..@... Hyps_logs]$ ls
calls  memory  tcp
```

```
[..@... tcp]$ ls
Fri_Dec_16_08:52:51_PST_2016_poseidon0050.wgcloud.uvic.
ca_eth2.3335.dump.lz4
Fri_Dec_16_09:17:16_PST_2016_poseidon0050.wgcloud.uvic.
ca_tap3178ed86-a9.dump.lz4
Fri_Dec_16_09:18:27_PST_2016_poseidon0049.wgcloud.uvic.
ca_eth2.3335.dump.lz4
Fri_Dec_16_08:52:51_PST_2016_poseidon0050.wgcloud.uvic.
ca_tape7fbbb33-8d.log.lz4
Fri_Dec_16_09:18:27_PST_2016_poseidon0049.wgcloud.uvic.
ca_eth2.3335.log.lz4
Fri_Dec_16_08:53:05_PST_2016_poseidon0049.wgcloud.uvic.
ca_eth2.3335.dump.lz4
Fri_Dec_16_09:18:27_PST_2016_poseidon0049.wgcloud.uvic.
```

```

ca_tap5f861c6c-ec.dump.lz4
Fri_Dec_16_08:53:05_PST_2016_poseidon0049.wgcloud.uvic.
ca_eth2.3335.log.lz4
..... etc.

[...@... VMs_logs]$ ls
2hpisot-centos7.log  hpisot-centos7.log  hpisot-dj.log
hpisot-ubuntu.log  hpisot-winserve.log  isotvm-1.log ... etc.

```

Network Traffic

In a cloud computing infrastructure such as OpenStack, the network traffic travels through different network points. In our case, the outside traffic first arrives via the entry and top-rack switches to dedicated network nodes, called neutron nodes, and then travels to the hypervisor on the compute nodes passing through our internal physical switches. Finally, the hypervisor delivers the traffic to the designated instance. With this OpenStack networking configuration, there are three different network flows: external, internal and local traffic. The external traffic is between the virtual machine and an outside machine (an “instance-outside” traffic). The internal traffic is between the compute node and another compute node (“hypervisor-hypervisor” traffic). The local traffic is between two instances on the same Compute node (“instance-instance” traffic). In ISOT-CID, we were able to collect all of these three different traffics from both hypervisors and instances. By setting the network interface into promiscuous mode, we were able to collect all the network traffic that passes through all the network interfaces on the hypervisors and instances (except for the special network interfaces not involved in our network traffic). The utility TCPdump was used to capture the network traffic [81] on *nix OSs and Netsh on winX OS, and stored in packet capture (pcap) format. We performed two kinds of network traffic data collections: the network traffic without payload on both hypervisors and instances, and the full network traffic on the hypervisors only.

The network traffic dataset contains a total of 22,372,418 network packets for phase 1, of which 22,356,769 packets are normal, and 15,649 are malicious. Table A.2 summarizes the total network traffic statistics and Table A.4 details the traffic breakdown per day and node for phase 1. For phase 2, the dataset contains a total of 11,509,254 network packets, of which 9,502,872 packets are normal, and 2,006,382 are malicious. Table A.3 summarizes

the total network traffic statistics, and Table A.5 details the traffic breakdown per day and node. Tables A.1, summarizes the dataset attacks types.

A.1 Phase One

The attack scenarios in this phase, involved different attack times and distinct attacker's geographical locations. The attacks were divided into 4 rounds in phase one, averaging for 1 hour for each round, and spread over 4 different days. Moreover, the attackers performed and completed the attack scenarios from two different continents, precisely Europe and North America. All the traces of these attacks were collected from all previously mentioned data sources. The ISOT-CID attacks are divided into inside and outside attacks that are performed by an insider and outsider attackers, respectively. The inside attacks were originated from within the ISOT-cloud environment and targeted either the internal cloud infrastructure or the outside world. In our case, we were involved two scenarios:

1. The attacks are performed by a malicious insider who has high privileges (e.g., root access) on the hypervisor nodes in our ISOT-cloud environment.
2. The attacks are originated from an instance inside the ISOT-cloud environment. This instance could be either compromised or used on purpose as a stepping stone to attack other instances in the ISOT-cloud environment or the outside world.

The outside attacks are defined as the attacks that target the ISOT- cloud environment from the outside world. In the outside attacks, in addition to the daily attacks that were performed by stranger attackers, we carried out different attacks such as Remote-to-Local (R2L), DOS, probing, information disclosure, input validation, authentication breach, and backdoors.

A.1.1 Inside Attack Scenarios

In the inside attack scenarios performed, multiple attacks were run by an insider having root access to the ISOT-cloud hypervisors. These attacks violate confidentiality, privacy, integrity of cloud user's data. We discuss below the different categories of inside attacks enacted.

Table A.1: Attack types in the ISOT-CID

<div>Attack Origin</div> <div>Attack Target</div>	Outside	Inside
Application Layer	<ul style="list-style-type: none"> • Web Vulnerabilities Scanning • Dictionary/Brute Force login attack • Directory/Path Traversal • Cross-site Scripting (XSS) • SQL Injection • Fuzzers • HTTP Flood DOS 	
Network Layer	<ul style="list-style-type: none"> • Dictionary/Brute Force login attack • DNS amplification DOS • Synflood DOS • Ports and Network scanning • Unclassified (unsolicited traffic) 	<ul style="list-style-type: none"> • Unauthorized Cryptomining (download/install/run cryptominer) • Ports and Network scanning • Dictionary/Brute Force login attack • Synflood DOS • UDP Flood DOS • Revealing Users Credentials and Confidential Data by Insider • Trojan Horse • Backdoor (reverse shell) • Stepping Stone Attack

Table A.2: Phase 1: Network traffic distribution

Total Normal Traffic	Total malicious Traffic	Total Packets
22356769	15649	22372418
99.93%	0.07%	100%

Table A.3: Phase 2: Network traffic distribution

Total Normal Traffic	Total malicious Traffic	Total Packets
9502872	2006382	11509254
82.57%	17.43%	100%

Table A.4: Phase 1: Network traffic details

Date	Node A			Node B		
	Total Normal Traffic	Total Malicious Traffic	Total Packets	Total Normal Traffic	Total Malicious Traffic	Total Packets
Day 1 9/12/16	3294811	982	3295793	2975278	243	2975521
Day 2 15/12/16	6704732	6833	6711565	4832628	1174	4833802
Day 3 16/12/16	522590	1470	524060	1549115	618	1549733
Day 4 19/12/16	1419617	3667	1423284	1057998	662	1058660

Table A.5: Phase 2: Network traffic details

Date	Node A			Node B		
	Total Normal Traffic	Total Malicious Traffic	Total Packets	Total Normal Traffic	Total Malicious Traffic	Total Packets
Day 1 15/02/18	599051	8478	607529	199673	11080	210753
Day 2 16/02/18	1701631	249555	1951186	898076	21917	919993
Day 3 19/02/18	604090	11127	615217	387495	5043	392538
Day 4 20/02/18	956179	40089	996268	715215	47267	762482
Day 5 21/02/18	1075900	32996	1108896	651908	21570	673478
Day 6 23/02/18	952603	1537079	2489682	761051	20181	781232

Revealing User's Credentials

Two different techniques were used to attack the ISOT-cloud environment and reveal user's credentials. The summary of the first attack scenario as follows:

Step 1 Scan the running instances and their associated disks.

Step 2 Extract the names of the instances from their *libvirt.xml* specifications.

Step 3 Focus on a single instance, and locate and mount its disk.

Step 4 Copy the password and shadow files, and the *.ssh* folder.

Step 5 Copy the private key to the attacker workstation.

Step 6 Finally, compromise the ISOT instance using the copied private key.

The second inside attack was performed by a root privileged user to get memory and strace dumps. These dumps were obtained using *gcore* and *strace*, respectively. As shown in [38], once the memory dumps are available, the inside attacker can extract user credential and private information, including passwords in clear text.

Extracting User's Confidential Data

Following the same steps as above, once the inside attacker has mounted the instance's disk he can search, copy, delete and change any user's data, similar to copying the *.ssh* folder above.

Back Door and Trojan Horse

In this scenario, the inside attacker shut down the instance using *virsh* tools, mounted its disk using *guestfish* tools, and created Trojan horse for *ls* and *ps*. He also added an attractive script called *psb* that runs a malicious code when executed (this is a kind of back door to access the machine later on).

The previous inside attack scenarios performed in the last attack day (day 4 date 2016/12/19). Moreover, the executed commands for previous attacks are found in the text files named as *commands_log_poseidon0049.txt* and *commands_log_poseidon0050.txt* under *attacks* directory.

The other inside attack scenarios that we performed were carried out from compromised ISOT-cloud instances. After two instances were compromised, the inside attacker

configured one of them to be a stepping stone, which potentially could be part of a botnet. Although this stepping stone was setup by an insider attacker, it could have been launched by the owner of the instance himself.

A.1.2 Outside Attack Scenarios

The benign IPs list in this Phase are :

172.16.1.21, 172.16.1.255, 172.16.1.24, 172.16.1.20,
 172.16.1.23, 172.16.1.10, 172.16.1.28, 172.16.1.26,
 172.16.1.19, 172.16.1.27, 192.168.0.10, 192.168.0.8,
 192.168.0.9, 255.255.255.255, 142.104.64.196, 142.104.80.2,
 142.104.6.1, 134.87.154.134, 134.87.157.129, 142.104.191.194,
 206.12.96.150, 206.12.96.149, 206.12.96.143, 206.12.96.142,
 206.12.96.141, 206.12.96.239, 206.12.96.240, 206.12.59.162,
 206.12.48.43, 172.16.1.254, 172.16.1.17, 172.16.1.16,
 206.12.48.115

Attack Scenarios for Day 1, 2016-12-09

Table A.6: Attack scenario steps for day 1

Day 1, 2016-12-09			
Seq	Attacks	Time	IPs
1	Scanning subnet 206.12.96.140-150 from Attacker's machine	09:37am	Src: Attacker's machine
			Des: 1- 172.16.1.21 (VM9) (206.12.96.141)
			2- 172.16.1.24 (VM8) (206.12.96.143)
			3- 172.16.1.27 (VM10) (206.12.96.150)
2	Dictionary attack from Attacker's machine against VM8	09:41am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Table A.6 continued from previous page

Day 1, 2016-12-09			
3	Login to VM8 from Attacker's machine	between 09:42-9:43am assumed to be 9:42am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.24 (VM8)
4	Scanning internal network 172.16.1.1-254 from VM8	09:45am	Src: 172.16.1.24 (VM8) Des: 1- 172.16.1.20 (VM7) (206.12.96.239) 2- 172.16.1.21 (VM9) 3- 172.16.1.27 (VM10)
5	End ssh connection to VM8	between 09:49-10:00am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
6	Login to VM8 from Attacker's machine	~09:59 - 10:00am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
7	End ssh connection to VM8	between 10:00-10:07am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
8	Transfer a file from attacker's machine to VM8 "Failed no space left on device"	~10:07am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
9	Login to VM8 from Attacker's machine	~10:09am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
10	End ssh connection to VM8	between 10:09-10:27am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
11	Login to VM8 from Attacker's machine	10:27am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Table A.6 continued from previous page

Day 1, 2016-12-09			
12	End ssh connection to VM8	~10:28am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
13	Transfer a file from Attacker's machine to VM8	~10:28 -10:29am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
14	Login to VM8 from Attacker's machine	~10:29am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
15	Download & Install hydra to VM8	~10:31am	Src: 172.16.1.24 (VM8) Des: Hydra repository
16	Internal scan 192.168.0.1-10 from VM8	10:34am	Src: 172.16.1.24 (VM8) Des: 192.168.0.1-10
17	Dictionary attack against 192.168.0.10 (VM5) from VM8	~10:36:12am	Src: 172.16.1.24 (VM8) Des: 192.168.0.10 (VM5)
18	End ssh connection to VM8	between 10:35-10:43am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
19	Failed login attempt against vm5 from attacker's machine	~10:42am	Src: Attacker's machine Des: 192.168.0.10 (VM5)
20	Login to VM8 from Attacker's machine	~10:43am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Table A.6 continued from previous page

Day 1, 2016-12-09			
21	Login to VM5 from VM8	~10:44am	Src: 172.16.1.24 (VM8) Des: 192.168.0.10 (VM5)
22	End ssh connection to VM5	~10:46am	Src: 172.16.1.24 (VM8) Des: 192.168.0.10 (VM5)
23	From VM8 ping the same machine	~10:46am	Src&Des: 172.16.1.24 (VM8)
24	Download & Instal hping3 in VM8	~10:47am	Src: 172.16.1.24 (VM8) Des: hping3 repository
25	End ssh connection to VM8	~10:47 - 11:00am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
26	zenmap scan from Attacker's machine against VM4	~10:54am	Src: Attacker's machine Des: 172.16.1.26 (VM4) (206.12.96.149)
27	Login to VM8 from Attacker's machine	10:57am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
28	Failed DOS attempt against VM4 from VM8	~11:00 -11:01am	Src: 172.16.1.24 (VM8) Des: 172.16.1.26 (VM4)
29	End ssh connection to VM8	~11:01am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
30	Login to VM8 from Attacker's machine	~11:04 -11:05am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Table A.6 continued from previous page

Day 1, 2016-12-09			
31	Ping VM4 from VM8	~11:04 -11:05am	Src: 172.16.1.24 (VM8) Des: 172.16.1.26 (VM4)
32	End ssh connection to VM8	~11:04 -11:05am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
33	DOS against VM4 from Attacker's machine	~11:04 -11:05am	Src: Attacker's machine Des: 172.16.1.26 (VM4)
34	Ping VM4 from Attacker's machine	~11:06 -11:07am	Src: Attacker's machine Des: 172.16.1.26 (VM4)

Network Statistics and Labelling for Day 1, 2016-12-09

Node: poseidon0049

Normal 3294811

Malicious 982

Total 3295793

ip	malicious	total
121.18.238.114	13.0	13
121.18.238.98	22.0	22
122.194.229.5	5.0	5
134.87.154.134	0.0	647497
14.162.253.53	1.0	1
142.104.191.194	0.0	189
142.104.6.1	0.0	804
142.104.64.196	0.0	320123
167.58.118.46	42.0	42
172.16.1.20	23.0	125118
172.16.1.21	189.0	890
172.16.1.24	218.0	610166
172.16.1.255	0.0	304

172.16.1.27	86.0	985728
172.16.1.28	0.0	71403
178.162.205.22	107.0	107
185.158.113.199	1.0	1
188.164.118.9	1.0	1
188.230.90.89	18.0	18
192.168.0.10	0.0	277759
196.52.43.56	1.0	1
206.108.0.131	1.0	1
206.12.48.43	0.0	255345
206.12.96.149	0.0	1
210.245.88.110	67.0	67
213.41.131.165	24.0	24
221.194.44.195	47.0	47
221.194.44.219	1.0	1
221.194.47.224	46.0	46
221.194.47.229	45.0	45
221.204.224.54	1.0	1
23.227.183.204	1.0	1
41.215.184.163	14.0	14
62.212.117.210	7.0	7
83.3.171.121	1.0	1

Node: poseidon0050

Normal 2975278

Malicious 243

Total 2975521

ip	malicious	total
104.167.113.95	5.0	5
120.192.73.121	5.0	5
121.18.238.114	6.0	6
122.194.229.5	2.0	2
134.87.154.134	0.0	381988
142.104.6.1	0.0	507

142.104.64.196	0.0	185998
142.104.80.2	0.0	9
158.69.244.236	7.0	7
167.58.118.46	23.0	23
172.16.1.19	24.0	255938
172.16.1.23	15.0	29613
172.16.1.24	0.0	769294
172.16.1.255	0.0	261
172.16.1.26	65.0	338
172.16.1.27	0.0	609411
172.16.1.28	24.0	299073
178.162.205.22	7.0	7
188.230.90.89	4.0	4
192.168.0.10	0.0	442744
192.168.0.8	0.0	1
192.168.0.9	0.0	231
192.95.25.79	1.0	1
199.182.221.110	7.0	7
207.210.46.249	1.0	1
207.5.168.18	6.0	6
213.41.131.165	2.0	2
217.100.113.74	13.0	13
224.0.0.252	12.0	12
41.215.184.163	9.0	9
72.38.129.202	5.0	5

Attack Scenarios for Day 2, 2016-12-15

Table A.9: Attack scenario steps for day 2

Day 2, 2016-12-15			
Seq	Attacks	Time	IPs

Table A.9 continued from previous page

Day 2, 2016-12-15			
1	Scan 206.12.96.143(VM8) from Attacker's machine	09:18am	Src: Attacker's machine Des: 172.16.1.24(VM8) (206.12.96.143)
2	Bruteforce attack from Attacker's machine against VM8 attack failed	between 09:29-9:37am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.24(VM8)
3	Password cracking using ncrack from Attacker machine against VM8	9:38am	Src: Attacker's machine Des: 172.16.1.24(VM8)
4	Login to VM8 from Attacker's machine	between 09:42-9:44am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.24(VM8)
5	Try to connect in reverse shell to Attacker machine (from VM8): ncat 184.69.179.82 4444	~10:02am	Src: 172.16.1.24 (VM8) Des: Attacker's machine (184.69.179.82)
6	From Attacker's machine copy private key of VM8	between 10:17-10:18am based on screenshot's time	Src: 172.16.1.24 (VM8) Des: Attacker's machine
7	Attempt to login into VM8 through SSH by cracking the private key using Metasploit ssh_login_pubkey module "attack failed"	between 10:20-10:24am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Table A.9 continued from previous page

Day 2, 2016-12-15			
8	Bruteforce from Attacker machine attack against VM8	10:28:24am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
9	End ssh connection to VM8	~10:29am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Network Statistics and Labelling for Day 2, 2016-12-15

Node: poseidon0049

Normal 6691221

Malicious 20344

Total 6711565

ip	malicious	total
100.35.44.34	8.0	8
104.167.113.112	3.0	3
109.98.17.26	1.0	1
109.99.128.119	1.0	1
110.77.204.157	1.0	1
114.32.237.192	3.0	3
116.16.144.231	1.0	1
121.18.238.109	57.0	57
121.185.217.142	1.0	1
122.194.229.39	695.0	695
123.193.20.71	1.0	1
134.87.157.129	0.0	2767438
142.104.191.194	4864.0	4864
142.104.6.1	0.0	2221
142.104.64.196	0.0	626029
154.16.132.187	1.0	1

163.172.210.63	1.0	1
168.62.9.64	20.0	20
169.254.169.254	287.0	287
172.16.1.16	3.0	3
172.16.1.17	7.0	7
172.16.1.20	368.0	302536
172.16.1.21	8791.0	14568
172.16.1.24	911.0	1385333
172.16.1.255	0.0	735
172.16.1.27	2012.0	1262856
172.16.1.28	0.0	209840
176.8.119.182	1.0	1
177.133.32.68	1.0	1
181.176.193.0	3.0	3
183.80.132.28	2.0	2
184.69.179.82	91.0	91
187.149.151.196	1.0	1
189.121.114.163	1.0	1
190.107.132.145	1.0	1
190.249.176.32	1.0	1
190.29.111.177	1.0	1
192.168.0.10	0.0	131747
199.182.221.110	6.0	6
2.136.215.32	1.0	1
203.127.19.42	11.0	11
203.177.11.195	324.0	324
206.108.0.131	2.0	2
206.108.0.133	5.0	5
206.186.121.125	6.0	6
207.210.46.249	5.0	5
208.180.114.12	7.0	7
208.86.164.250	6.0	6
209.126.122.15	1.0	1
210.121.112.84	1.0	1
212.66.51.29	1.0	1

218.161.33.56	1.0	1
218.28.225.66	5.0	5
220.133.146.105	1.0	1
221.194.44.195	11.0	11
221.194.44.224	37.0	37
221.194.44.231	6.0	6
221.194.47.224	46.0	46
221.194.47.229	47.0	47
222.124.18.147	1584.0	1584
224.0.0.252	2.0	2
255.255.255.255	4.0	4
46.1.139.244	1.0	1
49.4.133.72	1.0	1
5.101.66.252	8.0	8
5.235.38.105	1.0	1
50.245.137.161	8.0	8
50.77.127.137	6.0	6
58.104.196.133	1.0	1
61.164.149.128	1.0	1
66.196.242.187	6.0	6
67.215.197.149	4.0	4
78.186.22.191	1.0	1
79.7.213.30	6.0	6
86.107.164.157	1.0	1
91.189.89.198	8.0	8
91.189.89.199	6.0	6
91.189.91.157	11.0	11
91.189.94.4	8.0	8
91.224.160.207	1.0	1
94.255.224.2	3.0	3
97.88.219.127	2.0	2

Node: poseidon0050

Normal 4832627

Malicious 1175

Total 4833802

ip	malicious	total
117.239.43.91	1.0	1
118.189.162.204	7.0	7
120.192.73.121	7.0	7
122.194.229.39	193.0	193
122.56.185.22	3.0	3
134.87.157.129	0.0	1003825
142.104.6.1	0.0	840
142.104.64.196	0.0	250296
142.104.80.2	0.0	8
151.236.61.61	1.0	1
157.56.96.54	7.0	7
158.69.206.154	3.0	3
159.203.8.72	3.0	3
167.114.135.146	13.0	13
172.16.1.19	184.0	660662
172.16.1.23	255.0	58900
172.16.1.24	0.0	1828442
172.16.1.255	0.0	611
172.16.1.26	162.0	3057
172.16.1.28	11.0	580259
192.168.0.10	1.0	445975
192.168.0.9	0.0	365
192.95.25.79	3.0	3
192.99.2.8	2.0	2
199.182.221.110	2.0	2
203.127.19.42	12.0	12
203.177.11.195	11.0	11
207.210.46.249	1.0	1
208.180.114.12	9.0	9
208.86.164.244	5.0	5
208.86.164.250	7.0	7

216.58.193.110	14.0	14
218.65.30.134	15.0	15
222.124.18.147	142.0	142
224.0.0.22	10.0	10
224.0.0.252	18.0	18
24.122.14.21	1.0	1
255.255.255.255	1.0	1
37.182.235.207	6.0	6
5.101.66.252	24.0	24
59.63.166.83	21.0	21
62.210.189.248	4.0	4
72.38.129.202	3.0	3
79.7.213.30	6.0	6
89.248.162.160	5.0	5
89.36.213.153	2.0	2

Attack Scenarios for Day 3, 2016-12-16

Table A.12: Attack scenario steps for day 3

Day 3, 2016-12-16			
Seq	Attacks	Time	IPs
1	nmap scan from Attacker's machine against 206.12.96.149 (VM4)	09:05am	Src: Attacker's machine Des: 172.16.1.26 (VM4) (206.12.96.149)
2	"using zenmap" nmap scan from Attacker's machine against(VM4)	between 09:06-09:11am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.26 (VM4)

Table A.12 continued from previous page

Day 3, 2016-12-16			
3	Password cracking attack from Attacker's machine against VM4 on port 3389	between 09:11-09:12am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.26 (VM4)
4	Password cracking attack using ncrack from Attacker's machine against VM4 on port 3389	between 09:12-09:15am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.26(VM4)
5	Nmap scan from Attacker's machine against VM8	09:16am	Src: Attacker's machine Des: 172.16.1.24 (VM8) (206.12.96.143)
6	Brute force login attack from Attacker machine targeting VM8	between 09:17-09:25am based on screenshot's time	Src: Attacker's machine Des: 172.16.1.24 (VM8)
7	Login to VM8 from Attacker's machine	~9:25 -9:29am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
8	Download & Install netcat to VM8	between 09:30-09:32am based on screenshot's time	Src: 172.16.1.24 (VM8) Des: netcat repository
9	Start backdoor listening on port 4444 using ncat	~9:47-9:48am	VM 8
10	End ssh connection to 206.12.96.143	~9:52-9:53am	Src: Attacker's machine Des: 172.16.1.26 (VM4)

Network Statistics and Labelling for Day 3, 2016-12-16

Node: poseidon0049

Normal 522590

Malicious 1470

Total 524060

ip	malicious	total
104.37.196.219	4.0	4
114.251.141.82	12.0	12
114.44.94.170	1.0	1
121.18.238.104	111.0	111
134.87.157.129	0.0	159741
142.104.6.1	0.0	201
142.104.64.196	0.0	50115
142.104.80.2	0.0	27
155.133.82.13	9.0	9
159.192.251.198	1.0	1
172.16.1.20	3.0	18623
172.16.1.21	142.0	207
172.16.1.24	582.0	184512
172.16.1.255	0.0	215
172.16.1.27	3.0	53645
172.16.1.28	0.0	35080
183.240.20.81	1.0	1
192.168.0.10	0.0	20954
197.44.48.50	1.0	1
203.127.19.42	21.0	21
207.210.46.249	1.0	1
213.217.173.18	1.0	1
216.57.33.66	1.0	1
217.64.25.210	3.0	3
218.65.30.25	16.0	16
218.87.109.151	321.0	321
24.244.32.196	91.0	91
45.32.213.49	3.0	3

50.68.238.9	7.0	7
64.180.188.173	129.0	129
67.215.197.149	1.0	1
81.215.197.80	1.0	1
85.105.54.93	1.0	1
91.211.0.106	2.0	2
94.25.149.112	1.0	1

Node: poseidon0050

Normal 1549115

Malicious 618

Total 1549733

ip	malicious	total
134.87.157.129	0.0	268154
142.104.6.1	0.0	309
142.104.64.196	0.0	89488
142.104.80.2	0.0	2
158.69.206.154	1.0	1
159.203.8.72	2.0	2
172.16.1.19	22.0	180378
172.16.1.23	184.0	26747
172.16.1.24	0.0	627872
172.16.1.255	0.0	243
172.16.1.26	112.0	1143
172.16.1.28	5.0	209615
191.232.80.62	9.0	9
192.168.0.10	0.0	145372
192.168.0.9	0.0	115
192.95.25.79	1.0	1
203.127.19.42	4.0	4
207.210.46.249	3.0	3
218.65.30.25	1.0	1
221.194.44.219	28.0	28
24.122.14.21	1.0	1

24.244.32.196	33.0	33
45.32.213.49	7.0	7
45.63.8.221	14.0	14
58.218.204.181	168.0	168
59.63.188.30	2.0	2
64.180.188.173	19.0	19
72.38.129.202	2.0	2

Attack Scenarios for Day 4, 2016-12-19

Part 1:

In this phase, the hacker accesses the compromised VM via ssh, and attacked machines outside the cloud network using the compromised machine as stepping stone. First, the hacker scan the target network, and then attempt a DOS against it.

Table A.15: Attack scenario steps for day 4 part 1

Day 4, 2016-12-19			
Seq	Attacks	Time	IPs
1	Login to VM8 from Attacker's machine	~9:32-9:33am	Src: Attacker's machine Des: 172.16.1.24(VM8) (206.12.96.143)
2	Ping (from VM8) 142.104.64.202	~9:33 -9:35am	Src: 172.16.1.24 (VM8) Des: 142.104.64.202
3	Nmap scan from VM8 machine against 142.104.64.202	9:36am	Src: 172.16.1.24 (VM8) Des: 142.104.64.202
4	Synflood DOS attack from VM8 against 142.104.64.202 (failed)	~9:46 -9:56am	Src: 172.16.1.24 (VM8) Des: 142.104.64.202

Table A.15 continued from previous page

Day 4, 2016-12-19			
5	Nmap scan from VM8 machine against network range 142.104.64.194-206	9:56am	Src: 172.16.1.24 (VM8) Des: 142.104.64.194-206
6	Attempt to connect through a backdoor (using ncat) from VM8 to 142.104.64.202 on port 4444	~9:57 -10:00am	Src: 172.16.1.24 (VM8) Des: 142.104.64.202
7	End SSH connection to 206.12.96.143	~10:00 -10:01am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Part 2:

In this phase the attacker accesses the compromised VM and launches a failed DOS attack.

Table A.16: Attack scenario steps for day 4 part 2

Day 4, 2016-12-19			
Seq	Attacks	Time	IPs
8	Login to VM8 from Attacker's machine	~10:05-10:06am	Src: Attacker's machine Des: 172.16.1.24 (VM8)
9	Failed udp flooding DOS attack attempt from VM8	~10:07 -10:18am	Src&Des: 172.16.1.24 (VM8)
10	End SSH connection to 206.12.96.143	~10:17am	Src: Attacker's machine Des: 172.16.1.24 (VM8)

Network Statistics and Labelling for Day 4, 2016-12-19

Node: poseidon0049

Normal 1419617

Malicious 3667

Total 1423284

ip	malicious	total
101.78.190.246	2.0	2
106.116.21.143	1.0	1
106.37.240.6	84.0	84
121.18.238.104	186.0	186
121.18.238.114	163.0	163
121.18.238.98	116.0	116
121.185.218.81	1.0	1
134.87.157.129	0.0	480308
142.104.6.1	0.0	659
142.104.64.196	0.0	208677
172.16.1.20	66.0	138755
172.16.1.21	659.0	1735
172.16.1.24	1147.0	318978
172.16.1.255	0.0	365
172.16.1.27	61.0	193937
172.16.1.28	0.0	40725
182.100.67.4	72.0	72
183.148.166.254	1.0	1
185.11.83.45	18.0	18
185.158.112.18	6.0	6
186.210.101.145	1.0	1
188.65.97.136	6.0	6
189.218.226.71	1.0	1
190.146.239.131	1.0	1
190.82.81.59	1.0	1
192.168.0.10	0.0	37411
193.169.252.114	20.0	20
193.19.118.252	10.0	10

194.135.240.235	1.0	1
195.2.252.232	1.0	1
201.201.225.65	1.0	1
206.221.191.178	1.0	1
207.210.46.249	2.0	2
209.221.9.136	1.0	1
216.46.48.110	22.0	22
221.194.44.195	172.0	172
221.194.44.219	99.0	99
221.194.44.231	11.0	11
221.194.47.208	22.0	22
221.194.47.249	303.0	303
221.229.204.202	3.0	3
224.0.0.252	16.0	16
24.111.16.26	33.0	33
36.233.76.31	1.0	1
5.45.72.29	8.0	8
50.243.188.53	1.0	1
50.77.127.137	5.0	5
58.221.64.44	7.0	7
58.65.149.45	1.0	1
62.210.244.44	10.0	10
64.180.188.173	134.0	134
69.94.240.168	9.0	9
85.102.23.99	1.0	1
91.186.8.87	3.0	3
91.197.234.22	3.0	3
93.158.200.232	1.0	1
93.190.142.60	170.0	170
94.102.48.193	1.0	1
95.5.170.110	1.0	1

Node: poseidon0050

Normal 1057995

Malicious 665

Total 1058660

ip	malicious	total
103.7.85.53	7.0	7
106.37.240.6	71.0	71
134.87.157.129	0.0	189844
142.104.6.1	0.0	186
142.104.64.196	0.0	78878
142.104.80.2	0.0	3
169.38.72.169	7.0	7
172.16.1.17	3.0	3
172.16.1.19	18.0	133991
172.16.1.23	2.0	18447
172.16.1.24	0.0	396337
172.16.1.255	0.0	278
172.16.1.26	372.0	1514
172.16.1.28	2.0	110667
185.11.83.45	20.0	20
185.158.112.18	1.0	1
185.158.112.223	1.0	1
185.159.37.21	2.0	2
190.12.76.3	7.0	7
192.168.0.10	0.0	128136
192.168.0.9	0.0	108
192.99.2.8	2.0	2
195.2.252.232	1.0	1
199.182.221.110	1.0	1
206.108.0.133	1.0	1
207.210.46.249	1.0	1
209.221.9.136	3.0	3
209.89.58.50	8.0	8
216.46.48.110	7.0	7
221.194.44.224	7.0	7
221.194.47.249	11.0	11

24.111.16.26	16.0	16
24.122.14.21	1.0	1
5.101.66.252	3.0	3
58.221.64.44	5.0	5
72.38.129.202	1.0	1
93.190.142.60	84.0	84

A.2 Phase Two

The attacks in ISOT-CID phase two were divided into 6 rounds, averaging for 2 hours for each round, and spread over 6 different days. Moreover, the attackers performed and completed the attack scenarios independently. All the traces of these attacks were collected from all previously mentioned data sources but with lightweight agents only and no memory dump were collected.

The attacks in ISOT-CID phase 2 dataset simply consist of layer 7 and network layer DoS attacks launched remotely against the cloud infrastructure. Further attacks in phase 2 consist of exploiting input validation vulnerabilities in web applications, including cross-site scripting (XSS), SQL injection, and path/directory traversal.

The ISOT-CID phase 2 collection environment, procedure and detailed data types are published as a paper in a journal titled as “Hypervisor-Based Cloud Intrusion Detection through Online Multivariate Statistical Change Tracking”. In: IEEE Transactions on Information Forensics and Security, May 2018 (currently under review).

The benign IPs list in this Phase are :

142.104.64.201, 142.104.64.202, 172.16.1.21, 172.16.1.255,
 172.16.1.24, 172.16.1.20, 172.16.1.23, 172.16.1.10,
 172.16.1.28, 172.16.1.26, 172.16.1.19, 172.16.1.27,
 192.168.0.10, 192.168.0.8, 192.168.0.9, 255.255.255.255,
 142.104.64.196, 142.104.80.2, 142.104.6.1, 134.87.154.134,
 134.87.157.129, 142.104.191.194, 206.12.96.150,
 206.12.96.149, 206.12.96.143, 206.12.96.142, 206.12.96.141,
 206.12.96.239, 206.12.96.240, 206.12.59.162,
 206.12.48.43, 172.16.1.254, 172.16.1.17, 172.16.1.16,
 206.12.48.115, 2.89.202.164, 206.87.164.188, 51.218.248.166,
 188.49.184.140, 220.54.25.114, 37.105.194.65, 5.156.104.155,

51.36.227.160, 151.255.23.160, 94.48.53.155, 95.186.3.107,
 93.168.90.82, 93.168.144.25, 51.36.19.37, 51.39.8.69,
 24.244.32.170, 184.66.46.31, 129.237.123.95, 5.156.23.30,
 95.184.33.34, 93.169.127.140, 151.254.22.168, 147.143.196.4,
 51.39.153.205, 95.184.83.170, 134.87.154.71, 24.108.17.78,
 24.108.16.189, 5.156.239.222, 184.66.35.39, 95.186.109.44,
 90.148.165.218, 62.120.25.143, 188.55.218.54,
 95.185.185.142, 129.208.0.104, 95.187.159.184,
 188.50.228.245, 188.248.33.172, 93.169.29.93, 5.41.6.52,
 51.36.31.176, 51.36.39.186, 95.186.76.167, 151.255.78.159,
 51.39.202.109, 151.254.68.156, 78.95.126.150,
 51.36.217.50, 24.244.32.247, 134.87.164.132, 37.104.183.171,
 51.36.198.76, 95.184.34.83, 206.87.190.30, 5.246.50.54,
 176.45.160.91, 176.47.6.105, 188.48.138.54, 37.104.156.213,
 176.47.78.249, 93.168.64.12, 78.95.44.45, 51.218.252.241,
 51.39.162.99, 129.208.99.140, 37.104.214.214, 5.41.55.201,
 51.218.252.241, 51.36.89.58, 62.120.22.18, 188.49.40.63,
 5.108.143.27, 93.168.52.172, 93.168.61.191, 188.49.132.63,
 188.248.25.40, 129.208.142.220, 51.218.220.231,
 51.36.52.127, 94.98.250.78, 51.36.98.236, 184.151.231.50,
 184.66.39.200, 134.87.157.231, 147.143.196.5,
 147.143.196.33, 147.143.196.44, 147.143.196.39,
 51.255.40.63, 142.104.96.25, 184.66.37.31

A.2.1 Day 1, 2018-02-16

Attack Scenarios for Day 1

Table A.19: Attack scenario steps for day 1

Day 1, 2018-02-16			
Seq	Attacks	Time	IPs

Table A.19 continued from previous page

Day 1, 2018-02-16			
1	Access website	9:25am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10) (206.12.96.150)
2	Web scanning from Attacker's machine	9:28-10:05am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10)
3	Directory traversal attack (manual exploitation of path traversal vulnerability) in website (attack successful)	10:13-10:50 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10)
4	Download configuration file config	10:52 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10)
5	Download certificate file dhub.pem	11:01 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10)
6	Attack End		

Network Statistics and Labelling for Day 1**Node: poseidon0049**

Normal 1701631

Malicious 249555

Total 1951186

ip	malicious	total
10.40.9.248	1	1
100.10.87.118	1	1
101.226.196.136	392	392

104.236.182.105	1	1
106.186.20.183	1	1
107.170.225.228	1	1
107.170.232.10	1	1
109.248.9.10	1	1
109.248.9.248	4	4
110.175.231.172	1	1
111.185.20.246	1	1
111.37.128.94	1	1
112.119.212.136	1	1
112.217.150.112	3	3
113.214.26.106	1	1
113.64.147.37	1	1
114.151.128.77	802	802
115.238.245.2	743	743
115.238.245.6	386	386
117.81.149.10	1	1
118.122.5.91	1	1
118.174.147.62	3	3
118.174.99.14	1	1
118.193.31.110	1	1
118.212.143.46	14042	14042
118.241.121.191	20	20
119.102.47.166	1	1
120.14.15.84	1	1
121.14.7.244	27	27
121.153.30.40	21	21
121.18.238.39	502	502
121.208.190.238	3	3
121.99.136.95	1	1
122.226.181.165	744	744
122.226.181.166	392	392
123.116.67.154	20	20
123.249.12.230	1	1
124.166.102.224	1	1

124.232.130.157	1	1
125.139.163.67	1	1
125.205.81.159	1	1
125.66.152.219	2	2
134.119.213.127	1	1
137.226.113.10	1	1
137.74.4.61	14	14
139.162.112.248	1	1
139.162.118.185	1	1
139.162.75.112	3	3
139.60.161.163	1	1
14.134.3.4	1	1
141.212.122.16	1	1
141.212.122.26	1	1
141.212.122.27	1	1
142.104.6.1	0	637
142.104.64.201	0	81256
142.104.64.202	0	81531
142.104.80.2	0	12
142.165.95.151	11	11
144.217.181.221	10	10
146.0.77.142	1	1
148.72.168.40	1	1
149.56.121.19	11	11
154.66.246.186	15	15
155.94.88.122	3	3
155.94.88.186	3	3
156.204.248.41	14	14
159.203.119.68	185	185
159.89.141.168	2	2
163.131.120.48	1	1
163.172.174.126	1	1
171.234.216.170	1	1
171.235.55.193	1	1
172.16.1.17	0	6

172.16.1.19	0	184116
172.16.1.20	784	870
172.16.1.24	27734	746434
172.16.1.27	82214	713894
176.106.5.24	11	11
176.31.31.85	1	1
178.64.53.50	1	1
180.28.20.216	21	21
180.97.220.37	6	6
181.214.87.12	7	7
181.214.87.70	93	93
181.65.221.226	3	3
185.107.83.58	8	8
185.123.193.38	1	1
185.143.223.106	8	8
185.143.223.133	1	1
185.183.96.149	1	1
185.222.210.20	19	19
185.222.211.106	3	3
185.43.209.79	2	2
185.94.111.1	2	2
187.10.165.56	1	1
187.115.165.204	3	3
187.34.220.215	1	1
187.74.29.64	1	1
187.74.48.235	1	1
187.75.71.196	1	1
187.84.128.14	1	1
188.212.102.142	1	1
188.22.230.128	20	20
189.254.221.202	13	13
189.34.123.241	1	1
189.79.45.120	1	1
190.249.112.157	1	1
191.101.167.235	3	3

191.101.167.243	1	1
191.101.167.247	1	1
191.101.167.251	1	1
191.101.167.77	124	124
191.193.237.127	1	1
192.192.7.126	3	3
194.216.201.219	8	8
195.22.126.136	3	3
195.22.127.226	5	5
196.52.43.114	33	33
196.52.43.126	1	1
196.52.43.53	1	1
196.52.43.55	1	1
196.52.43.61	1	1
196.52.43.65	1	1
196.52.43.92	1	1
198.20.70.114	1	1
2.126.3.183	1	1
2.181.9.67	1	1
2.89.202.164	0	1096
200.1.216.136	2	2
200.148.35.202	1	1
200.57.3.4	2	2
201.148.118.115	11	11
201.208.203.37	2	2
205.209.159.19	1	1
206.108.0.133	11	11
206.87.164.188	0	483
208.100.26.228	2	2
209.126.136.5	1	1
212.237.45.193	1	1
212.28.94.242	1	1
212.92.115.237	6	6
213.80.147.253	1	1
216.243.31.2	1	1

218.189.25.36	1	1
220.211.148.25	1	1
220.226.22.216	82	82
221.194.44.211	533	533
221.194.47.221	314	314
221.194.47.233	492	492
221.194.47.236	515	515
221.194.47.239	531	531
221.194.47.243	506	506
221.194.47.245	496	496
222.238.61.171	6	6
223.100.102.88	1	1
23.105.70.77	1	1
23.16.123.57	105872	105872
255.255.255.255	2	2030
31.163.200.31	1	1
31.163.58.238	1	1
38.142.184.18	1	1
38.142.192.34	10	10
38.142.98.202	1	1
42.127.224.143	1	1
42.51.154.49	1	1
42.51.209.232	1	1
45.249.245.182	11	11
46.101.4.32	6	6
46.101.93.43	351	351
46.243.189.105	1	1
5.101.0.9	1	1
5.188.10.103	1	1
5.188.11.25	6	6
5.188.86.47	1	1
5.36.175.93	12	12
5.63.113.158	3	3
54.211.16.57	56	56
58.3.128.41	6	6

58.53.219.75	1	1
60.190.157.38	17	17
61.177.172.137	8027	8027
61.178.220.121	1702	1702
62.210.25.171	7	7
65.123.202.139	1	1
66.118.142.167	1	1
66.60.112.42	6	6
71.6.146.130	1	1
75.171.192.113	6	6
77.55.230.175	95	95
77.72.82.135	8	8
77.72.82.147	7	7
77.72.82.57	6	6
77.72.82.80	4	4
77.72.82.92	5	5
77.72.82.93	3	3
77.72.82.96	10	10
77.72.82.98	1	1
77.72.83.239	55	55
77.72.85.10	2	2
77.72.85.8	1	1
78.186.243.49	1	1
80.255.7.66	3	3
80.82.77.139	1	1
82.79.199.126	36	36
83.251.143.109	1	1
85.93.20.243	1	1
86.101.129.228	1	1
87.0.86.222	1	1
88.200.215.66	4	4
88.247.50.239	1	1
88.255.219.130	4	4
89.248.168.14	2	2
90.179.79.50	54	54

91.189.91.157	6	6
91.189.95.15	5	5
93.174.93.218	1	1
93.174.95.106	1	1
93.228.253.231	19	19
93.42.75.170	1	1
94.103.44.155	1	1
95.15.38.226	1	1
97.122.192.109	1	1

Node: poseidon0050

Normal 898076

Malicious 21917

Total 919993

ip	malicious	total
1.207.63.28	6	6
1.245.203.113	21	21
101.226.196.136	98	98
112.217.150.112	2	2
115.238.245.2	44	44
115.238.245.6	22	22
115.77.26.196	1	1
118.163.193.82	14	14
118.185.246.233	11	11
121.18.238.39	24	24
122.226.181.165	46	46
122.226.181.166	22	22
123.20.105.129	12	12
128.100.56.135	11	11
129.208.99.140	0	186
129.237.123.95	0	239
134.119.187.213	92	92
134.87.154.71	0	333
139.162.114.154	1	1

14.169.154.46	12	12
142.104.6.1	0	794
142.104.64.196	0	22
142.104.64.201	0	83398
142.104.64.202	0	83286
142.104.80.2	0	2
142.4.30.178	6	6
144.217.65.182	10	10
147.143.196.33	0	104
151.255.23.160	0	1661
152.74.52.100	42	42
158.69.125.231	11	11
159.89.141.168	2	2
159.89.33.22	5	5
164.90.161.7	11	11
172.104.108.109	10	10
172.16.1.17	0	6
172.16.1.19	2646	483279
172.16.1.23	7967	8820
172.16.1.24	0	233916
172.16.1.28	42	65
178.62.51.244	70	70
183.182.81.114	102	102
183.238.58.49	14	14
184.66.35.39	0	1784
184.66.39.200	0	660
185.43.209.79	2	2
187.115.165.204	2	2
188.49.184.140	0	389
195.22.127.226	12	12
198.143.133.154	6	6
198.143.133.155	1	1
198.143.133.156	6	6
198.143.133.158	9	9
198.50.139.209	10	10

203.93.215.81	1	1
206.108.0.133	22	22
206.87.164.188	0	317
208.100.26.228	1	1
208.73.56.29	11	11
208.81.1.244	18	18
218.201.250.77	43	43
219.147.95.246	1	1
221.194.44.211	22	22
221.194.47.233	22	22
221.194.47.236	22	22
221.194.47.239	22	22
221.194.47.243	24	24
221.194.47.245	22	22
222.129.241.81	14	14
222.186.101.212	85	85
24.108.16.189	0	431
24.108.17.78	0	1906
255.255.255.255	0	2028
37.104.214.214	0	710
46.101.93.43	250	250
5.101.0.9	1	1
5.41.55.201	0	1615
51.218.252.241	0	1881
51.36.227.160	0	361
58.53.219.75	1	1
61.177.172.137	8024	8024
61.178.220.121	1638	1638
62.210.25.171	6	6
66.249.93.41	21	21
66.249.93.43	16	16
66.249.93.45	6	6
70.28.63.31	12	12
77.55.230.175	98	98
78.61.195.216	6	6

87.109.46.5	7	7
87.109.46.7	14	14
87.81.139.154	21	21
90.225.49.17	27	27
92.222.40.57	14	14
93.168.144.25	0	244
93.168.90.82	0	294

A.2.2 Day 2, 2018-02-19

Attack Scenarios for Day 2

Table A.22: Attack scenario steps for day 2

Day 2, 2018-02-19			
Seq	Attacks	Time	IPs
1	Network scanning from Attacker's machine	10:27-10:29 am	Src: 142.104.79.224 Des: 172.16.1.27 (VM10) (206.12.96.150)
2	Network scanning from Attacker's machine	10:30-10:32 am	Src: 142.104.79.224 Des: 172.16.1.20 (VM7) (206.12.96.239)

Table A.22 continued from previous page

Day 2, 2018-02-19		
3	10:40-11:00 am	Src: 142.104.79.224
		Des: 1- 172.16.1.26 (VM4)
		(206.12.96.149)
		2- 172.16.1.20 (VM7)
		(206.12.96.239)
		3- 172.16.1.27 (VM10)
		(206.12.96.150)
		4- 172.16.1.27 (VM1)
		206.12.96.162
		5- 206.12.96.151

Network Statistics and Labelling for Day 2

Node: poseidon0049

Normal 604090

Malicious 11127

Total 615217

ip	malicious	total
10.204.155.105	1	1
101.85.45.20	12	12
103.60.13.34	2	2
107.170.232.10	1	1
109.248.9.10	1	1
113.57.197.162	14	14
115.238.245.2	369	369
115.238.245.4	382	382
115.238.245.6	12	12
116.226.51.28	52	52
119.249.54.217	52	52
120.63.209.69	1	1
121.170.154.59	40	40
121.18.238.125	475	475

122.226.181.166	15	15
123.1.153.231	7	7
125.212.217.214	1	1
125.212.217.215	1	1
125.64.94.201	1	1
129.208.0.104	0	1531
134.119.213.127	1	1
138.121.202.120	1	1
139.162.113.212	1	1
139.201.164.84	6	6
141.255.79.41	1	1
142.104.6.1	0	102
142.104.64.201	0	48000
142.104.64.202	0	48215
142.104.79.224	492	492
142.104.80.2	0	15
151.75.72.175	1	1
155.133.142.65	12	12
156.212.158.197	14	14
158.69.189.149	2	2
159.203.8.72	8	8
163.172.203.168	1	1
171.248.125.60	1	1
171.249.194.79	1	1
172.16.1.19	0	50850
172.16.1.20	563	615
172.16.1.24	3371	218256
172.16.1.27	1308	235600
177.68.14.229	1	1
181.214.87.12	6	6
181.214.87.70	65	65
182.101.50.66	1	1
183.203.220.234	14	14
185.107.83.58	4	4
185.143.223.127	1	1

185.143.223.167	2	2
185.143.223.201	1	1
185.158.212.22	5	5
185.222.210.20	13	13
185.222.210.30	1	1
185.37.227.86	5	5
187.11.18.239	1	1
187.39.91.186	1	1
188.166.57.143	1	1
189.110.99.150	6	6
190.180.66.188	1	1
190.206.103.13	1	1
190.69.19.242	1	1
191.101.167.235	3	3
191.101.167.246	2	2
191.101.167.250	1	1
191.101.167.251	1	1
191.101.167.77	73	73
191.19.233.72	1	1
191.207.222.27	16	16
194.9.51.137	5	5
195.22.127.170	3	3
196.52.43.109	6	6
196.52.43.62	1	1
196.52.43.94	1	1
196.52.43.97	1	1
197.82.209.224	1	1
198.245.51.213	8	8
199.182.221.110	7	7
2.89.202.164	0	797
201.42.182.213	1	1
206.117.25.90	1	1
206.87.164.188	0	494
208.81.1.244	8	8
209.124.66.13	5	5

209.126.136.4	1	1
210.237.211.53	1	1
210.86.225.59	92	92
212.237.45.42	1	1
212.92.127.11	2	2
212.92.127.12	3	3
218.144.207.79	20	20
219.66.114.117	1	1
221.194.47.221	933	933
221.194.47.233	493	493
221.194.47.243	528	528
222.186.138.72	1	1
223.202.66.130	20	20
27.223.103.18	1	1
36.189.242.19	1	1
36.235.169.207	1	1
37.59.116.24	5	5
38.142.119.122	1	1
5.101.0.9	1	1
5.188.11.25	1	1
5.188.62.53	1	1
5.188.86.140	4	4
51.218.252.241	0	542
51.255.40.63	0	61
51.36.217.50	0	1499
52.73.169.169	1	1
58.216.253.122	1	1
58.218.213.146	3	3
59.149.84.218	20	20
61.160.236.115	1	1
62.120.22.18	0	1251
65.123.202.139	1	1
66.249.81.180	155	155
66.249.81.182	699	699
66.249.81.184	288	288

71.6.146.130	1	1
76.27.83.105	6	6
77.72.82.135	6	6
77.72.82.147	4	4
77.72.82.57	3	3
77.72.82.80	3	3
77.72.82.92	2	2
77.72.82.93	2	2
77.72.82.96	3	3
77.72.85.10	2	2
77.72.85.17	1	1
77.72.85.23	1	1
77.72.85.8	1	1
78.186.118.55	1	1
78.186.245.120	1	1
82.102.173.70	1	1
82.79.199.126	12	12
85.105.26.166	1	1
85.93.20.244	40	40
85.93.20.34	5	5
86.59.210.119	15	15
89.120.94.226	42	42
89.248.162.171	1	1
89.248.168.14	2	2
91.189.91.157	3	3
91.189.94.4	4	4
93.171.128.149	21	21
94.177.199.217	156	156
94.177.77.15	2	2
94.231.108.215	5	5
95.185.185.142	0	1504

Node: poseidon0050

Normal 387495

Malicious 5043

Total 392538

ip	malicious	total
103.60.13.34	1	1
115.238.245.2	12	12
115.238.245.4	11	11
115.238.245.6	11	11
119.249.54.217	45	45
121.18.238.125	11	11
125.212.248.37	15	15
129.208.0.104	0	1443
129.237.123.95	0	317
134.87.154.71	0	75
134.87.157.231	0	225
142.104.6.1	0	65
142.104.64.196	0	37
142.104.64.201	0	48109
142.104.64.202	0	48314
142.104.80.2	0	10
144.217.164.10	7	7
144.217.65.182	7	7
147.143.196.44	0	1294
158.69.125.231	7	7
158.69.223.100	8	8
159.89.33.22	1	1
164.77.220.116	6	6
172.16.1.19	1888	201953
172.16.1.23	247	292
172.16.1.24	0	72894
172.16.1.28	23	36
181.211.21.186	26	26
186.251.122.27	5	5
188.248.33.172	0	3462
188.49.40.63	0	626

198.50.139.209	8	8
2.60.145.121	20	20
206.108.0.133	8	8
206.87.164.188	0	232
207.210.46.249	8	8
209.115.181.108	8	8
210.86.225.59	104	104
213.219.155.44	20	20
221.194.47.221	23	23
221.194.47.233	24	24
221.194.47.243	38	38
24.108.17.78	0	1383
24.244.32.247	0	374
5.108.143.27	0	1635
51.218.252.241	0	360
51.36.31.176	0	365
58.218.213.146	2	2
59.149.84.218	1	1
62.120.22.18	0	1296
62.120.25.143	0	39
66.249.81.29	586	586
66.249.81.3	261	261
66.249.81.31	436	436
66.249.93.34	206	206
66.249.93.61	560	560
66.249.93.63	375	375
70.78.101.15	24	24
90.148.165.218	0	1454
93.168.52.172	0	1372
93.168.61.191	0	239
95.186.76.167	0	1752

A.2.3 Day 3, 2018-02-20

Attack Scenarios for Day 3

1st attack scenario conducted by attacker A :

Table A.25: 1st attack scenario steps for day 3

Day 3, 2018-02-20			
Seq	Attacks	Time	IPs
1	Scan 206.12.96.150 from Attacker's machine using ZAP (XSS, SQL Injection, Path traversal etc)	~09:30-~10:00am	Src: Attacker's machine Des: 172.16.1.27 (VM10) (206.12.96.150)
2	Manual path traversal to download and upload files (was able to download shadow file and ssh keys)	~10:10-~10:22am	Src: Attacker's machine Des: 172.16.1.27 (VM10)
3	Manual XSS on blog posts and comments pages	~10:22-~10:46am	Src: Attacker's machine Des: 172.16.1.27 (VM10)
4	More manual path traversal to download and upload files (was able to download some system files like logs and configs and also the application config file containing the DB password)	~10:46-~11:01am	Src: Attacker's machine Des: 172.16.1.27 (VM10)

Table A.25 continued from previous page

Day 3, 2018-02-20			
5	Manual scan of the network trying to login to the database using the password acquired in the step above	~10:55-~11:01am	Src: Attacker's machine Des: 172.16.1.27 (VM10)

2nd attack scenario conducted by attacker B :

Table A.26: 2nd attack scenario steps for day 3

Day 3, 2018-02-20			
Seq	Attacks	Time	IPs
1	Manual brute force (trial and error) brute forcing SSH; goal try to find a host that has an account matching SSH key found in day 1 (through path traversal) Success at 9:26 am for target 206.129.239	9:21-9:26 am	Src: 23.16.123.57 Des: 1-206.12.96.150 2-206.12.96.151 3-206.12.96.152 4-206.12.96.153 5-206.12.96.230 6-206.12.96.235 7-206.12.96.236 8-206.12.96.237 9-206.12.96.239
2	SSH Login from Attackers machine Attempt to install programmes on target host; failed attempt due to lack of root capability	9:26 am	Src: 23.16.123.57 Des: 172.16.1.20 (VM7) (206.12.96.239)

Table A.26 continued from previous page

Day 3, 2018-02-20			
3	SSH Logout End SSH session	9:46 am	Src: 23.16.123.57 Des: 172.16.1.20 (VM7)
4	Launch Slowloris DOS attack against website	11-11:04 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10) (206.12.96.150)

Network Statistics and Labelling for Day 3**Node: poseidon0049**

Normal 956179

Malicious 40089

Total 996268

ip	malicious	total
1.238.209.149	1	1
103.207.39.219	1	1
104.236.145.154	1	1
106.6.74.187	1	1
109.236.86.40	1	1
110.235.130.96	4	4
110.85.163.160	1	1
112.92.209.23	1	1
115.85.121.241	1	1
116.25.248.71	1	1
117.84.101.195	4	4
117.90.144.234	4	4
118.122.5.91	1	1
118.91.34.173	1	1
119.249.54.217	476	476
119.250.147.219	1	1
120.11.231.107	1	1

120.188.72.199	2	2
121.137.41.110	25	25
122.183.251.123	9	9
122.226.181.165	778	778
123.150.200.121	6	6
123.21.12.74	3	3
123.249.27.95	1	1
125.66.152.219	1	1
126.111.92.179	1	1
134.119.213.127	2	2
139.162.126.103	1	1
139.201.164.169	6	6
14.232.125.105	1	1
141.212.122.104	1	1
141.212.122.153	1	1
141.212.122.208	9	9
141.212.122.227	1	1
141.212.122.228	1	1
142.104.6.1	0	97
142.104.64.201	0	61418
142.104.64.202	0	61755
142.104.80.2	0	2
154.85.179.103	513	513
159.203.8.72	8	8
159.65.138.195	1	1
159.65.163.58	1	1
159.65.27.228	1	1
163.172.203.168	3	3
172.16.1.19	0	142030
172.16.1.20	554	611
172.16.1.24	7193	378944
172.16.1.27	12351	325337
176.119.1.98	1	1
177.102.10.62	1	1
177.9.19.115	1	1

179.107.80.202	6	6
180.76.140.116	91	91
180.97.106.164	1	1
181.214.87.12	2	2
181.214.87.239	1	1
181.214.87.50	1	1
181.214.87.70	101	101
181.24.192.152	6	6
182.93.83.15	4	4
183.239.150.218	2	2
183.60.177.97	1	1
184.105.139.78	1	1
184.105.247.232	1	1
184.66.37.31	0	4450
185.107.83.58	6	6
185.143.223.126	3	3
185.143.223.127	2	2
185.169.231.3	1	1
185.178.142.85	1	1
185.209.0.163	1	1
185.210.218.98	11430	11430
185.222.210.20	12	12
185.222.210.29	1	1
185.222.211.106	3	3
185.230.124.35	1	1
185.56.81.51	1	1
185.92.73.149	3	3
185.94.111.1	2	2
187.10.76.245	1	1
187.34.75.144	1	1
188.49.132.63	0	1349
188.55.251.11	1	1
189.110.100.226	1	1
189.110.54.33	1	1
191.101.167.235	6	6

191.101.167.247	1	1
191.101.167.250	1	1
191.101.167.77	91	91
192.241.216.154	1	1
196.52.43.118	1	1
196.52.43.121	2	2
196.52.43.52	33	33
196.52.43.62	1	1
198.2.55.250	6	6
198.20.69.98	1	1
198.245.51.213	9	9
198.50.178.192	6	6
199.182.221.110	8	8
200.127.32.92	1	1
200.141.213.202	3	3
200.6.183.106	2	2
201.179.160.58	6	6
201.204.40.230	1	1
202.109.143.110	1	1
202.177.17.182	1	1
202.223.120.105	1	1
202.51.74.80	1	1
204.152.218.49	1	1
207.154.236.71	1	1
208.81.1.244	8	8
212.92.127.11	1	1
218.10.3.222	1	1
218.101.156.146	1	1
218.107.213.5	3	3
218.255.232.114	2	2
219.134.163.202	1	1
219.147.95.246	2	2
220.142.4.210	1	1
220.250.10.130	1	1
221.194.44.211	515	515

221.207.32.250	6	6
23.16.123.57	251	251
27.78.95.163	1	1
27.99.72.129	1	1
31.163.152.70	1	1
36.189.242.19	1	1
38.142.192.42	1	1
39.65.192.179	24	24
42.228.104.107	1	1
43.255.221.229	1	1
46.17.102.132	6	6
5.101.0.9	1	1
5.188.10.108	2	2
5.188.11.25	1	1
5.188.62.53	1	1
50.21.183.37	4	4
51.15.133.75	1	1
51.218.252.241	0	284
54.210.3.137	1	1
58.53.219.75	1	1
58.63.135.96	1	1
60.164.208.135	1	1
61.160.221.228	22	22
61.177.172.137	5152	5152
61.184.202.195	1	1
61.50.212.163	2	2
64.250.232.187	1	1
66.240.192.138	1	1
70.169.35.74	112	112
77.72.82.135	5	5
77.72.82.147	4	4
77.72.82.57	4	4
77.72.82.80	1	1
77.72.82.92	2	2
77.72.82.96	4	4

77.72.82.98	1	1
77.72.85.10	3	3
77.72.85.23	1	1
77.72.85.27	3	3
77.72.85.8	3	3
78.189.92.10	1	1
78.85.48.4	2	2
80.82.70.133	2	2
82.79.199.126	15	15
83.17.250.12	3	3
85.105.195.149	1	1
85.241.98.46	1	1
85.93.20.34	5	5
86.130.120.45	1	1
88.247.222.92	24	24
89.212.105.40	1	1
89.248.168.14	2	2
91.189.89.199	5	5
91.224.204.214	1	1
92.81.119.26	1	1
93.76.51.26	1	1
94.102.49.190	1	1
94.177.199.217	1	1
94.199.75.178	1	1

Node: poseidon0050

Normal 715215

Malicious 47267

Total 762482

ip	malicious	total
103.231.202.88	16	16
119.249.54.217	11	11
122.226.181.165	24	24
125.75.207.25	25	25

129.208.142.220	0	28
134.87.154.71	0	218
142.104.6.1	0	449
142.104.64.196	0	17
142.104.64.201	0	70822
142.104.64.202	0	71055
142.104.96.25	0	50
144.217.164.10	8	8
144.217.65.182	9	9
147.143.196.39	0	70
151.255.78.159	0	1745
154.70.110.211	8	8
158.69.125.231	9	9
158.69.223.100	8	8
172.16.1.19	11668	397879
172.16.1.23	10870	11301
172.16.1.24	0	180473
172.16.1.28	33	50
180.97.106.39	1	1
184.66.35.39	0	1654
185.162.248.242	52	52
185.210.218.98	265	265
185.94.188.130	1	1
198.50.139.209	8	8
198.71.236.46	14	14
203.156.18.130	14	14
206.108.0.133	8	8
206.214.12.247	12	12
206.87.164.188	0	62
207.210.46.249	8	8
209.115.181.108	9	9
211.25.101.194	20	20
212.124.187.121	24	24
216.227.214.95	14	14
218.107.213.5	16	16

221.194.44.211	11	11
23.16.123.57	10404	10404
24.108.17.78	0	194
31.167.217.100	17	17
42.7.26.88	11755	11755
5.101.0.9	1	1
50.62.77.204	14	14
51.36.39.186	0	247
51.36.89.58	0	84
51.39.202.109	0	1388
58.218.199.221	1	1
60.182.26.158	3	3
62.61.161.51	18	18
66.118.142.167	6	6
66.249.81.29	310	310
66.249.81.3	554	554
66.249.81.31	552	552
66.249.93.34	31	31
66.249.93.61	410	410
66.249.93.63	25	25

A.2.4 Day 4, 2018-02-21

Attack Scenarios for Day 4

Table A.29: Attack scenario steps for day 4

Day 4, 2018-02-21			
Seq	Attacks	Time	IPs
1	Brute force password cracking against website (Attack failed)	10:56-11:17am	Src:142.104.79.224 Des:172.16.1.27 (VM10) (206.12.96.150)

Network Statistics and Labelling for Day 4

Node: poseidon0049

Normal 1075900

Malicious 32996

Total 1108896

ip	malicious	total
106.75.18.144	1	1
107.170.227.111	27	27
111.125.248.216	1	1
111.198.184.2	12	12
111.56.12.19	1	1
111.93.186.246	1	1
113.122.39.138	1	1
114.199.223.66	1	1
114.35.77.143	24	24
115.238.228.33	1	1
115.238.245.8	420	420
115.52.75.86	4	4
117.27.137.57	87	87
117.70.100.251	1	1
119.180.247.16	1	1
120.96.122.65	22	22
122.117.99.77	1	1
122.226.181.164	807	807
122.226.181.166	391	391
123.150.200.121	4	4
123.249.27.95	1	1
125.212.217.215	1	1
129.82.138.44	1	1
134.119.213.127	1	1
136.169.253.43	3	3
139.162.79.111	1	1
14.134.18.222	1	1
14.45.92.228	1	1

142.104.6.1	0	44
142.104.64.201	0	51602
142.104.64.202	0	51279
142.104.79.224	1323	1323
142.104.80.2	0	19
142.252.252.35	1	1
152.250.166.87	1	1
159.203.8.72	7	7
159.65.34.76	1	1
159.65.58.39	1	1
162.208.100.134	1	1
162.223.89.57	3	3
162.243.146.188	1	1
163.172.74.24	15	15
164.132.91.12	1	1
172.16.1.17	0	7
172.16.1.19	0	123604
172.16.1.20	276	312
172.16.1.24	13839	468759
172.16.1.27	1993	395571
175.174.53.209	1	1
175.183.32.208	1	1
177.9.237.35	1	1
178.73.215.171	1	1
180.130.27.47	24	24
180.168.129.197	1	1
181.174.13.112	21	21
181.214.87.12	7	7
181.214.87.250	1	1
181.214.87.70	85	85
182.100.67.118	3	3
182.121.80.72	24	24
182.127.1.61	1	1
182.23.90.2	2	2
182.240.205.49	1	1

182.241.87.62	5	5
183.60.40.104	6	6
184.105.139.76	1	1
185.118.66.236	5	5
185.143.223.167	1	1
185.165.31.74	1	1
185.222.210.20	25	25
185.222.210.30	1	1
185.222.211.102	7	7
185.222.211.106	3	3
185.43.108.138	30	30
185.56.81.53	37	37
185.92.73.227	2	2
185.94.111.1	1	1
186.133.225.136	25	25
186.210.12.165	1	1
187.212.19.59	2	2
187.35.32.143	1	1
187.35.9.69	1	1
187.57.135.124	1	1
187.57.18.33	1	1
187.57.67.199	1	1
188.166.118.230	1	1
188.187.119.30	21	21
191.101.167.235	6	6
191.101.167.247	2	2
191.101.167.251	1	1
191.101.167.77	76	76
191.255.201.104	1	1
193.19.118.213	2	2
194.28.115.246	1	1
196.52.43.119	1	1
196.52.43.51	5	5
196.52.43.52	1	1
196.52.43.66	1	1

196.52.43.88	1	1
198.245.51.213	7	7
199.16.223.155	1	1
199.182.221.110	7	7
2.132.2.44	1	1
201.42.6.148	1	1
203.156.205.164	1	1
203.210.232.156	31	31
205.209.159.15	1	1
208.81.1.244	14	14
211.61.244.45	1	1
212.83.134.241	1	1
216.243.31.2	1	1
218.156.85.17	4	4
218.204.67.52	1	1
219.122.132.195	1	1
221.181.192.52	1	1
221.194.47.233	482	482
221.194.47.236	1012	1012
221.194.47.239	498	498
221.194.47.245	479	479
222.162.207.238	1	1
27.155.88.214	1	1
27.35.255.106	1	1
27.74.184.114	1	1
37.152.166.112	1	1
37.208.127.216	1	1
38.142.98.242	1	1
41.215.242.154	3	3
42.114.131.224	2	2
42.51.209.232	1	1
43.255.221.229	1	1
46.243.189.99	1	1
5.188.10.108	1	1
5.188.11.25	4	4

5.188.86.41	1	1
5.77.43.20	6	6
5.8.10.202	3	3
50.115.160.225	1	1
51.15.211.82	1	1
51.218.220.231	0	811
58.185.176.108	4	4
58.218.213.204	1	1
58.222.186.90	1	1
58.242.83.27	4955	4955
60.161.202.51	1	1
60.191.38.77	1	1
60.3.197.249	1	1
60.9.14.209	3	3
61.149.207.42	1	1
61.153.47.18	1	1
61.153.56.30	2	2
61.177.172.137	5494	5494
62.138.7.231	1	1
62.210.37.69	2	2
66.240.219.146	1	1
66.240.236.119	1	1
66.249.93.206	25	25
66.249.93.207	20	20
66.249.93.208	41	41
69.159.229.167	1	1
71.14.168.30	27	27
71.6.202.198	1	1
76.93.140.32	21	21
77.72.82.147	4	4
77.72.82.19	1	1
77.72.82.57	6	6
77.72.82.80	1	1
77.72.82.92	2	2
77.72.82.93	2	2

77.72.82.96	2	2
77.72.82.98	4	4
77.72.85.10	4	4
77.72.85.8	2	2
78.195.178.119	8	8
80.252.240.122	1	1
80.82.70.133	1	1
80.82.77.139	1	1
82.221.105.6	1	1
82.79.199.126	16	16
85.93.20.34	9	9
88.129.167.53	1	1
89.248.168.14	1	1
89.28.123.140	1	1
91.0.1.48	1	1
91.143.223.213	1	1
91.189.89.199	4	4
92.81.211.51	1	1
92.83.246.170	1	1
95.211.95.232	3	3
95.70.223.66	1	1

Node: poseidon0050

Normal 651908

Malicious 21570

Total 673478

ip	malicious	total
103.210.135.136	24	24
107.170.227.111	19	19
109.65.194.59	1	1
110.142.2.52	20	20
115.238.245.2	11	11
115.238.245.6	11	11
115.238.245.8	23	23

116.108.186.70	1	1
118.186.36.50	15	15
119.185.125.111	20	20
122.226.181.164	36	36
122.226.181.166	11	11
123.157.138.165	26	26
126.5.4.224	1	1
129.237.123.95	0	188
134.87.154.71	0	373
134.87.164.132	0	316
142.104.6.1	0	542
142.104.64.196	0	17
142.104.64.201	0	66184
142.104.64.202	0	65727
144.217.164.10	8	8
144.217.65.182	8	8
147.143.196.39	0	190
151.255.78.159	0	1619
158.69.125.231	8	8
158.69.223.100	8	8
159.65.58.39	1	1
172.16.1.17	0	9
172.16.1.19	587	355885
172.16.1.23	9658	10165
172.16.1.24	0	157606
172.16.1.28	32	50
179.27.99.22	18	18
182.100.67.118	2	2
184.66.35.39	0	134
186.61.59.117	24	24
188.49.40.63	0	424
197.86.149.70	6	6
198.50.139.209	8	8
202.124.205.225	173	173
203.210.232.156	27	27

206.108.0.133	8	8
206.87.190.30	0	167
207.210.46.249	8	8
209.115.181.108	8	8
210.121.164.121	14	14
221.194.47.233	13	13
221.194.47.236	22	22
221.194.47.239	34	34
221.194.47.243	11	11
221.194.47.245	24	24
24.108.16.189	0	123
24.108.17.78	0	22
37.104.183.171	0	1553
42.231.62.100	24	24
51.36.198.76	0	47
51.36.52.127	0	150
58.242.83.27	4884	4884
59.149.87.119	1	1
61.177.172.137	5589	5589
66.249.81.29	24	24
66.249.81.3	26	26
66.249.81.31	43	43
86.99.0.137	24	24
89.87.174.141	6	6
94.98.250.78	0	578
95.184.34.83	0	116
98.245.104.35	20	20

A.2.5 Day 5, 2018-02-23

Attack Scenarios for Day 5

1st attack scenario conducted by attacker A :

Table A.32: 1st attack scenario steps for day 5 conducted by attacker A.

Day 5, 2018-02-23			
Seq	Attacks	Time	IPs
1	SSH into 206.12.96.239 machine using key acquired beforehand	~09:45am	Src: 185.210.218.102 Des: 172.16.1.20 (VM7) (206.12.96.239)
2	Download and setup cryptominer	~09:45-~09:50am	Src: 172.16.1.20 (VM7) Des: cryptominer repository
3	Run cryptominer	09:51am	Src: 172.16.1.20 (VM7)
4	DNS amplification DOS using Saddam with UVic's DNS servers (142.104.6.1 and 142.104.80.2) as the amplifiers.	10:33-10:48am	Src: 1-185.210.218.100 2-142.104.6.1 3-142.104.80.2 Des: 172.16.1.19 (VM6) (206.12.96.240)

2nd attack scenario conducted by attacker B :

Table A.33: 2nd attack scenario steps for day 5 conducted by attacker B.

Day 5, 2018-02-23			
Seq	Attacks	Time	IPs
1	Visit website	09:20 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10) (206.12.96.150)

Table A.33 continued from previous page

Day 5, 2018-02-23			
	Two SSH login attempts (failed)		Src: 23.16.123.57
2	(trying to reuse credentials obtained in day 3)	9:25-9:30 am	Des: 172.16.1.20 (VM7) (206.12.96.239)
3	Launch HTTP flood DOS against Website	10:20-10:31 am	Src: 23.16.123.57 Des: 172.16.1.27 (VM10)

Network Statistics and Labelling for Day 5**Node: poseidon0049**

Normal 952603

Malicious 1537079

Total 2489682

ip	malicious	total
1.119.133.214	1	1
101.64.179.232	1	1
103.217.84.162	1	1
104.232.71.94	1	1
104.236.191.42	1	1
104.42.14.4	97	97
106.124.177.40	1	1
106.68.198.108	1	1
106.75.18.143	1	1
107.170.224.166	1	1
107.170.251.28	1	1
109.236.86.40	1	1
111.67.197.230	1	1
111.93.186.246	1	1
112.112.102.38	21	21

112.217.150.112	8	8
112.5.236.4	1	1
113.4.133.2	1	1
114.183.138.47	1	1
114.47.168.182	1	1
115.124.224.214	1	1
115.238.245.2	343	343
115.238.245.4	395	395
115.238.245.8	419	419
116.255.203.141	1	1
117.131.215.170	2	2
119.113.128.233	1	1
119.197.125.196	1	1
121.171.101.137	1	1
121.175.146.69	8	8
121.18.238.125	988	988
121.21.107.51	1	1
122.114.165.197	1	1
122.132.91.212	1	1
122.149.241.210	1	1
122.226.181.164	358	358
122.226.181.165	404	404
122.226.181.166	400	400
122.226.181.167	400	400
122.255.254.198	1	1
125.66.152.219	1	1
125.83.89.10	1	1
134.119.213.127	2	2
136.243.102.154	25	25
136.243.102.167	12	12
138.68.253.83	4	4
141.212.122.46	1	1
141.212.122.47	1	1
142.104.6.1	0	108
142.104.64.201	0	33968

142.104.64.202	0	33945
142.104.80.2	0	26
148.153.8.86	1	1
151.106.15.126	1	1
152.249.145.38	1	1
155.94.254.143	1	1
157.107.215.234	21	21
158.140.130.87	3	3
158.69.125.231	7	7
159.203.8.72	5	5
159.65.200.41	1	1
159.65.77.179	1	1
159.89.107.168	1	1
159.89.224.54	1	1
163.172.168.69	1	1
163.172.229.135	1	1
169.229.3.91	1	1
171.234.238.134	1	1
172.16.1.17	0	5
172.16.1.19	0	135816
172.16.1.20	8427	8612
172.16.1.24	19942	455220
172.16.1.27	610964	922401
172.16.124.112	1	1
174.142.39.145	5	5
176.9.0.89	1661	1661
176.9.8.174	3271	3271
177.102.181.171	1	1
177.94.23.182	1	1
179.225.245.203	1	1
179.27.155.90	84	84
179.98.27.120	1	1
180.97.82.3	1	1
181.211.93.114	1	1
181.214.87.12	1	1

181.214.87.221	27	27
181.214.87.249	10	10
181.214.87.70	91	91
182.120.30.133	1	1
184.105.247.212	1	1
184.66.35.39	0	1747
184.66.37.31	0	88
185.143.223.126	1	1
185.143.223.127	1	1
185.143.223.157	15	15
185.143.223.167	1	1
185.143.223.201	3	3
185.165.31.71	1	1
185.210.218.102	478	478
185.22.153.189	1	1
185.222.210.30	2	2
185.94.111.1	1	1
187.34.177.202	1	1
187.56.222.94	1	1
188.166.43.113	1	1
189.78.139.40	1	1
189.78.243.29	1	1
191.101.167.235	2	2
191.101.167.243	1	1
191.101.167.250	2	2
191.101.167.77	83	83
192.192.7.126	3	3
192.241.212.160	1	1
195.175.11.46	2	2
195.22.125.72	4	4
195.22.127.185	25	25
195.22.127.226	3	3
195.62.53.168	1	1
196.202.140.98	2	2
196.52.43.114	1	1

196.52.43.54	33	33
196.52.43.55	4	4
196.52.43.56	1	1
196.52.43.94	2	2
198.167.142.144	1	1
200.31.163.75	1	1
201.42.104.202	1	1
203.178.148.19	1	1
203.24.188.224	4	4
208.81.1.244	4	4
209.126.136.4	1	1
211.27.66.120	1	1
212.142.226.125	1	1
212.92.117.225	6	6
213.119.99.66	1	1
219.87.140.83	14	14
220.181.159.77	1	1
221.194.44.211	867	867
221.194.47.233	924	924
221.194.47.236	1021	1021
221.194.47.243	540	540
221.194.47.245	1580	1580
222.186.58.75	2	2
222.209.78.31	1	1
222.246.243.3	4	4
223.153.250.27	1	1
23.16.123.57	869825	869825
23.239.24.18	1	1
24.8.226.178	12	12
38.142.192.2	1	1
41.220.122.250	1	1
43.227.121.192	1	1
45.230.59.29	1	1
46.101.95.112	1	1
46.166.187.137	1	1

5.188.10.242	1	1
5.188.10.243	8	8
5.188.11.115	1	1
5.188.11.25	3	3
5.188.86.40	1	1
5.188.86.41	2	2
5.235.173.248	1	1
51.15.57.89	2	2
51.15.76.174	1	1
54.202.119.241	13	13
54.90.155.174	1	1
58.218.185.74	1	1
58.218.213.204	1	1
58.61.38.143	14	14
59.120.247.138	2	2
60.191.38.78	7	7
60.210.64.29	1	1
61.147.103.21	1	1
61.149.5.25	1	1
61.153.56.30	4	4
61.177.172.137	12735	12735
66.118.214.117	4	4
66.17.123.196	3	3
71.6.167.142	1	1
71.6.216.50	1	1
72.129.179.166	1	1
77.72.82.135	4	4
77.72.82.19	1	1
77.72.82.57	4	4
77.72.82.7	6	6
77.72.82.80	1	1
77.72.82.92	7	7
77.72.82.93	3	3
77.72.82.96	4	4
77.72.82.98	4	4

77.72.85.17	1	1
77.72.85.23	1	1
78.187.45.48	1	1
79.130.38.248	1	1
79.20.115.34	1	1
79.41.95.119	28	28
81.214.223.80	1	1
82.102.173.72	1	1
82.130.223.124	1	1
83.209.216.189	1	1
85.109.189.95	29	29
85.95.189.41	1	1
86.98.81.245	1	1
87.98.170.165	135	135
88.255.228.23	2	2
88.99.142.163	14	14
89.248.168.14	1	1
91.189.89.199	5	5
91.189.95.15	5	5
92.212.37.24	24	24
93.179.250.29	10	10
94.130.143.162	13	13

Node: poseidon0050

Normal 761051

Malicious 20181

Total 781232

ip	malicious	total
1.9.111.161	366	366
104.42.14.4	83	83
112.217.150.112	2	2
115.238.245.2	13	13
115.238.245.4	11	11
115.238.245.6	45	45

115.238.245.8	11	11
119.249.54.217	11	11
121.18.238.125	68	68
121.194.2.247	6	6
122.226.181.164	24	24
122.226.181.165	22	22
122.226.181.166	11	11
122.226.181.167	45	45
129.237.123.95	0	289
142.104.6.1	0	392
142.104.64.196	0	18
142.104.64.201	0	75315
142.104.64.202	0	76356
144.217.164.10	10	10
144.217.65.183	9	9
158.140.130.87	2	2
158.69.226.90	10	10
159.203.181.50	5	5
159.203.8.72	9	9
159.65.77.179	2	2
159.89.224.54	2	2
159.89.33.22	2	2
172.16.1.17	0	6
172.16.1.19	2808	421850
172.16.1.23	6079	6440
172.16.1.24	0	174620
172.16.1.28	37	55
176.47.78.249	0	2820
179.185.44.168	27	27
180.163.236.10	13	13
184.66.35.39	0	2063
188.248.25.40	0	4039
188.48.138.54	0	1303
192.241.157.239	5	5
198.143.158.82	18	18

198.143.158.83	1	1
198.143.158.85	1	1
198.50.139.209	9	9
199.195.253.124	5	5
199.66.200.40	10	10
206.108.0.133	9	9
207.179.149.113	9	9
207.210.46.249	9	9
218.214.180.198	1	1
219.156.233.44	2	2
221.194.44.211	47	47
221.194.47.233	45	45
221.194.47.236	47	47
221.194.47.239	11	11
221.194.47.243	22	22
221.194.47.245	72	72
23.16.123.57	1483	1483
31.167.217.100	7	7
5.246.50.54	0	1178
51.36.227.160	0	1608
51.36.98.236	0	90
61.160.254.19	1	1
61.177.172.137	6199	6199
66.249.81.226	707	707
66.249.81.252	315	315
66.249.81.254	185	185
66.249.93.34	342	342
66.249.93.61	568	568
66.249.93.63	247	247
78.242.160.71	29	29
87.56.189.237	24	24
93.168.64.12	0	1533
93.171.128.6	18	18